



The Land Bank
Buffalo Erie Niagara Land Improvement Corporation

Date Released: November 6, 2025

Bid: New construction of one single-family home at 68 Pulaski Street,
Buffalo, NY 14206

Deadline: **Wednesday, November 19th, 2025 at 9:00 AM**

Submit bids to: BENLIC
403 Main Street, Suite 602
Buffalo, NY 14203

Method of Submittal: Sealed Bid - US overnight mail, priority mail, 1st class mail, or
in-person (**email bids will not be accepted**)

CONTACT – QUESTIONS REGARDING WORK:

JOHN GOOD, CONSTRUCTION MANAGER
TELEPHONE #: 716-609-1473
EMAIL: J.GOOD@BENLIC.ORG

CONTACT – QUESTIONS REGARDING ALL OTHER:

MATT AZZANO, PROGRAM COORDINATOR
TELEPHONE #: 716-243-3996 EXT. 104
EMAIL: M.AZZANO@BENLIC.ORG

Bid Details:

Bidding contractors shall be expected to review the attached architectural plans and these directions in placing a bid for consideration. Review of these documents is the contractor and sub-contractor's responsibility and failure to do so may result in bids not being considered complete and being rejected. Failure to properly review plans will not be considered cause for a change order or additional payments.

General:

General Contractor shall be responsible for obtaining all necessary building permits, right of way permits, sewer and water tap and work permits, as well as any other permits deemed necessary by the City of Buffalo. Permit fees will be paid by BENLIC directly to the permitting agency.

General Site Requirements:

Contractor shall be responsible for installation of **Silt Socks** around all four sides of the construction site and around any street drains downstream of the construction site on Pulaski Street. Silt control measures shall be inspected regularly and replaced as necessary to ensure proper protection of off-site infrastructure.

Contractor shall establish a stabilized **construction entrance** to the site utilizing 1.5 to 3 inch stone. This entrance will be maintained with new stone as necessary for the duration of construction.

During work, the site shall be secured with a temporary (or permanent for duration of construction) 6-foot-tall chain link **fence** across the front of the lot parallel to the street. The other three sides shall be protected with minimum 4-foot-high snow fence with metal fence posts driven into the ground every 6 feet minimum. Fences shall be maintained in good condition and shall be in place during all non-working hours.

Upon clearing site and excavating for foundation work, no **dirt** or spoils will remain on site. All excavated dirt and spoils shall be removed from the site to a holding area (General Contractor's responsibility) or properly disposed of at a disposal site. Clearing of site shall include removal of sidewalks on the public right of way (permit required) and installation of detour and construction in progress signage to warn the public. Care shall be taken to prevent spillage of dirt or spoils in the roadway or any other public way. Any spillage shall be promptly cleaned up and disposed of properly.

At completion of construction, contractor shall install **new sidewalks** along the full width of the property within the public Right of Way, per City of Buffalo standards and Department of

Public Works requirements. Sidewalks shall also be installed on property, providing a path from the front porch to the public sidewalk

Grading of site at completion of construction shall consist of installation of 4 to 6 inches of clean topsoil over entire site graded to ensure proper drainage away from dwelling foundation. After final grading is complete entire site shall be hydroseeded with a quick growing grass mixture. Site shall be maintained by contractor until a minimum growth of 3 to 4 inches of grass over entire seeded area.

During construction contractor shall be responsible for site maintenance including **lawn mowing** or **snow removal** as necessary. All **utilities** will be put in contractors name and bills will be paid by contractor until dwelling is turned over to The Land Bank with all proper paperwork.

Minority Women owned Business Enterprise (MWBE) requirements:

Based upon the contractors bid amount, the contractor shall be required at minimum to meet a goal of 25% minority-owned business participation and 15% women-owned business participation. Companies hired to meet these goals must be New York State certified (County certification without state certification is not adequate).

Tracking of MWBE participation shall be verified utilizing the attached Affirmation of Income Payments to MBE/WBE and/or SDVOB form. This form shall be submitted on a quarterly basis as follows:

Quarter:	Form due date or next business day if on holiday or weekend:
January-March	April 15 th
April-June	July 15 th
July-September	August 15 th
October-December	January 15 th

The final reporting form must be submitted with the contractor's final retention pay application.

Radon Reduction:

Contractor shall follow section 302.1 of ANSI/AARST standards CCAH-2013 and install rough-in of a radon mitigation system per sections 402.1 through 901.1 as required in section 302.1.

At completion of construction, radon testing shall be performed by BENLIC. Contractor shall provide an alternate estimate for completion of Radon mitigation system in accordance with section 901, if necessary based on results of Radon testing.

Utility Hook-ups:

Contractor shall be responsible for utility hook-ups for sewer, water and electricity. This will include any work in the right of way and road, following all guidelines from the City of Buffalo, Buffalo Sewer Authority and Buffalo Water Authority including obtaining appropriate permits. Permit costs will be paid by BENLIC.

Toilet Facilities:

Contractor shall provide porta potty on site for use during construction.

Please write your total bid amount next to the corresponding property in both numbers and words.

(For example: “ \$10,250 ; Ten thousand two hundred and fifty Dollars”)

In case of discrepancy, amounts shown in words will govern.

1. New Construction of Single-Family Home at 68 Pulaski Street, Buffalo, NY according to attached building plans

Total bid amount: \$ _____; _____ Dollars

Total MBE amount: \$ _____; _____ Dollars

Total WBE amount: \$ _____; _____ Dollars

Business Name: _____

Mailing Address: _____

Federal EIN #: _____

Primary Contact: _____

Phone Number: _____

Email: _____

Total bid amount for all properties contractor is bidding on:

\$ _____; _____ Dollars

CONTRACTOR QUALIFICATIONS

In addition to filling out the bid sheet, attach the following:

- Provide three past customers as references
- Provide a brief description of your construction experience along with before and after photos of past projects if available
- Insurance Certificates
- EPA Lead Paint Contractor Certification
- Subcontractor Utilization Plan

BID DETAILS:

BENLIC is not responsible for delays occasioned by the U.S. Postal Service, the internal mail delivery system or any other means of delivery employed by the bidder. Similarly, BENLIC is not responsible for, and will not consider, any response which was received in our office later than the date and time stated above. Late bids shall not be considered and shall be returned to the late bidder. BENLIC reserves the right to reject any or all bids or waive any informality in a bid if it believes that the public interest will be promoted thereby. BENLIC may reject any bid, if, in its judgment, the business and technical organization, plant, resources, financial standing, or experience of the bidder justifies such rejection in view of the work to be performed. Any questions about the meaning, intent or specifications must be inquired into by the Bidder via mail, fax or email prior to the time set for the Bid Opening.

Bids will be submitted to the BENLIC Board of Directors for consideration and approval at a regularly scheduled meeting. Bid may be awarded to the lowest responsible bidder who, in the opinion of the corporation and approved by the Board, is qualified to perform the work required and who is responsible and reliable. The meeting is open to the public. In the case of tie bids, BENLIC will make the award based on priority factors. A bid tabulation summary of the received, reviewed and appropriate bids will be included in the minutes of BENLIC. Bidder agrees that his/her bid price remains effective for 120 days past the Deadline for Submittal.

The work cannot begin until contractor executes a BENLIC Standard Construction Contract and proves proper Certificate(s) of Insurance has been reviewed and approved by BENLIC.

Subcontractors may be used. All subcontractors will need to provide adequate insurance certificates. Job is not prevailing wage rate.

EQUAL EMPLOYMENT OPPORTUNITY

This organization will not discriminate against any employee or applicant for employment because of race, creed, color, national origin, sex, age, disability or marital status, will undertake or continue existing programs of affirmative action to ensure that minority group members are afforded equal employment opportunities without discrimination, and shall make and document its conscientious and active efforts to employ and utilize minority group members and women in its work force on State contracts.

This organization shall state in all solicitation or advertisements for employees that in the performance of the State contract all qualified applicants will be afforded equal employment opportunities without discrimination because of race, creed, color, national origin, sex disability or marital status.

At the request of the contracting agency, this organization shall request each employment agency, labor union, or authorized representative for a statement that it will not discriminate on the basis of race, creed, color, national origin, sex, age, disability or marital status and that such union or representative will affirmatively cooperate in the implementation of this organization's obligations herein.

Contractor shall comply with the provisions of the Human Rights Law, all other State and Federal statutory and constitutional non-discrimination provisions. Contractor and subcontractors shall not discriminate against any employee or applicant for employment because of race, creed (religion), color, sex, national origin, sexual orientation, military status, age, disability, predisposing genetic characteristic, marital status or domestic violence victim status, and shall also follow the requirements of the Human Rights Law with regard to nondiscrimination on the basis of prior criminal conviction and prior arrest.

NEW YORK STATE SALES AND LOCAL TAX EXEMPTION NOTE

Some materials for this project may be purchased tax-exempt. BENLIC is exempt from payment of New York State and local sales and use tax. BENLIC will furnish the winning bidder an Exempt Purchase Certificate (ST 119.1) as proof of its exemption. Personal property made part of the real property of project sites (that is materials, e.g. siding, shingles, gutters, windows, etc.) may be purchased exempt from such taxes provided that the winning bidder provide to his seller(s) properly completed Contractor Exempt Purchase Certificate(s) (ST 120.1). The cost benefit of exemption from such taxes is the benefit of BENLIC only. BENLIC seeks the lowest, responsible, and qualified bid. Bidders acknowledge that their bid herein contains pricing inclusive of this cost benefit.

MINORITY/WOMEN-OWNED BUSINESS ENTERPRISE UTILIZATION

This stabilization project will be funded by New York State Homes and Community Renewal (HCR). NYS-certified Minority- and Women-Owned Business Enterprises are encouraged to bid. To be considered certified as an M/WBE, the business enterprise must be listed on the NYS M/WBE directory. (This line is for HCR projects)

TERM OF PAYMENT

Pursuant to Contractor Agreement

BID AGREEMENT

The undersigned bidder offers and agrees, if this bid is accepted to enter into an agreement with the BUFFALO ERIE NIAGARA LAND IMPROVEMENT CORPORATION to complete all work as specified for the contract price and within the contract time indicated in accordance with these documents.

Bidder declares by submission of this bid, each bidder and each person signing on behalf of any bidder certifies, and in the case of a joint bid each party thereto certifies as to its own organization, under penalty of perjury, that to the best of his knowledge and belief:

- 1) The prices in this bid have been arrived at independently without collusion, consultation, communication, or agreement, for the purpose of restricting competition, as to any matter relating to such prices with any other bidder or with any competitor;
- 2) Unless otherwise required by law, the prices which have been quoted in this bid have not been knowingly disclosed by the bidder and will not knowingly be disclosed by the bidder prior to the opening, directly or indirectly, to any other bidder or to any competitor; and
- 3) No attempt has been made or will be made by the bidder to induce any other person partnership or corporation to submit or not to submit a bid for the purpose of restriction competition.

A bid shall not be considered for award nor shall any award be made where (a) (1) (2) and (3) above have not been complied with; provided however, that if in any case the bidder cannot make the foregoing certification, the bidder shall so state and furnish with the bid a signed statement which sets forth in detail the reasons therefor. Where (a) (1) (2) and (3) above have not been complied with, the bid shall not be considered for award nor shall any award be made unless the agency to which the bid is made, or his designee, determines that such disclosure was not made for the purpose of restricting competition that no person(s) other than those named herein are interested in this bid;

In submitting this bid, Bidder represent that he has examined the Instruction to Bidders; all other documents; that he has examined the proposed work site; that he has familiarized himself with all legal requirements (federal, state and local laws; ordinances; rules and regulations); that he as made such independent investigations as he deems necessary; he has satisfied himself as to all conditions affecting cost, progress or

performance of work; and that by signing this bid waives all rights to plead to misunderstanding regarding the same.

The Bidder further agrees that:

1. This bid shall remain open and may not be withdrawn for the time period set forth in the Instruction to Bidders.
2. That he accepts all terms and conditions in the Instruction to Bidders
3. The BUFFALO ERIE NIAGARA LAND IMPROVEMENT CORPORATION has the right to delete bid items and/or sections prior to award if the BUFFALO ERIE NIAGARA LAND IMPROVEMENT CORPORATION deems this to be in the BUFFALO ERIE NIAGARA LAND IMPROVEMENT CORPORATION'S best interest.
4. That upon acceptance of this bid, he will execute the agreement and will furnish the required contract insurance certificates (if not submitted with his bid) within a time period acceptable to the BUFFALO ERIE NIAGARA LAND IMPROVEMENT CORPORATION.

Respectfully Submitted on _____ 2025

By _____ (Signature of Bidder)

BUFFALO ERIE NIAGARA LAND IMPROVEMENT CORPORATION

TERMS AND CONDITIONS

- 1.** Bidder agrees to provide goods and/or services as described in this bid proposal to complete the Work, in a manner consistent with the highest standards of persons regularly engaged in providing such goods or services.
- 2.** Bidder shall be compensated at the rates and prices set forth in this bid proposal once approved by the BENLIC Board of Directors, for goods and/or services actually provided and only after receipt of an original invoice within thirty (30) days and after all services are rendered, inspected and accepted. Surcharges (i.e. fuel surcharges) shall NOT be allowed to be added to invoices. In no event shall the BENLIC's liability for payment to Bidder under this Contract, exceed the sum stated in the bid proposal and approved by the BENLIC Board of Directors.
- 3.** Bidder shall have seven (7) days from receipt of a Project Award Letter to provide BENLIC proof of insurance as detailed in the insurance requirements. Upon receipt of proof of insurance, BENLIC may issue a Notice and Order to Proceed Letter and Bidder shall within fifteen (15) days from receipt of same letter secure permits and start work. Bidder must forward copies of permits secured and notify BENLIC of the Start Date. From the Start Date, Bidder shall have forty-five (45) days to complete the work. Bidder shall immediately inform the BENLIC in writing by mail or facsimile transmission of any delay in providing goods and services to the BENLIC.
- 4.** BENLIC may, with or without cause, terminate Bidder's services, in whole or in part, immediately upon giving notice to Bidder. In such event Bidder shall be compensated and the BENLIC shall be liable only for payment for services already rendered.
- 5.** All records, if any, compiled by Bidder in providing services to BENLIC shall become and remain the property of BENLIC. Bidder may retain copies of such records for its own use.
- 6.** No portion of the work necessary to provide goods or services to BENLIC may be assigned or subcontracted without the prior written consent of BENLIC.
- 7.** Bidder agrees that it is an independent contractor and hereby waive all claims to benefits or privileges, if any available to persons as employees. Bidder shall comply, at Bidder's own cost and expense, with the provisions of all federal, state or local laws, ordinances, regulations or rules applicable to Bidder including without limitation, the N.Y.S. Labor Law and Worker's Compensation Law and any applicable license requirements.
- 9.** Bidder agrees that in providing goods or services to BENLIC, Bidder or any person working on Bidder's behalf, shall not, by reason of race, creed, color, sex, age, physical disability, national origin, genetic predisposition, carrier status, marital status or any other protected class, discriminate against, intimidate or harass any individual.
- 10.** Bidder agrees that, except for the amount, if any, of damage contributed to, caused by or resulting from the acts or omissions of BENLIC, Bidder shall indemnify, defend and hold harmless the BENLIC, its governmental sponsors-County of Erie, Cities of Buffalo, Lackawanna and/or Tonawanda, the Empire State Development Corporation, the Office of the New York Attorney General, their officers, employees and agents from and against any and all liability, damage, claims, demands, costs, judgments, fees, attorney's fees or loss arising directly or indirectly out of Bidder's acts or omissions or the acts or omissions of third parties under Bidder's direction and control.

BENLIC STANDARD INSURANCE **PROVISIONS**

CLASSIFICATION A:

Construction or Maintenance

BUFFALO ERIE NIAGARA LAND IMPROVEMENT CORPORATION STANDARD INSURANCE REQUIREMENTS

Vendor Insurance Classification A: Contracts Involving Construction or Maintenance

1. The contractor shall obtain, at its own cost and expense, the following insurance coverages with insurance companies licensed in the State of New York and shall provide a certificate of insurance as evidence of such coverages on the standard ACCORD Certificate, together with the corresponding policy endorsements.

- A. Commercial General Liability - with a minimum combined single limit of liability for Bodily Injury and Property Damage of \$3,000,000 per occurrence and \$3,000,000 general aggregate and \$3,000,000 Products – Completed Operation Aggregate. The coverage shall include:
 - Premises and Operations
 - Products and Completed Operations
 - Independent Contractors
 - Blanket Broad Form Contractual Liability (sufficient to cover all liability assumed under contracts with BENLIC)
 - Broad Form Property Damage
 - Explosion, Collapse and Underground Hazards (x, c, u) must NOT be excluded.Deductible must not exceed \$10,000.00
- B. Automobile Liability - with a minimum combined single limit of liability for Bodily Injury and Property Damage of \$1,000,000 each occurrence. The coverage shall include Owned, Hired, and Non-Owned Autos (Symbol "1" should be designated for Liability coverage on the Business Auto Policy). The deductible shall not exceed \$10,000.
- C. Excess "Umbrella" Liability - with a minimum limit of \$1,000,000 each occurrence / \$1,000,000 aggregate.
- D. Worker's Compensation and Employer's Liability - providing statutory coverage in compliance with the Worker's Compensation Law of the State of New York (Forms C-105.2; SI-12; GSI-105.2; or U-26.3). The deductible shall not exceed \$10,000.
- E. Disability Benefits - providing statutory coverage in compliance with the New York State Disability Benefits Law (Forms DB-120.1 or DB-155).

2. Commercial General Liability, Automobile Liability and Excess "Umbrella" Liability shall name the Buffalo Erie Niagara Land Improvement Corporation (BENLIC), and if applicable, HOUSING TRUST FUND CORPORATION, 38-40 State Street, Albany, NY 12207, and STATE OF NEW YORK, One Commerce Plaza, 99 Washington Ave, Albany, NY 12231-0001. Coverage should be provided on a primary and non-contributory bases. Designated Construction Project General Aggregate Limit Per Person Endorsement CG 2503 is required. Waiver of Subrogation is required on all lines in favor of BENLIC.

3. All policies in which BENLIC, and if applicable, HOUSING TRUST FUND CORPORATION and STATE OF NEW YORK is/are named as an additional insured(s) shall provide that:

- A. The insurance company or companies issuing the policies shall have no recourse against the BENLIC and/or HOUSING TRUST FUND CORPORATION and STATE OF NEW YORK for payment of any premiums or for assessments under any form of policy.
- B. The insurance shall apply separately to each insured (except with respect to the limit of the liability).


4. Prior to cancellation, non-renewal or material change of the above policies, at thirty (30) days advance written notice shall be given to the Executive Director of BENLIC with a copy to Counsel for BENLIC c/o John P. Sidd – Hancock Estabrook, LLP, 1800 AXA Tower I, 100 Madison Street, Syracuse, New York 13202, and the Agency requesting the certificate.

5. All certificates of insurance and policy endorsements shall be approved by the BENLIC Counsel prior to the inception of any work. Any request for a waiver of the above requirements shall be in writing to BENLIC Counsel c/o John P. Sidd – Hancock Estabrook, LLP, 1800 AXA Tower I, 100 Madison Street, Syracuse, New York 13202.

Failure to maintain coverage herein shall constitute a material breach of the contract and the Contractor shall suspend all work immediately upon such lapse in coverage.

68 PULASKI STREET - SINGLE FAMILY HOME

ISSUED FOR BID AND BUILDING PERMIT




68 PULASKI ST., BUFFALO NY
GOOGLE EARTH IMAGE

DRAWING INDEX


CS	68 PULASKI COVER SHEET	A-600	INTERIOR ELEVATIONS
V-100	68 PULASKI SURVEY (KHEOPS)	A-601	INTERIOR ELEVATIONS
SP101	SITE PLANS: SITE DEMOLITION, EROSION CONTROL PLAN & SITE LAYOUT PLAN	A-710	STAIR DETAILS
SP102	SITE PLANS: SITE GRADING PLAN & SITE UTILITIES PLAN	A-800	DOOR SCHEDULE AND DETAILS
SP201	SITE WORK DETAILS	A-801	WINDOW SCHEDULE AND DETAILS
SP202	SITE WORK SPECIFICATIONS	A-900	MILLWORK DETAILS
		A-901	SCHEDULES & TRIM DETAILS
S101	FOUNDATION / FLOOR PLANS	P-001	PLUMBING COVER SHEET
S102	SECOND FLOOR & ROOF FRAMING PLANS	P-100	SANITARY & VENT & PLUMBING PLANS
S201a	SPECIFICATIONS	P-101	DOMESTIC WATER PLUMBING PLANS
S201b	SPECIFICATIONS	P-102	PLUMBING RISER DIAGRAMS
S202	TYPICAL DETAILS	P-200	PLUMBING SPECIFICATIONS
S203	TYPICAL DETAILS		
S301	SECTION & DETAILS	M-001	MECHANICAL SPECIFICATIONS & DETAILS
S302	SECTION & DETAILS	M-101	MECHANICAL PLANS & SCHEDULES
A-001	GENERAL NOTES, LEGENDS & ABBREVIATIONS	E-001	ELECTRICAL SYMBOL LEGEND AND SCHEDULES
A-002	OUTLINE SPECS	E-002	ELECTRICAL DETAILS
A-003	OUTLINE SPECS	E-101	ELECTRICAL FLOOR PLANS
A-004	OUTLINE SPECS	E-201	ELECTRICAL SPECIFICATIONS
A-101	FIRST & SECOND FLOOR PLANS		
A-102	ATTIC & ROOF PLANS		
A-201	REFLECTED CEILING PLANS		
A-300	EXTERIOR ELEVATIONS		
A-301	EXTERIOR ELEVATIONS		
A-401	BUILDING SECTIONS		
A-402	BUILDING SECTIONS		
A-410	WALL SECTION / DETAILS / PARTITIONS		

SBL: 123.26-4-16
KAISERTOWN, LOVEJOY DISTRICT
N-3R RESIDENTIAL ZONING
REQUIRED
A LOT AREA: 1,800 SF MIN.
LOT WIDTH MIN/MAX: 30'/75'
C LOT COVERAGE: 70% MAX.
D IMPERVIOUS COVERAGE: 80% MAX.
E FRONT YARD (MIN/MAX) +/- 5' FROM
EST. FRONT YARD LINE
F BUILD TO PERCENTAGE: 65% MIN.
G SIDE YARDS TOTAL: 20% OF LOT WIDTH
H INTERIOR SIDE YARD: 3' MIN.
I REAR YARD: 20% OF LOT DEPTH
BUILDING HEIGHT: MAX. 3 STORIES/40'
FIN. GROUND FL. LEVEL: MIN/MAX: 0'/4'
GROUND FL. TRANSPARENCY: 20% MIN.
UPPER FL. TRANSPARENCY: 20% MIN.
MAIN ENTRANCE: FRONT, INTERIOR SIDE OR
CORNER SIDE FACADE

ACTUAL
LOT AREA: +/-2,565 SF (0.059 AC)
A LOT WIDTH: 30'
B LOT DEPTH: 85.5'
C HOUSE AREA (955 SF) + PAD (64 SF) = 1,019 SF
SITE COVERAGE: 39.7%
D IMPERVIOUS COVERAGE: 55.1%
E FRONT YARD: SEE SITE PLAN
F BUILD TO PERCENTAGE: 100%
G SIDE YARD TOTAL: 6'
H INTERIOR SIDE YARD: 3.0'
I REAR YARD: 17.1'
BUILDING HEIGHT: 32'-0"
FIN. GROUND FL. LEVEL: 2'-6"
GROUND FL. TRANSPARENCY: 21%
UPPER FL. TRANSPARENCY: 20%
MAIN ENTRANCE: FRONT FACADE



- FIRE RATED WALL CONSTRUCTION
1-HOUR
- ENTRY DOOR
- IMPERVIOUS SURFACE
- TRASH/RECYCLING TOTE
- EXISTING FENCE TO REMAIN
- PROPOSED FENCE
- 50 GAL. RAIN BARREL



2 FRONT ELEVATION - TRANSPARENCY 68 PULASKI STREET
1/8" = 1'-0"

SITE PLAN KEY

1 SITE PLAN - 68 PULASKI ST.
1/16" = 1'-0"

PROJECT NAME/LOCATION:
DESCRIPTION (NEW CONSTRUCTION)
68 PULASKI STREET - SINGLE FAMILY HOME

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876-7147

MEP
BUFFALO ENG., PC
4245 UNION RD.
BUFFALO, NY 14225
(716) 633-5598

BENJIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

HHL Architects
172 Allen Street, Buffalo, New York 14201
HHLArchitects.com


REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

DRAWING SUBMISSION STATUS: NOT FOR CONSTRUCTION | NOT FOR CONSTRUCTION | SCHEMATIC DESIGN | DESIGN DEVELOPMENT | CONSTRUCTION DOCUMENTS | ISSUED FOR CONSTRUCTION

DRAWING TITLE
COVER - 68 PULASKI ST.



SEAL

ISSUE DATE: 09.19.25
DRAWING NUMBER
CS




BOOK	434	PAGE	138	MAP	66188
------	-----	------	-----	-----	-------





SITE DEMOLITION & EROSION CONTROL PLAN

SITE LAYOUT PLAN



PLAN NOTES:

1. BOUNDARY AND TOPOGRAPHIC DATA SHOWN ON THIS DRAWING IS FOR INFORMATION ONLY. REFER TO SURVEYS PROVIDED BY THE OWNER. ENGINEER ASSUMES NO LIABILITY FOR UNFORESEEN CONDITIONS.
2. REFER TO ARCHITECTURAL DRAWINGS FOR ALL BUILDING DIMENSIONS & FEATURES, AND M.E.P. PLANS FOR UTILITY CONNECTIONS.

SITE DEMOLITION & EROSION
CONTROL NOTES:

1. SAWCUT & REMOVE PORTION OF CONCRETE/ASPHALT PAVT
2. NOT USED
3. NOT USED
4. NOT USED
5. NOT USED
6. PROTECT EXISTING PLANTING FROM DAMAGE THROUGHOUT CONSTRUCTION
7. 12" DIA COMPOST FILTER SOCK STAKED-IN
8. TEMPORARY STABILIZED CONSTRUCTION ENTRANCE

CONSTRUCTION NOTES:

1. CONCRETE PAVEMENT SECTION
2. NOT USED
3. 4-INCH MINIMUM TOPSOIL & LAWN SEED
4. PERVIOUS PAVER SECTION
5. STREET TREE: ACER RUBRUM -RED
SUNSET MAPLE 2.5" CAL. B&B -COORD.
LOCATION WITH UTILITIES
6. RAIN BARREL

COPYRIGHT© 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THIS
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.

REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.

UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 7209
PROVISION 2. OF THE NEW YORK
STATE EDUCATION LAW.

DRAWING SUBMISSION STATUS: ☒ NOT FOR CONSTRUCTION ☒ SCHEMATIC DESIGN ☒ DESIGN DEVELOPMENT ☒ CONSTRUCTION DOCUMENTS ☒ ISSUED FOR CONSTRUCTION

INSTRUCTION
DRAWING TITLE

SITE PLANS

REVISIONS AFTER ISSUANCE

NO.	DA
-----	----

DESCRIPTION

INSTRUCTION DO
ARCHITECT OF RECORD



PROJECT NAME/LOCATION: **DESCRIPTION [NEW CONSTRUCTION]**

DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI ST - SINGLE

FAMILY HOME



BENLIC DEVELOPMENT LLC
403 MAIN ST. SUITE 602
BUFFALO, NY 14203

PROJECT NUMBER: 2317.006
T.E. PROJ. NUMBER: 25-60


ISSUE DATE: 9.19.25
DRAWING NUMBER

SP101

EXPIRES: 10.31.25













- CONSTRUCTION NOTES:**
- STONE SIZE No.2 CRUSHER RUN.
 - LENGTH TO BE (20) FEET MINIMUM.
 - WIDTH TO BE (20) FEET MINIMUM.
 - THICKNESS NOT LESS THAN (6) INCHES AFTER STRIPPING TOPSOIL.
 - GEOTEXTILE FABRIC WILL BE PLACED OVER THE ENTIRE AREA AFTER TOPSOIL IS STRIPPED, AND PRIOR TO PLACEMENT OF STONE.
 - THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHT OF WAY. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHT OF WAY MUST BE REMOVED IMMEDIATELY.
 - WHEN EQUIPMENT WASHING IS REQUIRED IT SHALL BE DONE ON AN AREA WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.
 - PERIODIC INSPECTION AND MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN.





RESIDENTIAL SERVICE NOTES:

- THE SERVICE LATERAL MUST BE INSTALLED A MIN. OF 10" ABOVE THE BASEMENT FLOOR (IF APPLICABLE). WHERE LOCAL BUILDING ORDINANCES REQUIRE A GREATER DISTANCE, THE CONTRACTOR SHALL COMPLY TO THE MORE STRINGENT.
- PVC PIPE MATERIAL SHALL BE MANUFACTURED IN ACCORDANCE WITH THE LATEST REQUIREMENTS OF ASTM D-3033/D-3034. CAST-IRON PIPE MATERIAL SHALL BE EXTRA HEAVY ASTM A74-42.
- PURSUANT TO DISTRICT RULES AND REGULATIONS, PIPE SHALL BE LAID AT 1/4" PER FOOT GRADE. ANY VARIANCE MUST BE APPROVED BY THE DISTRICT MANAGER. IN NO CASE SHALL PIPE GRADE BE LESS THAN 1/8" PER FOOT.
- A MANUAL VALVE SHALL BE INSTALLED ON ALL BASEMENT DRAIN LINES.
- VENTS MUST BE INSTALLED IN LAWN AREAS, NOT IN SIDEWALK OR DRIVEWAY AREAS.
- SELECT BACKFILL IS REQUIRED UNDER PAVED AREAS.
- CONCRETE ENCASEMENT IS REQUIRED IF COVER DEPTH IS LESS THAN 4'-0" UNDER PAVED AREAS.
- MINIMUM DEPTH OF COVER SHALL BE 3'-0".



- GENERAL SITEWORK NOTES:**
- ALL WATERLINE, SANITARY SEWER AND OTHER WORK WITHIN THE R.O.W. SHALL BE IN ACCORDANCE WITH THE LATEST RULES AND REGULATIONS OF THE CITY OF BUFFALO CODE ENFORCEMENT OFFICE, DPW, BUFFALO WATER AUTHORITY, BUFFALO SEWER AUTHORITY, AND NEW YORK STATE DEPT. OF TRANSPORTATION SPECIFICATIONS.
 - WORK SHALL BE COMPLETED IN STRICT ACCORDANCE WITH ALL LOCAL CODES AND OSHA SAFETY RULES AND REGULATIONS.
 - VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS AT THE SITE. NOTIFY OWNER OF ANY DISCREPANCIES IN CONDITIONS SHOWN ON THE DRAWINGS PRIOR TO PROCEEDING WITH THE WORK.
 - CONTRACTOR SHALL ASCERTAIN THE LOCATION OF ALL UTILITIES PRIOR TO CONSTRUCTION SO THAT THIS WORK DOES NOT DISTURB EXISTING LINES AND/OR INSTALLATIONS. COORDINATE ALL WORK WITH THE APPLICABLE UTILITY COMPANIES.
 - CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS NECESSARY TO PERFORM THE WORK.



PROJECT NAME/LOCATION:
DESCRIPTION (NEW CONSTRUCTION)
68 PULASKI ST - SINGLE FAMILY HOME

PROJECT NUMBER: 2317 006
I.E. PROJ. NUMBER: 25-60

TREDO ENGINEERS
CIVIL/STRUCTURAL
7555 SENECA ST. #202
BUFFALO, NY 14210
(716) 876-7147

MEP
4245 UNION RD.
BUFFALO, NY 14225
(716) 633-5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 • F: 716.885.6414
hhlarchitects.com

DRAWING TITLE
SITE DETAILS

REVISIONS AFTER ISSUANCE
NO. DATE

ISSUES DATE: 9.19.25
DRAWING NUMBER
SP201

EXPIRES: 10.31.25

DIVISION 1 – GENERAL CONDITIONS

- A. ALL WORK SHALL COMPLY WITH THE LATEST ADDITION OF THE BUILDING CODE OF NEW YORK STATE, ACI BUILDING CODE (ACI-318), ASTM STANDARDS, NYSDOT, NYSDEC, AND ANY OTHER APPLICABLE CODES, RULES, AND REGULATIONS OF AGENCIES HAVING JURISDICTION INCLUDING BUT NOT LIMITED TO THE LOCAL MUNICIPALITY. WHERE CODES OVERLAP, COMPLY WITH THE MORE STRINGENT REQUIREMENTS.
- B. THE CONTRACTOR SHALL MAINTAIN INSURANCE AS WILL PROTECT HIM FROM LIABILITY UNDER WORKMAN'S COMPENSATION ACTS AND OTHER EMPLOYEE BENEFITS ACTS IN ACCORDANCE WITH THE LAWS OF NEW YORK STATE, AND FROM LIABILITY FOR DAMAGES BECAUSE OF BODILY INJURY, INCLUDING DEATH AND PROPERTY DAMAGE.
- C. CONTRACTOR IS TO REVIEW DRAWINGS AND EXISTING SITE CONDITIONS AND DIMENSIONS FOR SCOPE OF WORK INVOLVED. CONTRACTOR IS TO INCLUDE IN HIS PROPOSAL ALL ITEMS, MATERIALS, ETC., TO ACHIEVE THE DESIGN CONCEPTS SHOWN ON THE DRAWINGS. MINOR CHANGES IN THE WORK, DUE TO EXISTING CONDITIONS, WILL BE ALLOWED IF APPROVED BY THE ENGINEER BEFORE PROCEEDING.
- D. EXISTING DIMENSIONS SHOWN ARE APPROXIMATE; CONTRACTOR SHALL VERIFY ALL DIMENSIONS ON THE JOB. BOUNDARY SURVEY INFORMATION SHOWN IS FOR INFORMATION ONLY (REFER TO SURVEYS) PROVIDED BY THE OWNER. SITE PLANS MAY NOT HAVE BEEN PREPARED WITH THE BENEFIT OF RECENT TOPOGRAPHIC SURVEY AND UTILITY SEARCH AND ENGINEER ASSUMES NO LIABILITY FOR INFORMATION HEREON OR UNFORESEEN CONDITIONS BELOW GROUND. CONTRACTOR IS ADVISED TO CONTACT UNDERGROUND UTILITY LOCATION SERVICES PRIOR TO ANY EXCAVATION ACTIVITIES.
- E. CONTRACTOR IS TO INCLUDE IN HIS PROPOSAL ALL ADDITIONAL MATERIALS AND LABOR AS REQUIRED TO WORK AROUND EXISTING CONDITIONS AND PAY FOR ALL PERMITS AND INSPECTIONS REQUIRED.
- F. ALL WORKMANSHIP MUST BE IN THE BEST PRACTICE OF THE TRADE AS DETERMINED BY THE ENGINEER. ANY WORK NOT MEETING THESE STANDARDS WILL BE REJECTED.
- G. CONTRACTOR IS TO DISPOSE OF ALL DEMOLITION MATERIALS AND LEAVE THE WORK IN A READY TO USE CONDITION. STATE AND FEDERALS CODE REQUIREMENTS SHALL CONTROL THE DISPOSAL OF WASTE MATERIALS AND CONTAMINATED SOILS, IF ENCOUNTERED.
- H. CONTRACTOR IS RESPONSIBLE FOR LOCATING AND PROTECTING ANY EXISTING UTILITIES ON OR ADJACENT TO PROPERTY.
- I. THE CONTRACTOR MUST SUBMIT SHOP DRAWINGS AND/OR PRODUCT INFORMATION FOR ENGINEER REVIEW AND APPROVAL. MINOR ITEMS IN THE WORK ARE NOT SPECIFIED. CONTRACTOR IS TO USE QUALITY AND QUANTITY THAT IS STANDARD TO THE TRADE. FOR ALL PRODUCTS, WORK MUST COMPLY WITH THE MANUFACTURER'S STRICT RECOMMENDATIONS FOR INSTALLATION. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN INSTRUCTIONS AND TO THEN FOLLOW THEM.
- J. TYPICAL DETAILS APPLY TO ALL DRAWINGS AND SHALL BE USED EXCEPT WHERE OTHERWISE SHOWN OR NOTED.

DIVISION 2.1 – SITE CLEARING

- A. CONDUCT SITE CLEARING OPERATIONS TO ENSURE MINIMUM INTERFERENCE WITH ROADS, STREETS, WALKS, AND OTHER ADJACENT OCCUPIED OR USED FACILITIES. DO NOT CLOSE OR OBSTRUCT STREETS, WALKS OR OTHER OCCUPIED OR USED FACILITIES WITHOUT PERMISSION FROM AUTHORITIES HAVING JURISDICTION.
- B. PROVIDE PROTECTIONS NECESSARY TO PREVENT DAMAGE TO EXISTING IMPROVEMENTS INDICATED TO REMAIN IN PLACE.
- C. PROTECT IMPROVEMENTS ON ADJOINING PROPERTIES AND ON OWNER'S PROPERTY.
- D. PROTECT EXISTING TREES AND OTHER VEGETATION INDICATED TO REMAIN IN PLACE, AGAINST UNNECESSARY CUTTING, BREAKING OR SKINNING OF ROOTS, SKINNING OR BRUISING OF BARK, SMOTHERING OF TREES BY STOCKPILING CONSTRUCTION MATERIALS OR EXCAVATED MATERIALS WITHIN DRIP F. LINE, EXCESS FOOT OR VEHICULAR TRAFFIC, OR PARKING OF VEHICLES WITHIN DRIP LINE. PROVIDE TEMPORARY GUARDS TO PROTECT TREES AND VEGETATION TO BE LEFT STANDING.
- E. CAREFULLY REMOVE ITEMS INDICATED TO BE SALVAGED, AND STORE ON OWNER'S PREMISES WHERE INDICATED OR DIRECTED.
- F. REMOVE TREES, SHRUBS, GRASS AND OTHER VEGETATION, IMPROVEMENTS, OR OBSTRUCTIONS AS REQUIRED TO PERMIT INSTALLATION OF NEW CONSTRUCTION. REMOVE SIMILAR ITEMS ELSEWHERE ON SITE OR PREMISES AS SPECIFICALLY INDICATED. "REMOVE" INCLUDES DIGGING OUT AND OFF-SITE DISPOSING OF STUMPS AND ROOTS.
- G. CUT MINOR ROOTS AND BRANCHES OF TREES INDICATED TO REMAIN IN A CLEAN AND CAREFUL MANNER, WHERE SUCH ROOTS AND BRANCHES OBSTRUCT INSTALLATION OF NEW CONSTRUCTION. PROVIDE PROTECTION FOR ROOTS OVER 1-1/2 INCH DIAMETER THAT ARE CUT DURING CONSTRUCTION OPERATIONS. "CUT" CUT FACES WITH AN EMULSIFIED ASPHALT, OR OTHER ACCEPTABLE COATING, FORMULATED FOR USE ON DAMAGED PLANT TISSUES. TEMPORARILY COVER EXPOSED ROOTS WITH WET BURLAP TO PREVENT ROOTS FROM DRYING OUT; COVER WITH EARTH AS SOON AS POSSIBLE.
- H. STRIP TOPSOIL (REFERENCE DIVISION 2.2) TO WHATEVER DEPTHS ENCOUNTERED IN A MANNER TO PREVENT INTERMINGLING WITH UNDERLYING SUBSOIL OR OTHER OBJECTIONABLE MATERIAL. REMOVE HEAVY GROWTH OF GRASS FROM AREAS WHERE EXISTING TREES ARE INDICATED TO REMAIN. LEAVE EXISTING TOPSOIL IN PLACE WITHIN DRIP LINES TO PREVENT DAMAGE TO ROOT SYSTEM. STOCKPILE TOPSOIL IN STORAGE PILES IN AREAS INDICATED OR DIRECTED. CONSTRUCT STORAGE PILES TO PROVIDE FREE DRAINAGE OF SURFACE WATER. COVER STORAGE PILES, IF REQUIRED, TO PREVENT WIND EROSION.
- I. CLEAR SITE OF TREES, SHRUBS AND OTHER VEGETATION, EXCEPT FOR THOSE INDICATED TO BE LEFT STANDING. COMPLETELY REMOVE STUMPS, ROOTS, AND OTHER DEBRIS PROTRUDING THROUGH GROUND SURFACE. USE ONLY HAND METHODS FOR GRUBBING LINES INDICATED TO REMAIN. PROVIDE PROTECTION FOR PLANT DEPRESSIONS CAUSED BY CLEARING AND GRUBBING OPERATIONS WITH SATISFACTORY SOIL MATERIAL. UNLESS FURTHER EXCAVATION OR EARTHWORK IS INDICATED, PLACE FILL MATERIAL IN HORIZONTAL LAYERS NOT EXCEEDING 6 INCHES DEPTH, AND THOROUGHLY COMPACT TO A DENSITY EQUAL TO ADJACENT ORIGINAL GROUND.
- J. REMOVE EXISTING ABOVE-GRADE AND BELOW-GRADE IMPROVEMENTS AS INDICATED AND AS NECESSARY TO FACILITATE NEW CONSTRUCTION. REMOVAL OF ABANDONED UNDERGROUND PIPING OR CONDUIT INTERFERING WITH CONSTRUCTION IS INCLUDED UNDER THIS SECTION.
- K. REMOVE WASTE MATERIALS AND UNSUITABLE OR EXCESS TOPSOIL FROM OWNER'S PROPERTY.

DIVISION 2.2 – EARTHMOVING

- A. SLOPED SIDES OF EXCAVATIONS ARE TO COMPLY WITH THE LOCAL CODES, ORDINANCES AND REQUIREMENTS OF AGENCIES HAVING JURISDICTION. SHORE AND/OR BRACE WHERE SLOPING IS NOT POSSIBLE BECAUSE OF SPACE RESTRICTIONS OR STABILITY OF MATERIAL EXCAVATED. MAINTAIN SLOPES AND SLOPES OF EXCAVATIONS IN SAFE CONDITION UNTIL COMPLETION OF BACKFILLING.
- B. PROVIDE MATERIALS FOR SHORING AND BRACING, SUCH AS SHEET PILING, UP-RIGHTS, STAINLESS, AND CROSS BRACES, AS REQUIRED, MAINTAIN SHORING AND BRACING IN EXCAVATIONS REGARDLESS OF TIME PERIOD EXCAVATIONS WILL REMAIN OPEN. EXTEND SHORING AND BRACING AS EXCAVATION PROGRESSES.
- C. BARRICADE OPEN EXCAVATIONS OCCURRING AS PART OF THIS WORK AND POST WITH WARNING LIGHTS. OPERATE WARNING LIGHTS DURING HOURS FROM DUSK TO DAWN EACH DAY AND AS OTHERWISE REQUIRED.
- D. PREVENT SURFACE WATER AND SUBSURFACE GROUND WATER FROM FLOWING INTO EXCAVATIONS AND FROM FLOODING PROJECT SITE AND SURROUNDING AREA. NO MATERIALS SHALL BE PLACED IN WATER OR ON FROZEN GROUND.
- E. MATERIALS:

1. GENERAL FILL: SAND, GRAVEL, FRABLE EARTH OR CLAYS OF LOW PLASTICITY, FREE OF ORGANIC MATERIALS, FROZEN MATERIAL, TRASH, MASONRY, RUBBLE, CONCRETE, DEBRIS AND FREE OF STONES HAVING A DIMENSION OF 4-INCHES OR GREATER
2. CONCRETE SAND: NYSDOT ITEM 703-04
3. GROUT SAND: NYSDOT ITEM 703-04
4. GRAVEL: NYSOT ITEM 703-02, TYPE 1
5. STRUCTURAL FILL: NYSOT ITEM 304-2.02, TYPE 2 OR TYPE 4
6. CRUSHED STONE: NYSOT ITEM 703-02, BLEND OF TYPE 1 AND TYPE 2, WITH 100% PASSING 1.5", 90-100% PASSING 1", 25-60% PASSING 3/4", 0-10% PASSING #4, AND 0-5% PASSING #6.
7. WOVEN GEOTEXTILE FABRIC: MIRAFI 500X
8. NON-WOVEN GEOTEXTILE FABRIC: MIRAFI 140N
9. TOPSOIL: NATURAL, FERTILE, FRABLE GRANULAR SOIL CHARACTERISTIC OF PRODUCTIVE SOILS IN THE VICINITY, UNIFORM IN COMPOSITION AND TEXTURE, FREE FROM SUBSOIL, CLAY LUMPS, STONES, ORGANIC MATERIAL, TOXIC OR HAZARDOUS SUBSTANCES, AND ANY MATERIAL TWO INCHES OR MORE IN GREATEST DIMENSION
10. SLAG NOT PERMITTED

- F. REMOVE EXISTING SURFACE SOIL MATERIAL, INCLUDING VEGETATION, TOPSOIL AND LOOSE BOULDERS TO A MINIMUM DEPTH OF 12 INCHES BELOW EXISTING SURFACE GRADE OR AS REQUIRED TO COMPLY WITH CROSS-SECTIONS, ELEVATIONS, AND GRADES AS INDICATED. THE EXPOSED SURFACE SOIL MUST BE PROOFROLLED WITH A MINIMUM 10-TON STATIC ROLLER, IN THE PRESENCE OF THE SOILS TESTING AGENCY. WHERE UNCONTROLLED FILL, SOFT, LOOSE OR YIELDED MATERIAL EXISTS, THESE AREAS MUST BE UNDERGTA A MINIMUM OF 2'-0". TESTING AND INSPECTION OF THE UNDERCUT SUBGRADE, BY THE SOILS TESTING AGENCY, MAY REQUIRE FURTHER UNDERCUTTING ON SOME AREAS, DEPENDING ON THE TYPE AND NATURE OF FILL/UNUSABLE MATERIAL EXPOSED.
- G. EXCAVATE TRENCHES TO THE UNIFORM WIDTH REQUIRED FOR PARTICULAR ITEM TO BE INSTALLED AND SUFFICIENTLY WIDE TO PROVIDE AMPLE WORKING ROOM. PROVIDE 1'-0" MINIMUM CLEARANCE ON BOTH SIDES OF PIPE OR CONDUIT, BUT NOT LESS THAN 3'-0" TOTAL TRENCH WIDTH. EXCAVATE TRENCHES TO DEPTH INDICATED OR REQUIRED. CARRY DEPTH OF TRENCHES FOR PLACING TO ESTABLISH INDICATED FLOW LINES AND INVERT ELEVATIONS. GRADE BOTTOMS OF TRENCHES AS INDICATED, NOTICING TO PROVIDE SOUND BEARING FOR ENTIRE BODY OF PIPE. REMOVE UNSTABLE, SOFT, AND UNSUITABLE MATERIALS AT THE SURFACE UPON WHICH PIPES ARE TO BE LAID AND BACKFILL WITH CLEAN SAND OR PEA GRAVEL TO INDICATED LEVEL. FILL UNEVENNESS WITH TAMPED SAND BACKFILL. DIG BELL HOLES AT EACH PIPE JOINT TO RELIEVE THE BELLS OF ALL LOADS AND TO ENSURE CONTINUOUS BEARING OF THE PIPE BARREL ON THE FOUNDATION. DO NOT BACKFILL TRENCHES UNTIL ALL CORRECTIONS HAVE BEEN MADE AND BACKFILLING AUTHORIZED BY THE ARCHITECT/ENGINEER. USE CARE IN BACKFILLING TO AVOID DAMAGE OR DISPLACEMENT OF PIPE SYSTEMS.
- H. CONTRACTORS WILL TAKE EVERY PRECAUTION DURING FINAL STAGES OF EXCAVATION TO PREVENT DISTURBANCE OF THE NATURAL SOIL AT PROPOSED SUBGRADE ELEVATIONS. SUCH PRECAUTIONS SHALL INCLUDE, BUT NOT BE LIMITED TO, KEEPING EQUIPMENT OFF FINAL SUBGRADE DURING THE LAST SEVERAL FEET OF EXCAVATION, USING EXCAVATING BUCKETS WITHOUT TEETH, PLACING CONCRETE MUD MATS BELOW FOUNDATIONS AND DEMOLITION EXCAVATIONS.
- I. SET GRADE STAKES WHERE SPOT ELEVATIONS ARE SHOWN, AT BREAKS IN GRADE, ALONG DRAINAGE "SWALES" AND AS OTHERWISE REQUIRED TO CORRECTLY GRADE THE AREA ACCORDING TO ELEVATIONS SHOWN ON PLANS. MAXIMUM SPACING OF STAKES TO BE 50 FEET ON CENTER. GRADE NOT OTHERWISE INDICATED SHALL BE UNIFORM SLOPES OR SLOPES BETWEEN POINTS WHERE ELEVATIONS ARE GIVEN OR BETWEEN SUCH POINTS AND EXISTING FINISHED GRADES. ABRUPT CHANGES IN SLOPES SHALL BE ROUNDED. ALL NEW GRADES, OTHER THAN GRADES FOR PAVED AREAS, TO BE WITHIN PLUS OR MINUS 0.50" OF GRADES INDICATED ON DRAWINGS OR IN SPECIFICATIONS. GRADE FOR PAVED AREAS, BOTH SUBGRADE AND BASE COURSES, TO BE PLUS OR MINUS 0.25" OF INDICATED GRADES.
- J. COMPACTION OF FILL: UNFORMLY SPREAD EACH LAYER, MOISTEN OR DRY AS REQUIRED FOR OPTIMUM MOISTURE CONTENT; AND THEN COMPACT SO DENSITY OF THE COMPACTED MATERIAL MEETS OR EXCEEDS 95% MAXIMUM DRY DENSITY EXCEPT IN NON-LOADED GRASSED AREAS WHICH NEED NOT EXCEED 90%.
- K. REPAIR TO PROPER GRADE ANY SETTLEMENT OF SLAB, PAVEMENT, UTILITY, STRUCTURE, OR LAWN, ADVERSELY AFFECTED BY SETTLEMENT, WITHIN ONE YEAR AFTER FINAL ACCEPTANCE AT NO EXPENSE TO THE OWNER.

DIVISION 2.3 – TEMPORARY EROSION AND SEDIMENT CONTROL

- A. FURNISH, INSTALL, INSPECT, MAINTAIN, AND REMOVE SOIL EROSION AND SEDIMENT CONTROL MEASURES AS SHOWN ON THE CONTRACT DOCUMENTS OR AS ORDERED BY THE ENGINEER DURING THE LIFE OF THE CONTRACT. COORDINATE WITH THE SOIL EROSION AND SEDIMENT CONTROL FEATURES SPECIFIED ELSEWHERE IN THE CONTRACT DOCUMENTS TO THE EXTENT PRACTICAL TO ASSURE EFFECTIVE AND CONTINUOUS SOIL EROSION AND SEDIMENT CONTROL THROUGHOUT THE CONSTRUCTION AND POST CONSTRUCTION PERIOD IN ACCORDANCE WITH REFERENCE STANDARDS NOTED IN DIVISION 1 AND "NEW YORK STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL", SOIL AND WATER CONSERVATION SOCIETY, EMPIRE STATE CHAPTER, IN THE EVENT OF CONFLICT BETWEEN THESE

SPECIFICATION REQUIREMENTS AND POLLUTION CONTROL LAWS, RULES, REGULATIONS OR PERMIT CONDITIONS BY OTHER FEDERAL OR STATE OR LOCAL GOVERNMENT AGENCIES, THE MORE RESTRICTIVE LAWS, RULES OR REGULATIONS SHALL APPLY.

B. MATERIALS:

1. STONE FILLING: STONE FILLING SHALL MEET THE REQUIREMENTS OF NYSDOTSS SECTION 620-2.02 STONE FILLING, LIGHT.
2. GEOTEXTILE: GEOTEXTILES SHALL MEET THE REQUIREMENTS OF NYSDOTSS SECTION 207-2 MATERIALS. UV SENSITIVE GEOTEXTILES SHALL BE PROTECTED FROM EXPOSURE TO SUNLIGHT DURING TRANSPORT AND STORAGE.
- C. PERIMETER SEDIMENT CONTROLS SHALL BE INSTALLED PRIOR TO PERFORMING GRUBBING, EXCAVATION, AND BORROW OR FILL OPERATIONS.
- D. TEMPORARY SEED AND MULCH
1. SEED SHALL BE RYEGRASSES (ANNUAL OR PERENNIAL) OR CEREAL GRASSES SUITABLE TO THE AREA AND AS A TEMPORARY COVER WHICH WILL NOT COMPETE WITH THE GRASSES SOWN LATER FOR PERMANENT COVER.
2. THE CONTRACTOR SHALL APPLY SEED AND MULCH ON DISTURBED AREAS CONSISTENT WITH THE APPROVED PROJECT SCHEDULE.
3. PRIOR TO THE APPLICATION OF SEED, ALL AREAS WHERE COMPACTION HAS OCCURRED SHALL BE SCARIFIED. THE SEED BED SHALL BE LOOSE AND FRABLE FOR EASY SEED RETENTION.
4. RYEGRASSES SHALL BE SPREAD AT A RATE OF 3.5 G/M² TO UNIFORMLY COVER THE GROUND. CEREAL GRASSES SHALL BE SPREAD AT A RATE OF 11.2 G/M² TO UNIFORMLY COVER THE GROUND. SEEDS SHALL BE EVENLY DISTRIBUTED BY ANY METHOD OF SOWING THAT DOES NOT INJURE THE SEEDS IN THE PROCESS OF SPREADING.
5. MULCH SHALL BE SPREAD IMMEDIATELY FOLLOWING APPLICATION OF SEED. MULCH SHALL BE SPREAD UNIFORMLY IN A CONTINUOUS BLANKET AT AN APPROXIMATE RATE OF 4 T/YM². MULCH MAY BE SPREAD BY HAND, MECHANICAL SPREADERS, OR BLOWERS. MULCH AND SEED SHALL NOT BE PLACED SIMULTANEOUSLY, EXCEPT IN THE CASE OF HYDROSEEDING.

E. TEMPORARY SILT FENCE

1. SILT FENCE SHALL BE LISTED IN THE NYSDOT APPROVED LIST. A SILT FENCE ASSEMBLY SHALL CONSIST OF SILT FENCE, GEOTEXTILE, POSTS, AND FASTENERS AND MAY INCLUDE MESH SUPPORT AND FASTENERS WITH THE APPROVED LIST.
2. POSTS SHALL BE DRIVEN INTO THE GROUND. POSTS SHALL BE EITHER WOOD, METAL, OR CONCRETE. SOFTWOOD POST SHALL BE 38 MM X 89 MM SOFTWOOD POST SHALL BE HEAVY-DUTY, FASTENERS SHALL BE 1/2" OR 1" SHAPED IN CROSS SECTION, WITH A MINIMUM WEIGHT OF 2 KG/M. POSTS SHALL BE A MINIMUM OF 1.2 M LONG AND SHALL BE SPACED INCONSISTENT WITH THE MATERIAL SELECTED AND AS INDICATED IN THE NYSOT AND APPROVED LIST.
3. GEOTEXTILE AND ANY MESH SUPPORT (IF APPLICABLE) SHALL BE PLACED ON THE UPSTREAM SIDE OF THE POSTS. FOR THOSE SILT FENCE ASSEMBLIES ON THE NYSOT APPROVED LIST THAT REQUIRE A MESH SUPPORT SHALL CONSIST OF 14 GAUGE (WV) WELDED WIRE MESH WITH A MINIMUM OF 150 MM X 150 MM OPENING OR POLYMERIC MESH. ALL MESH SUPPORT SHALL BE A MINIMUM OF 750 MM IN HEIGHT.
4. GEOTEXTILE SHALL BE FASTENED TO EACH POST IN NO LESS THAN 4 LOCATIONS WITH APPROVED FASTENERS. THE MESH SUPPORT SHALL BE FASTENED TO EACH POST AT THE TOP, BOTTOM, AND TWO ADDITIONAL EVENLY SPACED LOCATIONS, OR BY A CONTINUOUS CORDED ATTACHMENT ALONG THE TOP OF THE ASSEMBLY. FASTENERS SHALL BE HEAVILY-DUTY, STAPLES, HOG RINGS, THE WIRES, OR ANY OTHER FASTENER COMPATIBLE WITH THE POST MATERIAL.
5. GEOTEXTILE AT THE BOTTOM OF THE DITCH, THE PIPE DIMENSION SHALL BE CONSISTENT WITH 150 MM. THE TRENCH SHALL BE BACK FILLED WITH THE EXCAVATED SOIL AND THE SOIL COMPACTED BY TAMPING.
6. ANY GEOTEXTILE OR MESH SPICES NECESSARY FOR FENCE ERECTION SHALL BE CONTINUOUS BETWEEN TWO POST SECTIONS.

TEMPORARY COMPOST FILTER SOCK –12-INCH DIA MINIMUM BY FILTREXX OR ACCEPTED EQUIVALENT. STAKE-IN PERMANUFACTURER'S RECOMMENDATIONS.

G. DRAINAGE STRUCTURE INLET PROTECTION

1. DRAINAGE STRUCTURE INLET PROTECTION SHALL BE PLACED WHERE SHOWN IN THE CONTRACT DOCUMENTS AND CONSTRUCTED IN ACCORDANCE WITH THE STANDARD DETAIL SHEETS.

H. CONSTRUCTION ENTRANCES

1. CONSTRUCTION ENTRANCES SHALL BE PLACED WHERE SHOWN IN THE CONTRACT DOCUMENTS AND CONSTRUCTED IN ACCORDANCE WITH THE STANDARD SHEETS. CONSTRUCTION ENTRANCES SHALL CONSIST OF A GEOTEXTILE, CRUSHED STONE OR GRAVEL AND, IF NECESSARY, A DRAINAGE PIPE TO BE INSTALLED IN THE CENTER OF THE DITCH. THE PIPE DIMENSION SHALL BE CONSISTENT WITH THE MODIFIED SOIL EROSION AND SEDIMENT CONTROL PLAN APPROVED BY THE ENGINEER. ALL AREAS CUT OR FILLED AND NOT STABILIZED BY THE SEDIMENT CONTROL PLAN APPROVED BY THE ENGINEER OR AREAS CUT OR FILLED AND NOT STABILIZED BY THE SEDIMENT CONTROL PLAN APPROVED BY THE ENGINEER SHALL BE COVERED WITH AN EROSION CONTROL TREATMENT (TEMPORARY MULCH, TEMPORARY SEED AND MULCH, ETC.) AND SHALL BE INCLUDED IN THIS PAY ITEM.
2. WASHING OR FLOWING OF SEDIMENT ONTO THE RIGHT-OF-WAY, ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO THE RIGHT-OF-WAY SHALL BE REMOVED IMMEDIATELY. IN THE EVENT THE ENTRANCE IS NO LONGER PERFORMING PROPERLY (I.E. THE ENTRANCE AGGREGATE BECOMES CLOGGED WITH SEDIMENT), THE CONTRACTOR SHALL TOP-DRESS THE ENTRANCE WITH ADDITIONAL COURSE AGGREGATE MATERIAL.

J. TEMPORARY PIPE INLET/OUTLET PROTECTION, SILT FENCE

1. TEMPORARY PIPE INLET/OUTLET, SILT FENCE, SHALL BE PLACED WHERE SHOWN IN THE CONTRACT DOCUMENTS AND CONSTRUCTED IN ACCORDANCE WITH THE STANDARD DETAIL SHEETS.

DIVISION 2.4 – PAVING

- A. FINE GRADE AND PROOF ROLL SUBGRADE UNDER PAVEMENT IN ALL AREAS IN ACCORDANCE WITH NYSOT SPECIFICATIONS 203-3.14.
- B. BITUMINOUS PAVING MATERIALS
1. SUB-BASE COURSE – STRUCTURAL FILL PER DIVISION 2.2
2. ASPHALT BINDER: SEE DETAIL
3. ASPHALT TOPPING: SEE DETAIL
4. TACK COAT: SEE DETAIL
5. BITUMINOUS PAVEMENT SEALER: A COAL TAR EMULSION MATERIAL SPECIFICALLY FORMULATED TO SEAL ASPHALT CONCRETE PAVEMENT. ADD FOUR POUNDS OF GROUT SAND PER GALLON OF SEALER AND PAVEMENT SEALER. TWO COATS OF SEALER UNIFORM AT A MINIMUM TOTAL COVERAGE OF 0.18 GALLONS PER SQUARE YARD PER COAT. ALLOW A MINIMUM OF 24 HOURS FOR CURING PRIOR TO CHECKING SEALED PAVEMENT FOR VEHICLE USAGE.

E. BITUMINOUS PAVING PLACEMENT

1. ALL COURSES: ROLL EACH COURSE WITH 10 TON ROLLER OR EQUIVALENT. COMMENCE ROLLING HINDRANCE FREE AND CONTINUE UNTIL EDGE OF EACH COURSE IS THOROUGHLY COMPACTED. AFTER WHICH GRADUALLY ADVANCE TO THE CROWN. CONTINUE ROLLING UNTIL THE LAYER HAS BECOME THOROUGHLY COMPACTED AND IS TRUE TO GRADE AND CROSS SECTION.
2. BASE COURSE: PLACE ON DRY SUBGRADE IN MAXIMUM LIFTS OF 4" WITH A MINIMUM COMPACTION OF 95% OF MAXIMUM DRY DENSITY. REMOVE SUBGRADE MATERIAL, WHICH BECOMES MIXED WITH BASE COURSE AND RECONSTRUCT. GRADE TOLERANCE: PLUS OR MINUS 3/8" FROM INDICATED GRADES.
3. ASPHALT TOP COURSE: DO NOT INSTALL ASPHALT PAVING OVER WET BASE COURSE OR IF AMBIENT TEMPERATURE IS BELOW 40 DEGREES F. IN ANY COURSE PLACEMENT, THE SURFACE SHALL BE DETAILED. WHERE PAVEMENT ABUTS CURBS, CONCRETE WALKS, OR EXISTING PAVEMENT, APPLY A LIBERAL APPLICATION OF TACK COAT MATERIAL. CHECK WITH 10' STRAIGHT EDGE AND CORRECT ALL DEPRESSIONS AND HIGH AREAS GREATER THAN 1/4". FORM OR CUT ALL PAVEMENT EDGES TO CLEAN, SHARP LINES OR RADII, AS INDICATED. COMPACTION FOR WEARING COURSE SHALL BE MINIMUM OF 92% OF LABORATORY SPECIMEN DENSITY.
- F. PAVEMENT SEALER, REQUIRED FOR ALL PARKING AREAS AND LOTS (NOT ON ROADWAYS): ALLOW PAVEMENT TO WEATHER A MINIMUM OF FOUR WEEKS PRIOR TO SEALING. CLEAN SURFACE OF DIRT AND DEBRIS. APPLY SEALER TO WEATHERED PAVEMENT IN TWO COATS OF SEALER UNIFORM AT A MINIMUM TOTAL COVERAGE OF 0.18 GALLONS PER SQUARE YARD PER COAT. ALLOW A MINIMUM OF 24 HOURS FOR CURING PRIOR TO CHECKING SEALED PAVEMENT FOR VEHICLE USAGE.

DIVISION 2.5 – WATER SERVICE PIPING

- A. SUBMIT PRODUCT DATA FOR VALVES, WATER METER, AND IDENTIFICATION DEVICES ALONG WITH SHOP DRAWINGS FOR PRECAST CONCRETE VALVE PITS AND METER PIT, INCLUDING FANGES AND COVERS. ALL MATERIALS AND PRODUCTS USED WITHIN THE SAME SYSTEM SHALL BE PROVIDED BY THE SAME MANUFACTURER.
- B. SUBMIT RECORD DRAWINGS AT PROJECT CLOSEOUT OF INSTALLED WATER SERVICE PIPING AND PRODUCTS.
- C. SUBMIT MAINTENANCE DATA FOR VALVES AND WATER METER, FOR INCLUSION IN OPERATING AND MAINTENANCE MANUALS.
- D. WATER SERVICE PIPING QUALITY CONTROLS SHALL COMPLY WITH REQUIREMENTS OF UTILITY SUPPLYING WATER TO THE PROJECT.
- E. WATER VALVES SHALL BE PROPERLY PREPARED, STORED AND HANDLED PRIOR TO INSTALLATION.
- F. COORDINATE CONNECTION TO PUBLIC WATER MAIN WITH UTILITY COMPANY, INTERIOR WATER DISTRIBUTION PIPING AND WITH OTHER UTILITY WORK.
- G. PIPE AND FITTING MATERIAL SHALL BE COMPATIBLE WITH EACH OTHER. WHERE MORE THAN ONE TYPE OF MATERIAL OR PRODUCT IS INDICATED, SELECTION IS INSTALLER'S OPTION.
- H. COPPER WATER TUBE 2 INCHES AND SMALLER: ASTM B 88; TYPE K, SEAMLESS, ANNEALED TEMPER. COPPER FITTINGS: ANSI B16.22, WROUGHT-COPPER, SOLDER JOINT PRESSURE TUBE. INSTALL IN ACCORDANCE WITH CDA "COPPER TUBE" HANDBOOK.
- I. COUPLINGS: IRON BODY SLEEVE ASSEMBLY FABRICATED TO MATCH OUTSIDE DIAMETERS OF PIPES TO BE JOINED. SPEC: ASTM A 126, CLASS B, GRAY IRON FLOWERS: ASTM A 47, GRADE 32510 OR ASTM A 536 DUCTILE IRON, GASKETS: RUBBER. BOLTS AND NUTS: ASTM A118, FINISH: ENAMEL PAINT.
- NONRISING STEM GATE VALVES, 2 INCHES AND SMALLER: MSS SP-80; BODY AND SCREW BONNET OF ASTM B 62 CAST BRONZE, WITH CLASS 125S TREADED ENDS, SOLID WEDGE, NONRISING COPPER-SILICON ALLOY STEM, BRASS PACKING-GUARDED PACKING IMPREGATED AND MALLEABLE IRON HANDWHEEL. COMPLY WITH AWWA C600. USE BRONZE CORPORATION STOPS AND VALVES, WITH ENDS COMPATIBLE TO PIPING, FOR 2-INCH AND SMALLER INSTALLATION. USE THREADED AND FLANGED END VALVES FOR INSTALLATION IN PITS AND INSIDE BUILDING. INSTALL BURIED VALVES WITH STEM POINTING UP AND WITH CAST-IRON CURB BOX.

- K. VALVE BOXES: CAST-IRON BOX HAVING TOP SECTION AND COVER WITH LETTERING "WATER", BOTTOM SECTION WITH BASE OF SIZE TO FIT OVER VALVE AND BARREL APPROXIMATELY 5 INCHES IN DIAMETER, AND ADJUSTABLE CAST-IRON EXTENSION OF LENGTH REQUIRED FOR DEPTH OF BURY OF VALVE. PROVIDE A STEEL TEE-HANDLE OPERATING WRENCH WITH EACH VALVE BOX. WRENCH SHALL HAVE TEE HANDLE WITH ONE POINTED END, STEM OF LENGTH TO OPERATE VALVE, AND SOCKET FITTING VALVE OPERATING NUT.
- L. CURB STOPS: BRONZE BODY, GROUND KICK PLUG OR BALL, AND WIDE TEE HEAD, WITH INLET AND OUTLET TO MATCH SERVICE WATER MATERIAL.

- M. SERVICE CLAMPS AND CORPORATION STOPS: PROVIDE A COMPLETE ASSEMBLY, INCLUDING SERVICE CLAMP, CORPORATION STOP, AND BOLTS AND NUTS. THE CLAMP AND STOP SHALL BE COMPATIBLE WITH THE PIPE OR DUCTILE IRON SERVICE CLAMP. SERVICE CLAMP: CAST IRON OR DUCTILE IRON WITH GASKET AND AWWA C800 THREADED OUTLET FOR CORPORATION STOP, AND THREADED END STRAPS. CORPORATION STOPS: BRONZE BODY AND NO BOLD KEY TO BE USED. WITH AWWA C800 THREADED OUTLET AND END TO MATCH SERVICE PIPING MATERIAL. MANIFOLD: COPPER WITH TWO TO FOUR INLETS, AS REQUIRED, WITH ENDS MATCHING CORPORATION STOPS, AND OUTLET MATCHING SERVICE PIPING. COMPLY WITH MANUFACTURER'S INSTALLATION INSTRUCTIONS. INSTALL BURIED CURB STOPS WITH HEAD POINTED UP AND WITH CAST-IRON CURB BOX.
- N. PROVIDE ANCHORAGES FOR TEES, PLUGS AND CASPS, BENDS, CROSSES, VALVES, AND HYDRANT BRANCHES.
1. CLAMPS, STRAPS, AND WASHERS: ASTM A 575, STEEL
2. RODS: ASTM A 575, STEEL
3. ROD COUPLINGS: ASTM A 197, MALLEABLE IRON
4. BOLTS: ASTM A 307, STEEL
5. CAST-IRON WASHERS: ASTM A 126, GRAY IRON
6. GASKETS: REACTOR 100, 100 X 100 P.S.I. SLOWLY NIP CLAMP AGAIN TO TEST

- O. INSTALL CONTINUOUS POLYETHYLENE PLASTIC TAP WITH METALLIC CORE UNDERGROUND WARNING TAPES, 6 INCHES WIDE BY 4 MILS THICK, SOLID BLUE IN COLOR WITH CONTINUOUSLY PRINTED CAPTION IN BLACK LETTERS "CAUTION – WATER LINE BURIED BELOW" DURING BACK-FILLING OF TRENCH FOR UNDERGROUND WATER SERVICE PIPING. LOCATE 6 TO 8 INCHES BELOW FINISHED GRADE, DIRECTLY OVER PIPING.
- P. PROVIDE MINIMUM 5'-0" COVER OVER LOCATE.
- Q. WATER METER WILL BE FURNISHED BY THE UTILITY COMPANY WITH REMOTE REGISTRATION SYSTEM.
- R. WATER MAIN CONNECTION: TAP WATER MAIN WITH SIZE AND IN LOCATION AS INDICATED, IN ACCORDANCE WITH REQUIREMENTS OF WATER UTILITY.

1. INSTALL CORPORATE STOPS INTO SERVICE CLAMPS. INSTALL VALVE WITH STEM POINTING UP AND WITH CAST-IRON VALVE BOX.
2. WATER SERVICE TERMINATION: TERMINATE WATER SERVICE PIPING 5'-0" FROM BUILDING FOUNDATION IN LOCATION AND INVERT AS INDICATED. PROVIDE TEMPORARY PIPE PLUG FOR PIPING EXTENSION INTO BUILDING.
- T. TUNNELING: INSTALL PIPE UNDER STREETS OR OTHER OBSTRUCTIONS THAT CANNOT BE DISTURBED, BY TUNNELING, JACKING, OR A COMBINATION OF BOTH.
- U. FIELD QUALITY CONTROL

1. PIPING TESTS: CONDUCT PIPING TESTS BEFORE JOINTS ARE COVERED AND AFTER TRUNK BLOCKS HAVE SUFFICIENTLY HARDENED. FIELD PIPELINE 24 HOURS PRIOR TO TESTING AND APPLY TEST PRESSURE TO STABILIZE SYSTEM. USE ONLY POTABLE WATER.
2. HYDROSTATIC TESTS: TEST AT NOT LESS THAN 1-1/2 TIMES WORKING PRESSURE FOR 2 HOURS. INCREASE PRESSURE IN 50 P.S.I. INCREMENTS AND INSPECT EACH JOINT BETWEEN INCREMENTS. HOLD AT TEST PRESSURE FOR ONE HOUR, DECREASE TO 10 P.S.I. SLOWLY NIP CLAMP AGAIN TO TEST PRESSURE AND HOLD FOR ONE MORE HOUR. MAXIMUM ALLOWABLE LEAKAGE IS 2 QUARTS PER HOUR PER 100 JOINTS. REMARK ANY LEAKING JOINTS WITH NEW MATERIALS AND REPEAT TEST UNTIL LEAKAGE IS WITHIN ABOVE LIMITS.
3. CLEAN AND DISINFECT WATER DISTRIBUTION PIPING: PURGE ALL NEW WATER DISTRIBUTION PIPING SYSTEMS AND FENERS OF EXISTING SYSTEMS THAT HAVE BEEN ALTERED, EXTENDED OR REPAIRED PRIOR TO USE. USE THE PURGING AND DISINFECTING PROCEDURE PRESCRIBED BY THE AUTHORITY HAVING JURISDICTION, OR, IN THE EVENT THAT A METHOD IS NOT PRESCRIBED BY THAT AUTHORITY, USE THE PROCEDURE DESCRIBED IN AWWA C651. PREPARE REPORTS FOR ALL PURGING AND DISINFECTING ACTIVITIES.

DIVISION 2.7 – SANITARY SEWERAGE

A. WASTEWATER PIPING

1. HUB AND SPIGOT CAST-IRON SOIL PIPE AND FITTINGS: ASTM A 74, GRAY CAST IRON, FOR COMPRESSION GASKET JOINTS; CLASS: SERVICE-CLASS: EXTRA HEAVY-GASKETS: ASTM C 564, RUBBER, THICKNESS TO MATCH CLASS OF PIPE.
2. PVC (POLYVINYL CHLORIDE) SEWER PIPE AND FITTINGS: ASTM D 3034, SDR 35, FOR SOLVENT CEMENT OR ELASTOMER GASKET JOINTS. SOLVENT CEMENT: ASTM D 2564-GASKETS: ASTM F 477, ELASTOMERIC SEAL.
3. COUPLINGS: RUBBER OR ELASTOMERIC SLEEVE AND STAINLESS STEEL BAND ASSEMBLY FABRICATED TO MATCH OUTSIDE DIAMETERS OF PIPES TO BE JOINED.
4. MATEOS: ASTM C 425, RUBBER FOR WRTIFIED CLAY PIPE; ASTM C 443, RUBBER FOR CONCRETE PIPE; ASTM C 564, RUBBER FOR CAST-IRON SOIL PIPE; AND ASTM F 477, ELASTOMERIC SEAL FOR PLASTIC PIPE. RUBBER FOR DISSIMILAR OR OTHER PIPE MATERIALS SHALL BE COMPATIBLE WITH AFTER MATERIALS BEING JOINED.
5. BANDS: STAINLESS STEEL, ONE AT EACH PIPE INSERT.
- B. CLEANOUTS – PROVIDE CAST-IRON FERRULE AND COUNTERSUNK BRASS CLEANOUT PLUG, WITH ROUND CAST-IRON ACCESS FRAME AND HEAVY-DUTY, SECURED, SCORATED CAST-IRON COVER.
- C. IDENTIFICATION – METALLIC-LINED PLASTIC UNDERGROUND WARNING TAPES: POLYETHYLENE PLASTIC TAP WITH METALLIC CORE, 6 INCHES WIDE BY 4 MILS THICK, SOLID BLUE OR GREEN IN COLOR WITH CONTINUOUSLY PRINTED CAPTION IN BLACK LETTERS "CAUTION – SEWER LINE BURIED BELOW."
- D. INSTALL PIPING BEGINNING AT LOW POINT OF SYSTEMS, TRUE TO GRADES AND ALIGNMENT INDICATED WITH UNBROKEN CONTINUITY OF INVERT. PLACE BELL ENDS OF PIPING FACING UPSTREAM. INSTALL GASKETS, SEALS, SLEEVES AND COUPLINGS AND PROTECT SEEDS AREAS AGAINST EROSION BY SPREADING SPECIFIED LUMP MULCH AFTER COMPLETION OF SEEDING OPERATIONS.
- E. USE FITTINGS FOR BRANCH CONNECTIONS, EXCEPT WHERE DIRECT TAP INTO EXISTING SEWER IS INDICATED.
- F. USE PROPER SIZE INCREASERS, REDUCERS, AND COUPLINGS, WHERE DIFFERENT SIZE OR MATERIAL OF PIPES AND FITTINGS ARE CONNECTED. REDUCTION OF THE SIZE OF PIPING IN THE DIRECTION OF FLOW IS PROHIBITED.

- G. INSTALL PIPING PITCHED DOWN IN DIRECTION OF FLOW, AT MINIMUM SLOPE OF 2 PERCENT, EXCEPT WHERE INDICATED OTHERWISE.
- H. EXTEND SANITARY SEWERAGE SYSTEM PIPING TO CONNECT TO BUILDING SANITARY DRAINS, OF SIZES AND IN LOCATIONS INDICATED.
- I. INSTALL 1-INCH-THICK EXTRUDED POLYSTYRENE OVER UNDERGROUND BUILDING DRAIN PIPING NOT UNDER BUILDING. WIDTH OF INSULATION SHALL EXCEED MINIMUM OF 12 INCHES BEYOND EACH SIDE OF PIPE. INSTALL DIRECTLY OVER AND CENTER ON PIPE CENTER LINE.
- J. TUNNELING: INSTALL PIPE UNDER STREETS OR OTHER OBSTRUCTIONS THAT CANNOT BE DISTURBED, BY TUNNELING, JACKING, OR A COMBINATION OF BOTH.

- K. JOIN AND INSTALL HUB AND SPIGOT CAST-IRON SOIL PIPE AND FITTINGS WITH COMPRESSION GASKETS IN ACCORDANCE WITH CISPI "CAST IRON SOIL PIPE AND FITTINGS HANDBOOK, VOLUME 1," USE "SERVICE" OR "EXTRA HEAVY" CLASS GASKETS TO MATCH CLASS OF PIPE AND FITTINGS.
- L. INSTALL POLYETHYLENE ENCASEMENT IN ACCORDANCE WITH AWWA C105.
- M. INSTALL CLEANOUTS AND EXTENSION FROM SEWER PIPE TO CLEANOUT AT GRADE AS INDICATED. SET CLEANOUT FRAME AND COVER IN CONCRETE BLOCK 18 BY 18 BY 12 INCHES DEEP, EXCEPT WHERE LOCATION IS IN CONCRETE PAVING. SET TOP OF CLEANOUT 1 INCH ABOVE SURROUNDING EARTH GRADE. FLUSH WITH GRADE WHEN INSTALLATION OF PAVING IS COMPLETED.

- N. TOP CONNECTIONS: MAKE CONNECTIONS TO EXISTING PIPING AND UNDERGROUND STRUCTURES SO THAT FINISHED WORK WILL CONFORM AS NEARLY AS PRACTICABLE TO THE REQUIREMENTS SPECIFIED FOR NEW WORK.

- O. MAKE BRANCH CONNECTIONS FROM SIDE INTO EXISTING 24-INCH OR LARGER PIPING OR TO UNDERGROUND STRUCTURES BY CUTTING OPENING INTO EXISTING UNIT SUFFICIENTLY LARGE TO ALLOW 3 INCHES OF CONCRETE TO BE PACKED AROUND ENTERING CONNECTION. CUT END OF CONNECTION PIPE PASSING THROUGH PIPE OR STRUCTURE WALL TO CONFORM TO SHAPE OF AND BE FLUSH WITH INSIDE SURFACE OF EXISTING PIPE OR STRUCTURE WALL. IF STRUCTURE WALL IS THICKER THAN 4 INCHES, CONNECTION IN 6 INCHES OF CONCRETE FOR MINIMUM LENGTH OF 12 INCHES TO PROVIDE ADDITIONAL SUPPORT OF COLLAR FROM CONNECTION TO UNDISTURBED GROUND.

- P. PROVIDE CONCRETE THAT WILL ATTAIN MINIMUM 28-DAY COMPRESSIVE STRENGTH OF 3000 PSI, UNLESS OTHERWISE INDICATED.
- Q. USE EPOXY BONDING COMPOUND AS INTERFACE BETWEEN NEW AND EXISTING CONCRETE AND PIPING OTHER THAN SLABS.
- R. PROTECT EXISTING PIPING AND STRUCTURES TO PREVENT CONCRETE OR DEBRIS FROM ENTERING WHILE MAKING TAP CONNECTIONS. REMOVE DEBRIS, CONCRETE, OR OTHER EXTRANEOUS MATERIAL THAT MAY ACCUMULATE.


DIVISION 2.8 – LANDSCAPE WORK

- A. SHIP LANDSCAPE MATERIALS WITH CERTIFICATES OF INSPECTION REQUIRED BY GOVERNING AUTHORITIES. COMPLY WITH REGULATIONS APPLICABLE TO LANDSCAPE MATERIALS. DO NOT MAKE SUBSTITUTIONS WITHOUT PRIOR AUTHORIZATION FROM ARCHITECT/ENGINEER, TOGETHER WITH PROPOSAL FOR USE OF EQUIVALENT MATERIAL.
- B. PROVIDE HEALTHY, VIGOROUS, NURSERY GROWN TREES, SHRUBS, AND PLANTS FREE OF DISEASE AND OTHER DEFECTS OF QUANTITY, SIZE, GENUS, SPECIES, AND VARIETY SHOWN AND SCHEDULED FOR LANDSCAPE WORK AND COMPLYING WITH RECOMMENDATIONS AND REQUIREMENTS OF ANSI Z60.1.
- C. TYPEWRITTEN INSTRUCTIONS RECOMMENDING PROCEDURES TO BE ESTABLISHED BY OWNER FOR MAINTENANCE OF LANDSCAPE WORK FOR ONE FULL YEAR. SUBMIT PRIOR TO EXPIRATION OF REQUIRED MAINTENANCE PERIOD(S).
- D. DELIVER PACKAGED MATERIALS IN CONTAINERS; DO NOT REMOVE CONTAINER GROWN STOCK FROM CONTAINERS UNTIL PLANTING TIME. PROVIDE FRESHLY DUG TREES AND SHRUBS AND PROTECT AS REQUIRED TO AVOID DAMAGE TO TREE OR ROOT BALL. DELIVER TREES AND SHRUBS AFTER PLANTING AND PROTECT LAMN AREAS AND PROMPTLY REPAIR DAMAGE TO LAWNS RESULTING FROM PLANTING OPERATIONS.
- E. PLANT TREES AND SHRUBS AFTER FINAL GRADES ARE ESTABLISHED AND PRIOR TO PLANTING OF LAWNS, UNLESS OTHERWISE ACCEPTABLE TO ARCHITECT/ENGINEER. IF PLANTING OF TREES AND SHRUBS OCCURS AFTER LAWN WORK, PROTECT LAWN AREAS AND PROMPTLY REPAIR DAMAGE TO LAWNS RESULTING FROM PLANTING OPERATIONS.
- F. WARRANTY TREES AND SHRUBS, FOR A PERIOD OF ONE YEAR AFTER DATE OF SUBSTANTIAL COMPLETION. REMOVE AND REPLACE TREES, SHRUBS, OR OTHER PLANTS FOUND TO BE DEAD OR IN UNHEALTHY CONDITION DURING WARRANTY PERIOD. MAKE REPLACEMENTS DURING GROWTH SEASON. END OF WARRANTY PERIOD. ANOTHER WARRANTY INSPECTION WILL BE CONDUCTED AT END OF EXTENDED WARRANTY PERIOD TO DETERMINE ACCEPTANCE OR REJECTION.


- G. SOIL AMENDMENTS, AS REQUIRED, CAN INCLUDE LIME, COMMERCIAL GRADE ALUMINUM SULFATE, PEAT HUMUS, BENONICAL, SUPERPHOSPHATE, SAND, PERLITE, VERMICULITE, SANDWIT, MANURE, MULCH, AND COMMERCIAL FERTILIZERS APPROPRIATE FOR EACH TYPE OF PLANT.
- H. GRASS SHALL BE EITHER FRESH, CLEAN, NEW CROP SEED OR STRONGLY ROOTED SOOD, NOT LESS THAN 2 YEARS OLD. SEED MIX OR SOO SHALL BE FREE OF WEEDS AND UNDESIRABLE NATIVE GRASSES. ACCEPTABLE SPECIES SHALL BE KENTUCKY BLUEGRASS (POA PRATENSIS), BERMUDA GRASS (CYNODON DACTYLON), ST. AUGUSTINEGRASS (STENOCHLOPUM SCANDINAVIUM), AND/OR CENTAURIDEGRASS (ERMENCHOLOA PHUOIDEUS).

- I. GRAVEL: WATER WORN, HARD, DURABLE GRAVEL, WASHED FREE OF LOAM, SAND, CLAY, AND OTHER FOREIGN SUBSTANCES, WITH 1-1/2 INCHES MAXIMUM, 3/4-INCH MINIMUM SIZE AND OF READILY-AVAILABLE NATURAL GRAVEL COLOR RANGE.

- J. ANTI-EROSION MULCH: PROVIDE CLEAN, SEED-FREE SALT HAY OR THRESHED STRAW OF WHEAT, RYE, OATS, OR BARLEY.
- K. ANTI-DESICCANT, EMULSION TYPE, FILM-FORMING AGENT DESIGNED TO PERMIT TRANSPIRATION, BUT RETARD EXCESSIVE LOSS OF MOISTURE FROM PLANTS. DELIVER IN MANUFACTURER'S FULLY IDENTIFIED CONTAINERS AND MIX IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
- L. PLASTIC SHEET: BLACK, WEATHER-RESISTANT POLYETHYLENE SHEETING, .008 INCH (8-MILS) THICK.
- M. COMMERCIALLY AVAILABLE ROLLED WEED BARRIER AND UNDERLAYMENT.
- N. WRAPPING: TREE WRAP TAPE NOT LESS THAN 4 INCHES WIDE, DESIGNED TO PREVENT BORER DAMAGE AND WINTER FREEZING.
- O. STAKES AND GUYS: PROVIDE STAKES AND DEADEND OF SOUND NEW HARDWOOD, TREATED SOFTWOOD, OR REDWOOD, FREE OF KNOT HOLES AND OTHER DEFECTS. PROVIDE WIRE TIES AND GUYS OF 2-STRAND, TWISTED, PLUMBE GALVANIZED IRON WIRE, NOT LIGHTER THAN 12 GA. WITH ZINC-COATED TURNBUCKLES. PROVIDE 1/2 INCH PLANTER RUBBER OR PLASTIC HOES, CUT TO LENGTH TO MATCH PLANT LENGTHS AND OF UNIFORM COLOR, MATERIAL, AND SIZE TO PROTECT TREE TRUNKS FROM DAMAGE BY WIRES.
- P. LAY OUT INDIVIDUAL TREE AND SHRUB LOCATIONS AND AREAS FOR MULTIPLE PLANTINGS. PREPARE PLANTING SOIL BY REMOVING ROOTS, PLANTS, CLUMP LUMPS, AND OTHER EXTRANEOUS MATERIALS AND MIX SPECIFIED SOIL AMENDMENTS AND FERTILIZERS WITH TOPSOIL AT APPROPRIATE RATES AND TIMES RECOMMENDED FOR EACH TYPE OF PLANT/APPLICATION.
- Q. PREPARATION FOR PLANTING LAWNS:
- LOOSEN SUBGRADE OF LAWN AREAS TO A MINIMUM DEPTH OF 4 INCHES. REMOVE STONES MEASURING OVER 1-1/2 INCHES IN ANY DIMENSION. REMOVE STICKS, ROOTS, RUBBISH, AND OTHER EXTRANEOUS MATTER. LIMIT PREPARATION TO AREAS, WHICH WILL BE PLANTED PROMPTLY AFTER PREPARATION. SPREAD TOP SOIL TO MINIMUM DEPTH REQUIRED TO MEET LINES, GRADES, AND ELEVATIONS SHOWN, AFTER LIGHT ROLLING AND NATURAL SETTLEMENT. ADD SPECIFIED SOIL AMENDMENTS AND MIX THOROUGHLY INTO UPPER 4 INCHES OF TOPSOIL.



FIRST FLOOR PLAN
ALTERNATE #3-PATIO SLIDER



HOLDOWN SCHEDULE					
LABEL	at FIRST FLOOR			at SECOND FLOOR	
	PRODUCT	POST SIZE	ANCHOR ROD	STRAP	No. of NAILS (0.148"x 3 1/4")
HD1	HDU2-SDS2.5	3x6	PAB5x54	CMSTC-16x69	22
HD2	HDU5-SDS2.5	3x6	PAB5x54	N/A	N/A
HD3	HDQ8-SDS3	6x6	PAB7x72	CMSTC-16x69	44
HD4	HDQ8-SDS3	6x6	PAB7x72	CMST-14x69	56

- NOTES: 1. ALL HOLDOWNS TO BE SUPPLIED IN PAIRS
2. LOCATE HOLDOWNS WHERE SHOWN ON PLAN AS CLOSE TO CORNERS OR ROUGH OPENINGS ABOVE AS POSSIBLE
3. STRAP SHALL EXTEND AT LEAST 25" ABOVE SILL PLATE AND BELOW TOP PLATES. HALF OF THE NAILS IN EACH MEMBER BEING CONNECTED.

FOUNDATION/FIRST FLOOR PLAN
1/4" = 1'-0"

1. TOP OF FINISHED FLOOR SLAB EL. 100.00' UON [+ OR -] FROM EL. 100.00'
2. BOTTOM OF TRENCH FOOTING EL. 93.50' (-6'-6") UNLESS NOTED THUS:
3. FS INDICATES STEPPED BOTTOM OF TRENCH FOOTING AS PER TYPICAL DETAIL
4. SJ INDICATES SAWCUT SLAB CONTROL JOINTS AS PER TYPICAL DETAIL
5. HD# INDICATES LOCATION OF SIMPSON HOLDOWN PER SCHEDULE AND TYPICAL DETAIL
6. INDICATES THICKENED SLAB PER TYPICAL DETAIL BENEATH STAIR STRINGERS AND INTERIOR BEARING WALL. COORDINATE LOCATION WITH ARCHITECTURAL DRAWINGS

COPYRIGHT © 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THE
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 2209
PROVISION 2. OF THE NEW YORK
STATE EDUCATION LAW.

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE
FOUNDATION / FLOOR PLAN

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION
1 02.03.25 MSA

SEAL

EXPIRES: 10.31.25

ISSUE DATE: 9.19.25
DRAWING NUMBER
S101

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET - SINGLE FAMILY HOME

TREDO ENGINEERS
CIVIL/STRUCTURAL
755 SENECA ST. #202
BUFFALO, NY 14210
(716) 876 - 7147


MEP
BUFFALO ENG. PC
4245 UNION RD.
BUFFALO, NY 14225
(716) 633 - 5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 ■ F: 716.885.6414
HHLArchitects.com

ARCHITECT OF RECORD

PROJECT NUMBER: 2317.006
T.E. PROJ. NUMBER: 25-61

BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203



STRUCTURAL WALL TYPES	
MARK	DESCRIPTION
1	2x6 SPF STUD GRADE at 16" O.C.
2	2x4 SPF STUD GRADE at 16" O.C.

NOTES: 1. PROVIDE PT 2x MATERIAL FOR ALL SILL PLATES IN CONTACT WITH FOUNDATIONS
2. TAG POINTS TO SIDE OF WALL WITH SHEATHING UON


LABEL	NAILING PATTERN	SOLE PLATE ANCHOR SPACING		SILL PLATE ANCHOR SPACING	
		SINGLE SHEATHED	DOUBLE SHEATHED	SINGLE SHEATHED	DOUBLE SHEATHED
A	8d at 6"	6'-0"	4'-0"	16" O.C.	8" O.C.
B	8d at 4"	5'-0"	3'-0"	--	--
C	10d at 6"	6'-0"	3'-0"	--	--
D	10d at 4"	4'-0"	2'-6"	--	--

NOTES: 1. ALL SHEATHING TO BE 7/16" APA RATED EXPOSURE 1 OSB OR PLYWOOD
2. ALL SOLE ANCHORS TO BE 1/2"Ø gr.36 HOOKED ANCHOR RODS WITH 7" MIN EMBEDMENT
3. SILL PLATE NAILS TO BE 16d (0.135"x 3 1/2")


SECOND FLOOR FRAMING PLAN

1/4" = 1'-0"

- TOP OF PLYWOOD SUBFLOOR EL. 110.31' (+10'-3 3/4" A.F.F. 1st FLOOR)
- FLOOR TRUSS BEARING EL. 109.08' (+9'-1" A.F.F. 1st FLOOR)
- FLOOR SHEATHING TO BE 3/4" T&G APA RATED EXP. 1 PLYWOOD (GLUED AND NAILED) TYPICAL
ROOF SHEATHING TO BE 5/8" APA RATED EXP. 1 PLYWOOD TYPICAL
- INDICATES FLOOR FRAMING THUS:
 - SPACING (IN INCHES)
 - TYPE OF FRAMING:
 - J = DFL#2 2x LUMBER
 - L = 1.9E LVL (1 3/4" w)
 - W = OPEN WEB TRUSS
 - T = TJI
 - DEPTH (IN INCHES)
- INDICATES WALL TYPE PER SCHEDULE
- HD3 INDICATES LOCATION OF SIMPSON STRAP PER HOLDOWN SCHEDULE ON DRAWING S101: PROVIDE SQUASH BLOCK at RIM BOARD
- GT INDICATES LOCATION OF GIRDER TRUSS
- H* INDICATES LOAD BEARING WOOD LINTEL REQUIRED PER SCHEDULE: REF. TYPICAL DETAILS
- P1 INDICATES 6x6 POST PT SPF STUD GRADE OR BETTER WITH ABW66Z BASE AND 1/2"Ø TITEN HD (4" EMBED): PROVIDE PC6Z CAP UNLESS OTHERWISE NOTED



JACK TRUSS LOAD DIAGRAM




DORMER ROOF FRAMING PLAN

ROOF FRAMING PLAN

1/4" = 1'-0"

- TOP OF PLATE (TRUSS BEARING) EL. 118.83' (+8'-6 1/4" ABOVE 2nd FLOOR PLYWOOD SUBFLOOR)
- ROOF SHEATHING TO BE 5/8" APA RATED EXP. 1 PLYWOOD (TYP)
ATTIC FLOOR SHEATHING TO BE 3/4" T&G APA RATED EXP. 1 PLYWOOD (GLUED AND NAILED) TYPICAL
- INDICATES WALL TYPE PER SCHEDULE
- INDICATES LOCATION OF GIRDER TRUSS
- INDICATES FLOOR FRAMING THUS:
 - SPACING (IN INCHES)
 - TYPE OF FRAMING:
 - J = DFL#2 2x LUMBER
 - L = 1.9E LVL (1 3/4" w)
 - W = OPEN WEB TRUSS
 - T = TJI
 - DEPTH (IN INCHES)
- INDICATES SPAN DIRECTION OF 2x6 DFL#2 at 16" O.C. MAX, LOCATED at BOTTOM CHORD OF TRUSS FOR WIDTH OF ATTIC AND at TOP CHORD FULL WIDTH OF ROOF



ROOF TRUSS LOAD DIAGRAM

DRAWING STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

ARCHITECT OF RECORD

SECOND FLOOR and ROOF FRAMING PLANS
REVISIONS AFTER ISSUANCE
NO. DATE

SEA1



ISSUE DATE: 9.19.25
DRAWING NUMBER

S102

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET - SINGLE FAMILY HOME

TREDO ENGINEERS
CIVIL/STRUCTURAL
755 SENECA ST. #202
BUFFALO, NY 14210
(716) 876 - 7147

BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203
(716) 633 - 5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 ■ F: 716.885.6414
HHLarchitects.com

COPYRIGHT © 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THE
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 7209
PROVISION 2. OF THE NEW YORK
STATE EDUCATION LAW.

- DIVISION 1 - GENERAL CONDITIONS**
- A. ALL WORK SHALL COMPLY WITH THE LATEST ADDITION OF THE BUILDING CODE OF NEW YORK STATE, AISC CODE, ACI BUILDING CODE (ACI-318), AWS CODE, ASTM STANDARDS AND ANY OTHER APPLICABLE CODES, RULES AND REGULATIONS BY AGENCIES HAVING JURISDICTIONS. WHERE CODES OVERLAP, COMPLY WITH THE MORE STRINGENT REQUIREMENTS.
- B. THE CONTRACTOR SHALL MAINTAIN INSURANCE AS WILL PROTECT HIM FROM LIABILITY UNDER WORKMAN'S COMPENSATION ACTS AND OTHER EMPLOYEE BENEFITS ACTS IN ACCORDANCE WITH THE LAWS OF NEW YORK STATE, AND FROM LIABILITY FOR DAMAGES BECAUSE OF BODILY INJURY, INCLUDING DEATH AND PROPERTY DAMAGE.
- C. CONTRACTOR IS TO REVIEW DRAWINGS AND EXISTING SITE CONDITIONS AND DIMENSIONS FOR SCOPE OF WORK INVOLVED. CONTRACTOR IS TO INCLUDE IN HIS PROPOSAL ALL ITEMS, MATERIALS, ETC., TO ACHIEVE THE DESIGN CONCEPTS SHOWN ON THE DRAWINGS. MINOR CHANGES IN THE WORK, DUE TO EXISTING CONDITIONS, WILL BE ALLOWED IF APPROVED BY THE ARCHITECT/ENGINEER BEFORE PROCEEDING.
- D. EXISTING DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL VERIFY ALL DIMENSIONS ON THE JOB. VERIFICATION OF EXISTING DIMENSIONS AND CONDITIONS SHALL BE DONE PRIOR TO PREPARATION OF SHOP DRAWINGS.
- E. CONTRACTOR IS TO INCLUDE IN HIS PROPOSAL ALL ADDITIONAL MATERIALS AND LABOR AS REQUIRED TO WORK AROUND EXISTING CONDITIONS, AND PAY FOR ALL PERMITS AND INSPECTIONS REQUIRED.
- F. ALL WORKMANSHIP MUST BE IN THE BEST PRACTICE OF THE TRADE AS DETERMINED BY THE ARCHITECT. ANY WORK NOT MEETING THESE STANDARDS WILL BE REJECTED.
- G. THERE WILL BE NO SUBSTITUTION OF MATERIALS UNLESS APPROVED IN WRITING BY THE ARCHITECT/ENGINEER.
- H. CONTRACTOR IS TO DISPOSE OF ALL DEMOLITION MATERIALS AND LEAVE THE WORK IN A READY TO USE CONDITION.
- I. CONTRACTOR IS RESPONSIBLE FOR ALL MEANS, METHODS, LABOR PROCEDURES AND SAFETY PRECAUTIONS FOR COMPLETING THE WORK.
- J. CONTRACTOR IS RESPONSIBLE FOR ALL WORK DURING CONSTRUCTION UNTIL FINAL APPROVAL BY ARCHITECT, OWNER AND LOCAL OFFICIALS.
- K. DURING DEMOLITION WORK, THE CONTRACTOR IS RESPONSIBLE FOR ALL TEMPORARY SHORING AND BRACING TO PREVENT DAMAGE TO ANY ADJACENT EXISTING STRUCTURES.
- L. CONTRACTOR IS RESPONSIBLE FOR LOCATING AND PROTECTING ANY EXISTING UTILITIES ON OR ADJACENT TO PROPERTY.
- M. WHERE A SPECIFIC MANUFACTURER'S PRODUCT IS CALLED OUT, ALL MATERIALS AND WORK MUST COMPLY WITH THE MANUFACTURER'S STRICT RECOMMENDATIONS FOR INSTALLATION. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN INSTRUCTIONS AND TO THEN FOLLOW THEM.
- N. WHERE A NAME BRAND IS NOT CALLED OUT, THE CONTRACTOR MUST SUBMIT SHOP DRAWINGS AND/OR PRODUCT INFORMATION FOR REVIEW AND APPROVAL. MINOR ITEMS IN THE WORK ARE NOT SPECIFIED. CONTRACTOR IS TO USE QUALITY AND QUANTITY THAT IS STANDARD TO THE TRADE.
- O. CONSULT THE ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS FOR LOCATIONS AND DIMENSIONS OF CHASES, INSERTS, OPENINGS, SLEEVES, WASHES, DRIPS, REVEALS, DEPRESSIONS AND OTHER PROJECT REQUIREMENTS.
- P. TYPICAL DETAILS APPLY TO ALL DRAWINGS AND SHALL BE USED EXCEPT WHERE OTHERWISE SHOWN OR NOTED.

DIVISION 1.4 - SPECIAL INSPECTIONS AND TESTING

- A. PROVIDE SPECIAL INSPECTIONS AND TESTING IN ACCORDANCE WITH CHAPTER 17 OF THE BUILDING CODE OF NEW YORK STATE. THE PROGRAM OF SPECIAL INSPECTIONS AND TESTING IS A QUALITY ASSURANCE PROGRAM INTENDED TO ENSURE THAT THE WORK IS PERFORMED IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. THIS SECTION IS INTENDED TO INFORM THE CONTRACTOR OF THE OWNER'S QUALITY ASSURANCE PROGRAM AND EXTENT OF THE CONTRACTOR'S RESPONSIBILITIES. THIS SECTION IS ALSO INTENDED TO NOTIFY THE SPECIAL INSPECTORS, TESTING LABORATORIES, AND OTHER AGENTS OF THE SPECIAL INSPECTORS OF THEIR REQUIREMENTS AND RESPONSIBILITIES.
- B. REQUIRED INSPECTIONS AND TESTS ARE IDENTIFIED IN THE SUPPLEMENTAL STATEMENT OF SPECIAL INSPECTIONS. THE SERVICES AND QUANTITIES OF TESTING SPECIFIED ARE APPROXIMATE AND MAY VARY. ACTUAL SERVICES AND QUANTITIES OF TESTING WILL BE DETERMINED BY THE OWNER AND/OR ARCHITECT AND CONSTRUCTION MANAGER DURING THE CONSTRUCTION PERIOD.
- C. THE ARCHITECT, ENGINEER AND/OR CONSTRUCTION MANAGER WILL DETERMINE THE LOCATIONS FOR TAKING SAMPLE SPECIMENS FOR TESTING IN ACCORDANCE WITH THE STATEMENT OF SPECIAL INSPECTIONS.
- D. SPECIAL INSPECTORS MUST DEMONSTRATE, TO THE ENGINEER OF RECORD AND BUILDING OFFICIAL'S SATISFACTION, EXPERIENCE AND SKILLS TO SATISFACTORILY CONDUCT TESTING INDICATED WITHOUT DELAYING THE PROGRESS OF THE WORK. THE OWNER WILL EMPLOY AND PAY FOR THE SERVICES OF THE SPECIAL INSPECTORS TO PERFORM THE SERVICE SPECIFIED HEREIN; HOWEVER, THE CONTRACTOR SHALL REIMBURSE THE OWNER FOR THE COST OF THOSE SERVICES WHICH, IN THE OPINION OF THE ARCHITECT/ENGINEER (AND CONSTRUCTION MANAGER), ARE REQUIRED DUE TO THE FOLLOWING:
- a. FAILURE OF MATERIALS OR WORKMANSHIP TO MEET CONTRACT REQUIREMENTS.
- b. MATERIALS OR PRACTICES, NOT COMPLYING WITH THE SPECIFICATIONS WHICH COULD POSSIBLY RESULT IN DEFECTIVE WORK THEREBY RENDERING IT NECESSARY OR ADVISABLE TO PERFORM TESTS TO DETERMINE WHETHER OR NOT WORK IS ACCEPTABLE.
- c. CHANGES IN SOURCE, QUALITY OR CHARACTERISTICS OF MATERIALS.
- d. SITE CURED CYLINDERS REQUESTED BY THE CONTRACTOR.
- E. THE SPECIAL INSPECTOR SHALL RETAIN THE SERVICES OF A FULL TIME REGISTERED PROFESSIONAL ENGINEER WHO SHALL CERTIFY ALL TEST REPORTS. THE ENGINEER SHALL BE RESPONSIBLE FOR THE TRAINING OF THE TESTING TECHNICIANS AND SHALL BE IN RESPONSIBLE CHARGE OF THE FIELD AND LABORATORY TESTING OPERATIONS.
- F. SPECIAL INSPECTIONS SHALL BE PERFORMED BY SPECIAL INSPECTORS WHO ARE CERTIFIED AS IDENTIFIED BELOW, OR ARE WORKING UNDER THE DIRECTION OF A REGISTERED PROFESSIONAL ENGINEER.
- a. TECHNICIANS PERFORMING SAMPLING AND TESTING OF CONCRETE SHALL BE ACI CERTIFIED CONCRETE FIELD TESTING TECHNICIANS - GRADE 1.
- b. INSPECTORS PERFORMING INSPECTIONS OF CONCRETE WORK SUCH AS INSPECTIONS OF CONCRETE PLACEMENT, BATCHING, REINFORCING PLACEMENT, CURING AND PROTECTION, SHALL BE ACI CERTIFIED CONCRETE CONSTRUCTION INSPECTORS OR ICBO CERTIFIED REINFORCED CONCRETE SPECIAL INSPECTORS.
- c. TECHNICIANS PERFORMING VISUAL INSPECTION OF WELDING SHALL BE AWS CERTIFIED WELDING INSPECTORS OR ICBO CERTIFIED STRUCTURAL STEEL AND WELDING SPECIAL INSPECTORS; TECHNICIANS PERFORMING NON-DESTRUCTIVE TESTING SUCH AS ULTRASONIC TESTING, RADIOGRAPHIC TESTING, MAGNETIC PARTICLE TESTING, OR DYE-PENETRATE TESTING SHALL BE CERTIFIED AS AN ASNT-TC LEVEL II OR LEVEL III TECHNICIAN.
- d. TECHNICIANS PERFORMING STANDARD TESTS DESCRIBED BY SPECIFIC ASTM STANDARDS SHALL HAVE TRAINING IN THE PERFORMANCE OF SUCH TESTS AND MUST BE ABLE TO DEMONSTRATE EITHER BY ORAL OR WRITTEN COMPETENCE FOR THE TEST TO BE CONDUCTED. THEY SHALL BE UNDER THE SUPERVISION OF A LICENSED PROFESSIONAL ENGINEER AND SHALL NOT BE PERMITTED TO INDEPENDENTLY EVALUATE TEST RESULTS.
- G. CONTRACTOR'S SHALL COOPERATE WITH LABORATORY PERSONNEL AND PROVIDE ACCESS TO THE WORK AND TO MANUFACTURERS/FABRICATOR'S FACILITIES AS REQUIRED FOR THE PERFORMANCE OF THEIR SERVICES. SHALL RETAIN THE LATEST SET OF CONSTRUCTION DRAWINGS, FIELD SKETCHES, APPROVED SHOP DRAWINGS, AND SPECIFICATION AT THE PROJECT SITE FOR USE BY THE INSPECTORS AND TESTING TECHNICIANS. CONTRACTOR'S SHALL ALSO PROVIDE CASUAL LABOR AND FACILITIES TO PROVIDE ACCESS TO THE WORK TO BE INSPECTED OR TESTED, TO OBTAIN AND HANDLE SAMPLES AT THE SITE, TO FACILITATE INSPECTIONS AND TESTS, TO CONSTRUCT A STORAGE BOX ON THE SITE OF SUFFICIENT SIZE TO STORE CYLINDERS, WHICH WILL AFFORD PROTECTION, REQUIRED BY ASTM C_31.
- H. CONTRACTOR'S SHALL PROVIDE THE LABORATORY WITH PRELIMINARY REPRESENTATIVE SAMPLES OF MATERIALS TO BE TESTED, IN REQUESTED QUANTITIES. WHEN THE SOURCE, QUALITY OR CHARACTERISTIC OF AN APPROVED MATERIAL CHANGES OR INDICATES LACK OF COMPLIANCE WITH CONTRACT REQUIREMENTS, CONTRACTOR'S SHALL SUBMIT ADDITIONAL SAMPLES OF MATERIALS TO TESTING LABORATORY.

DIVISION 1.4 - SPECIAL INSPECTIONS AND TESTING (CONTINUED)

- I. WHEN REQUESTED BY THE ARCHITECT/ENGINEER, OR THE TESTING LABORATORY, THE CONTRACTOR SHALL IMMEDIATELY PROVIDE COPIES OF MILL REPORTS, CULTING LISTS, MATERIAL BILLS, SHIPPING BILLS, TIME AND PLACE OF SHIPMENT OF MATERIALS TO SHOP AND FIELD AND ANY RELEVANT DATA ON PREVIOUS TESTING AND INVESTIGATIONS OF MATERIALS.
- J. CONTRACTOR'S SHALL REVIEW THE STATEMENT OF SPECIAL INSPECTIONS AND BE RESPONSIBLE FOR COORDINATING AND SCHEDULING INSPECTIONS AND TESTS TO FACILITATE THE TIMELY SEQUENCE OF INSPECTION AND TESTING. THE CONTRACTOR SHALL GIVE ADVANCED NOTIFICATION TO THE TESTING LABORATORY AND THE ARCHITECT/ENGINEER (AND CONSTRUCTION MANAGER) THAT WORK HAS PROGRESSED TO A POINT WHERE INSPECTION AND TESTING MAY PROCEED.
- K. ADVANCED NOTIFICATION, SHALL BE 48 HOURS (MIN.) PRIOR TO COMMENCEMENT OF THE FOLLOWING:
- a. SITE PREPARATION:
- i. EXCAVATION FOR FOUNDATIONS AND SLAB ON GRADE.
- ii. PROOF-ROLLINS OF SLAB ON GRADE SUBGRADE.
- b. SOIL COMPACTION:
- i. DELIVERY OF FILL TO THE SITE.
- ii. PLACEMENT AND COMPACTION OF FILL OR BACKFILL.
- c. CONCRETE:
- i. SETTING OF REINFORCING AND FORMWORK.
- ii. PLACING CONCRETE.
- d. WOOD:
- i. SHOP FABRICATION OF TRUSSES.
- ii. ERECTION OF WALLS.
- iii. ERECTION OF TRUSSES.
- iv. INSTALLATION OF WALL, FLOOR, AND/OR ROOF SHEATHING.
- L. THE SPECIAL INSPECTION PROGRAM DOES NOT, IN ANY WAY, RELIEVE THE CONTRACTOR OF HIS OBLIGATION TO PERFORM WORK IN ACCORDANCE WITH THE REQUIREMENTS OF THE CONTRACT DOCUMENTS OR FROM IMPLEMENTING AN EFFECTIVE QUALITY CONTROL PROGRAM. ALL WORK THAT IS TO BE SUBJECTED TO SPECIAL INSPECTIONS SHALL FIRST BE REVIEWED BY THE CONTRACTOR'S QUALITY CONTROL PERSONNEL.
- M. SERVICES OF TESTING LABORATORY RETAINED BY THE OWNER IS FOR VERIFICATION OF CONTRACTOR'S COMPLIANCE AND IF SUCH TESTS OF INSPECTION INDICATES FAILURE TO COMPLY WITH THE CONTRACT DOCUMENTS, THE CONTRACTOR SHALL BEAR ALL COST ASSOCIATED WITH ADDITIONAL TESTING AND INSPECTION, AFTER THE WORK HAS BEEN CORRECTED, TO VERIFY COMPLIANCE. AREAS WHERE SAMPLES ARE TAKEN FOR PURPOSES OF TESTING SHALL BE PATCHED TO THE SATISFACTION OF THE ARCHITECT.
- N. THE SPECIAL INSPECTORS OR TESTING LABORATORIES MAY NOT RELEASE, REVOKE, ALTER, OR ENLARGE ON THE REQUIREMENTS OF THE CONTRACT DOCUMENTS. THE SPECIAL INSPECTORS OR TESTING LABORATORIES WILL NOT HAVE CONTROL OVER THE CONTRACTOR'S MEANS AND METHODS OF CONSTRUCTION. THE SPECIAL INSPECTORS OR TESTING LABORATORIES ARE NOT RESPONSIBLE FOR CONSTRUCTION SITE SAFETY. THE SPECIAL INSPECTORS OR TESTING LABORATORIES HAVE NO AUTHORITY TO STOP THE WORK.
- O. THE SPECIAL INSPECTOR SHALL SUBMIT THREE COPIES OF BI-WEEKLY REPORTS OF EACH INSPECTION OR TEST ON SOILS, CONCRETE, MASONRY, AND STRUCTURAL STEEL TO THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE. REPORTS SHALL INCLUDE THE FOLLOWING:
- a. DATE OF TEST OR INSPECTION.
- b. NAME OF INSPECTOR OR TECHNICIAN.
- c. LOCATION OF SPECIFIC AREAS TESTED OR INSPECTED.
- d. DESCRIPTION OF TEST OR INSPECTION AND RESULTS.
- e. APPLICABLE ASTM STANDARD.
- f. WEATHER CONDITIONS.
- g. SIGNATURE OF SPECIAL INSPECTOR OR TECHNICIAN.
- P. SUBMIT INTERIM REPORTS TO THE BUILDING OFFICIAL WHICH INCLUDE ALL INSPECTIONS AND TEST REPORTS RECEIVED THAT WEEK. PROVIDE COPIES TO THE ARCHITECT, AND CONTRACTOR. THE FREQUENCY OF THE INTERIM REPORTS SHALL BE AS REQUIRED BY THE TOWNSHIP.
- Q. ANY DISCREPANCIES FROM THE CONTRACT DOCUMENTS FOUND DURING A SPECIAL INSPECTION SHALL BE IMMEDIATELY REPORTED TO THE CONTRACTOR. IF THE DISCREPANCIES ARE NOT CORRECTED, THE SPECIAL INSPECTOR SHALL NOTIFY THE EOR AND BUILDING OFFICIAL. REPORTS SHALL DOCUMENT ALL DISCREPANCIES IDENTIFIED AND THE CORRECTIVE ACTION TAKEN.
- R. THE TESTING LABORATORY SHALL IMMEDIATELY NOTIFY THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE BY TELEPHONE OR FAX OF ANY TEST RESULTS WHICH FAIL TO COMPLY WITH THE REQUIREMENTS OF THE CONTRACT DOCUMENTS.
- S. PROVIDE A STATEMENT TO THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE AT THE COMPLETION OF THE WORK REQUIRING SPECIAL INSPECTIONS FROM EACH INSPECTION AGENCY AND TESTING LABORATORY THAT ALL WORK WAS COMPLETED IN SUBSTANTIAL CONFORMANCE WITH THE CONTRACT DOCUMENTS AND THAT ALL APPROPRIATE INSPECTIONS AND TESTS WERE PERFORMED.
- a. COMPLETE FINAL REPORT OF SPECIAL INSPECTIONS BY THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE AND SUBMIT TO THE EOR AND BUILDING OFFICIAL PRIOR TO THE INSURANCE OF A CERTIFICATE OF USE AND OCCUPANCY.
- b. USE C.A.S.E. FORM 102 - 2001 FOR THE FINAL REPORT OF SPECIAL INSPECTIONS.
- c. THE FINAL REPORT OF SPECIAL INSPECTIONS WILL CERTIFY THAT ALL REQUIRED INSPECTIONS HAVE BEEN PERFORMED AND WILL ITEMIZE ANY DISCREPANCIES THAT WERE NOT CORRECTED OR RESOLVED.
- T. THE SPECIAL INSPECTORS AND TESTING LABORATORIES SHALL SUBMIT TO THE EOR AND BUILDING OFFICIAL FOR REVIEW A COPY OF THEIR QUALIFICATIONS WHICH SHALL INCLUDE THE NAMES AND QUALIFICATIONS OF EACH OF THE INDIVIDUAL INSPECTORS AND TECHNICIANS WHO WILL BE PERFORMING INSPECTIONS OR TESTS.
- U. THE SPECIAL INSPECTORS AND TESTING LABORATORIES SHALL DISCLOSE ANY PAST OR PRESENT BUSINESS RELATIONSHIP OR POTENTIAL CONFLICT OF INTEREST WITH THE CONTRACTOR OR ANY OF THE SUBCONTRACTORS WHOSE WORK WILL BE INSPECTED OR TESTED.
- V. THE FREQUENCY OF INSPECTIONS SHALL CONFORM TO THE PROGRAM OF SPECIAL INSPECTIONS. AND SHALL BE COMPLY WITH THE FOLLOWING DEFINITIONS:
- a. PERIODIC - IN GENERAL, NO MORE THAN A HALF DAY SITE VISIT, NOT LESS THAN 48 HOURS APART, UNLESS OTHERWISE DIRECTED BY OWNER, ARCHITECT, OR ENGINEER, OR SPECIFIED BELOW.
- b. CONTINUOUS - IN GENERAL, THE SPECIAL INSPECTOR OR AGENT SHOULD BE ON SITE BEFORE, DURING, AND AFTER OPERATION REQUIRING INSPECTION.
- W. TESTING AND INSPECTIONS FOR EXISTING SUBGRADES SHALL INCLUDE LABORATORY TESTING AND FIELD VERIFICATION AS FOLLOWS:
- a. LABORATORY TESTS
- i. FOR EXISTING SITE MATERIAL
1. COHESIVE SOILS AND SEMI-COHESIVE SOILS: PROVIDE ONE OPTIMUM MOISTURE_MAXIMUM DENSITY CURVE FOR EACH TYPE OF SUBGRADE SOIL ENCOUNTERED IN ACCORDANCE WITH ASTM D_1557.
2. NON-COHESIVE SOILS: PROVIDE MAXIMUM AND MINIMUM IDENTITY DENSITIES AND RELATIVE DENSITIES FOR EACH TYPE OF SUBGRADE SOIL ENCOUNTERED IN ACCORDANCE WITH ASTM D_4254.
- ii. FOR BORROW MATERIALS: ANALYZE EACH TYPE OF BORROW MATERIALS BEFORE ACCEPTANCE AND DELIVERY TO THE SITE. ANY CHANGE IN THE SOURCE OR QUALITY OF THE MATERIAL WILL REQUIRE A NEW SERIES OF TESTS TO DETERMINE ACCEPTABILITY.
1. PARTICLE SIZE ANALYSIS OF SOILS ASTM D_422, ASTM D_421, ASTM D_420, ASTM C_117 RECOMMENDED PRACTICE.
2. PLASTICITY INDEX DETERMINATION ASTM D_4318.
3. MOISTURE_DENSITY CURVE DETERMINATION ASTM D_1557 OR RELATIVE DENSITY (ASTM D_4253 OR ASTM D_4254) AS SPECIFIED ABOVE.
4. FROST SUSCEPTIBILITY ANALYSIS.
- b. FIELD TESTS:
- i. THE OWNER'S SOILS TESTING AGENCY REPRESENTATIVE SHALL BE PRESENT DURING DELIVERY AND COMPACTION OF FILL MATERIALS. OBSERVE PROOFROLLING OPERATIONS, IDENTIFY LOCATION AND EXTENT OF SOFT, LOOSE, OR YIELDED SUBGRADE MATERIAL THAT MUST BE REMOVED OR UNDERCUT, AND INSPECT UNDERCUT SUBGRADE.
- ii. ESTABLISH SUITABLE BEARING GRADES FOR FOUNDATIONS AND STRUCTURAL FILL BELOW SLABS ON GRADE.
- iii. VERIFY NATURAL SOIL AND STRUCTURAL FILL SUBGRADES FOR ALL SLABS ON GRADE.
- iv. IN PLACE DENSITY TESTS: TEST IN ACCORDANCE WITH ASTM D_1556 (SAND CONE METHOD) OR ASTM D_2922 (NUCLEAR METHOD) ON COMPACTED NATURAL SOILS OR STRUCTURAL FILL MATERIALS AS FOLLOWS:
- v. ONE TEST FOR EACH 2000 SQ. FT. OF SLAB ON GRADE AND PAVEMENT SUBGRADE PER 12" LIFT.
- vi. ONE TEST FOR EACH 200 CU. YD. OF FILL AND BACKFILL AT EXTERIOR SIDE OF FOUNDATION WALLS AND UNPAVED AREAS.

DIVISION 1.4 - SPECIAL INSPECTIONS AND TESTING (CONTINUED)

- X. CONCRETE SAMPLES SHALL BE TAKEN IN ACCORDANCE WITH ASTM C_172 "SAMPLING FRESH CONCRETE" AND COMPRESSION TESTS TO VERIFY THAT DESIGN MIX COMPLIES WITH CONTRACT DOCUMENTS SHALL BE COMPLETED. TEST SLUMP AND AIR CONTENT OF CONCRETE AT SAME FREQUENCY AND FROM SAME TRUCKLOAD AS COMPRESSION TESTS AND MORE OFTEN WHEN DIRECTED BY THE OWNERS REPRESENTATIVE.
- a. SLUMP TEST SHALL BE MADE IN ACCORDANCE WITH ASTM C_143 "METHODS FOR SLUMP OF PORTLAND CEMENT CONCRETE".
- b. DETERMINE AIR CONTENT BY ASTM C_231 "METHOD OF TEST FOR AIR CONTENT OF FRESHLY MIXED CONCRETE BY THE VOLUMETRIC METHOD".
- c. LABEL EACH COMPRESSION TEST CYLINDER IDENTIFYING THE TRUCKLOAD OF CONCRETE FROM WHICH SAMPLE WAS TAKEN AND THE EXACT LOCATION IN CONSTRUCTION WHERE DEPOSITED.
- d. TEST SPECIMENS IN ACCORDANCE WITH ASTM C_39 "METHODS OF TESTS FOR COMPRESSIVE STRENGTH OF MOLDED CONCRETE CYLINDERS". INCLUDE WEIGHT TEST.
- e. ONE COMPRESSION TEST, AS USED HEREIN SHALL CONSIST OF 3 TEST CYLINDERS MADE FROM COMPOSITE SAMPLES SECURED FROM A SINGLE TRUCKLOAD OF CONCRETE. ONE COMPRESSION TEST WILL BE REQUIRED FOR EACH OF THE FOLLOWING CONDITIONS:
- f. EACH 50 CU. YD. OF CONCRETE OR FRACTION THEREOF.
- g. EACH CLASS OF CONCRETE PLACED IN ONE DAY.
- h. BREAK 1 TEST CYLINDER AT 7 DAYS AND THE REMAINING 2 AT 28 DAYS. IF DESIRED BY THE ARCHITECT, ENGINEER, OR CONSTRUCTION MANAGER A FOURTH TEST CYLINDER CAN BE MADE AND HELD FOR 56 DAYS.
- Y. INSPECT FORMWORK AND REINFORCING PRIOR TO PLACING OF CONCRETE.
- Z. INSPECT BATCHING, MIXING AND DELIVERY OPERATIONS FOR COMPLIANCES WITH THE SPECIFICATIONS.
- AA. VERIFY THAT EACH FABRICATOR MAINTAINS A COMPLETE, ACCURATE, DETAILED FABRICATION AND QUALITY CONTROL PROCEDURE EVALUATED RELATIVE TO THE CODE REQUIREMENTS AND FABRICATOR'S SCOPE OF WORK.
- BB. INSPECT FABRICATOR'S PLANT BASED ON PROGRAM DESCRIBED ABOVE.
- CC. REVIEW THE FOLLOWING CONNECTIONS DURING CONSTRUCTION:
- a. FIELD GLUING - ENSURE THAT ALL SUBFLOORING IS GLUED WITH APPROVE CONSTRUCTION ADHESIVE.
- b. NAILING - VERIFY SIZE AND SPACING OF NAILS FOR:
- i. SHEATHING TO WALL STUDS AT SHEAR WALLS.
- ii. SUBFLOORING TO FLOOR JOISTS AT FLOOR LEVELS.
- iii. ROOF SHEATHING TO FRAMING.
- iv. CONFIRM PROPER INSTALLATION OF ADDITIONAL NAILS REQUIRED BY THE CONSTRUCTION DOCUMENTS INCLUDING BUT NOT LIMITED TO DRAG STRUTS, HOLDOWN LOCATIONS, BRACES, ETC.
- c. BOLTING
- i. CONFIRM SIZE, SPACING, AND PROJECTION OF SILL BOLTS.
- ii. CONFIRM SIZE, SPACING AND LOCATION OF HOLDDOWN ANCHORS.
- iii. CONFIRM SIZE AND SPACING OF LEDGE BOLTS.
- iv. CONFIRM PROPER INSTALLATION OF ADDITIONAL BOLTS REQUIRED BY THE CONSTRUCTION DOCUMENTS INCLUDING BUT NOT LIMITED TO DRAG STRUTS, HOLDOWN LOCATIONS, BRACES, ETC.
- d. ANCHORING
- DD. CONFIRM TYPE, QUANTITY AND LOCATIONS OF SIMPSON-TYPE METAL FRAMING ANCHORS SUCH AS HOLDOWNS, STRAPS, HURRICANE TIES, FRAMING HANGERS, ETC.
- EE. VERIFY GENERAL COMPLIANCE WITH CONSTRUCTION DOCUMENTS AND MANUFACTURER'S RECOMMENDED PROCEDURES INCLUDING THE INSTALLATION OF ADDITIONAL BLOCKING, BRIDGING, PERIMETER BRACING, ETC.

ABBREVIATION AGENT

SER	STRUCTURAL ENGINEER OF RECORD LISTED ABOVE.
AOR	ARCHITECT OF RECORD LISTED ABOVE.
SI	SPECIAL INSPECTOR
OIAF	OWNER'S INSPECTION AGENCY - FIELD
OIPA	OWNER'S INSPECTION AGENCY - PLANT
GE	GEOTECHNICAL ENGINEER
FQP	FABRICATOR'S QUALITY CONTROL PROGRAM
CQP	CONTRACTOR'S QUALITY CONTROL PROGRAM
NR	NOT REQUIRED
NA	NOT APPLICABLE

DIVISION 3 - CONCRETE

- A. ALL CONCRETE SHALL HAVE A 28-DAY MINIMUM COMPRESSIVE STRENGTH OF 4000 PSI. PORTLAND CEMENT SHALL BE ASTM C150, TYPE 1 OR II OR ASTM C595 TYPE II. LIMIT CEMENTITIOUS SUBSTITUTION TO BETWEEN 10 AND 20% BY WEIGHT. THE USE OF GROUND GRANULATED BLAST FURNACE SLAG (ASTM C898, GRADE 100 OR 120) IS PROHIBITED FOR USE IN CONCRETE EXPOSED TO VIEW WITHOUT WRITTEN CONSENT FROM THE ARCHITECT.
- B. ALL CONCRETE SHALL BE NORMAL WEIGHT CONCRETE WITH A NOMINAL AIR DRY DENSITY OF 145 PCF.
- C. CONCRETE ACCEPTANCE SHALL BE ON THE BASIS OF "30 CONSECUTIVE TEST" OR "TRIAL MIXTURES" AS DESCRIBED IN ACI 318, SECTION 5.3. PROVIDE TRIAL MIXTURES FOR THREE DIFFERENT WATER-CEMENT RATIOS INDICATING 7-DAY AND 28-DAY COMPRESSIVE STRENGTH (F_c); 1200 PSI GREATER THAN REQUIRED SHALL BE ACCEPTED.
- D. A MINIMUM OF ONE SET OF THREE STANDARD TEST CYLINDERS FOR EACH DAY'S PLACEMENT SHALL BE TAKEN, AND THE OWNER'S TESTING AGENCY WILL PERFORM COMPRESSION TESTS ON ONE CYLINDER AT 7 DAYS AND 28 DAYS, LEAVING ONE CYLINDER IN RESERVE.
- E. ADMIXTURES, ADD TO MIX PER MANUFACTURER'S RECOMMENDATIONS: WATER REDUCING ADMIXTURE (ASTM A494, TYPE A) AIR ENTRAINING ADMIXTURE (ASTM C2260)
- F. ADD AIR ENTRAINING ADMIXTURE TO PRODUCE MAXIMUM AIR BY VOLUME OF:
- 6% +/- 1% CLASS A CONCRETE, FOR EXPOSURE TO EARTH OR WEATHER.
- 3.5%, +1%, -2% CLASS A CONCRETE, FOR INTERIOR FLOOR SLABS.
- G. FINE AGGREGATE SHALL CONSIST OF WASHED NATURAL SAND CONFORMING TO ASTM C-33 AND COARSE AGGREGATE SHALL CONSIST OF WELL-GRADED CRUSHED STONE OR WASHED GRAVEL CONFORMING TO ASTM C-33, 3/4" SIZE.
- H. WATER CEMENT RATIO SHALL NOT EXCEED 0.45 FOR CLASS A CONCRETE. WATER SHALL BE CLEAN AND FREE FROM DELETERIOUS AMOUNTS OF ACIDS, ALKALIS OR ORGANIC MATERIALS.
- I. SLUMP SHALL BE:
- | | |
|------------------------------|----------|
| PAVEMENTS AND SLAB ON GROUND | 3" +/-1" |
| FOOTINGS | 3" +/-1" |
| REINFORCED WALLS | 4" +/-1" |
- MAX WITH MID-RANGE WATER REDUCER (PLANT ADDED) 5" +/-1"
- MAX WITH HIGH-RANGE WATER REDUCER (FIELD ADDED) 8"
- J. ALL CONCRETE SHALL BE TRUCK MIXED.
- K. WALL/FORM PANELS SHALL BE PLYWOOD OR TEMPERED HARDBOARD FACES WITH AN ACCEPTED APPLIED FORM RELEASE AGENT.
- L. CLEARANCE OF MAIN REINFORCEMENT FROM ADJACENT SURFACES SHALL CONFORM TO THE FOLLOWING (UNLESS OTHERWISE SHOWN IN DETAIL):
- | | |
|---|------------|
| 1. UNFORMED SURFACES IN CONTACT WITH GROUND (FOOTINGS) | 3 INCHES |
| 2. SLABS ON GRADE | 1/2 INCHES |
| 3. FORMED SURFACES IN CONTACT WITH GROUND OR EXPOSED TO WEATHER (WALLS) | 2 INCHES |
| 4. IN ALL CASES, CLEARANCE NOT LESS THAN DIAMETER OF BARS. | |

NOTE: MAXIMUM DEVIATION FROM THESE REQUIREMENTS SHALL BE +1/4" FOR SECTIONS TEN (10) INCHES OR LESS AND +1/2" FOR SECTIONS OVER TEN (10) INCHES THICK.

DIVISION 3 - CONCRETE (CONTINUED)

- M. ALL PLACEMENT OF CONCRETE AND REINFORCEMENT:
- ACCORDING TO ACI 318 (INCLUDING ACI RECOMMENDATIONS FOR HOT AND COLD WEATHER CONDITIONS); AND CRSI RECOMMENDED PRACTICES FOR PLACING REINFORCING BARS.
- N. CURING COMPOUND:
- FOUNDATION WALLS: MASTER BUILDERS CO. MB-429.
- BUILDING FLOORS: MASTER BUILDERS CO. "MASTERSEAL".
- O. FLOOR FINISH: HARD STEEL TROWEL UNLESS OTHERWISE INDICATED ON DRAWINGS.
- P. EXPANSION JOINT FILLERS: SEE DETAILS AND NOTES ON DRAWINGS.
- Q. FORM REMOVAL (MINIMUM TIME):
- 5-DAYS FOR AIR TEMPERATURES BETWEEN 40 & 50 DEGREES.
- 3-DAYS FOR AIR TEMPERATURE ABOVE 55 DEGREES.
- R. WHERE EXPOSED ABOVE GRADE, EITHER INTERIOR OR EXTERIOR, CONCRETE SHALL HAVE A SMOOTH FINISH AS OBTAINED BY THE USE OF SMOOTH PLYWOOD OR TEMPERED BOARD FORMS. GRIND OFF FIN. JOINT MARKS, BULGES AND OTHER PROMINENT GRAIN MARKINGS. FILL AND GRIND OFF HONEYCOMBED OR DEPRESSED AREAS AND LEAVE SMOOTH AND WASHED CLEAN.
- S. REINFORCING BARS SHALL BE NEW ASTM A615, GRADE 60.
- T. STEEL WELDED WIRE FABRIC SHALL BE NEW ASTM A185. FURNISH IN FLAT SHEETS. LAP 1-1/2 SQUARES IN ALL DIRECTIONS AT JOINTS.
- U. BAR SUPPORTS SHALL BE GALVANIZED OR STAINLESS STEEL. BAR SUPPORTS IN CONTACT WITH EXPOSED SURFACES SHALL BE GALVANIZED AND PLASTIC TIPPED.
- V. WHERE CONTINUOUS REINFORCING IS CALLED FOR, IT SHALL BE RUN CONTINUOUSLY AROUND CORNERS, LAPPED AT NECESSARY SPLICES AND HOOKED AT DISCONTINUOUS ENDS.
- W. SUBMIT SHOP DRAWINGS TO THE ARCHITECT/ENGINEER FOR REVIEW PRIOR TO FABRICATION OF REBAR.
- X. ALL REINFORCING SHALL BE INSPECTED BY THE OWNER'S TESTING AGENCY BEFORE CONCRETE IS PLACED.
- Y. NON-SHRINK GROUT SHALL BE A MIXTURE OF WATER AND MASTERFLOW 713 BY MASTER BUILDERS.
- Z. NO CALCIUM CHLORIDE SHALL BE USED IN ANY CONCRETE.

BEAM, SLAB AND WALL REINFORCING LAP SPLICE LENGTHS

LAP SPLICE LENGTHS FOR REINFORCING IN 4000 PSI CONCRETE ARE AS FOLLOWS:

BAR SIZE	TENSION SPLICE		
	TOP	OTHER	DEVELOPMENT LENGTH
3	21	15	13
4	29	20	17
5	36	26	21
6	43	31	25
7	54	39	32
8	71	51	42
9	90	65	53
10	115	82	68
11	163	101	83

NOTES:

1. LAPPED SPLICE LENGTHS BASED ON ASTM A-615, GRADE 60. REBAR.
2. REINFORCING BARS ARE CLASSED AS TOP BARS WHEN MORE THAN 12" OF CONCRETE IS CAST BENEATH RESPECTIVE REINFORCING BAR.
3. COMPRESSION SPLICES PERMISSIBLE ONLY WHERE SPECIFICALLY NOTED ON THE DRAWINGS, DETAILS OR SCHEDULES.
4. TENSION SPLICES SHALL BE USED IN ALL BEAMS, SLABS AND WALLS UNLESS OTHERWISE NOTED.
5. WHEN LAPPING LARGER BAR WITH SMALLER BAR, LAP LENGTH FOR SMALLER BAR SHALL GOVERN RESPECTIVE SPLICE.
6. SPLICE CONTINUOUS TOP REINFORCING BARS AT CENTER OF CLEAR SPAN WITH COMPRESSION SPLICES.
7. SPLICE CONTINUOUS BOTTOM REINFORCING BARS AT CENTER OF SUPPORTING ELEMENT WITH COMPRESSION SPLICES.
8. ALL SPLICE LENGTHS NOTED IN INCHES.

Copyright © 2008 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THIS
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 2209
PROVISION 2. OF THE NEW YORK
STATE EDUCATION LAW.

PROJECT NAME/LOCATION:
DESCRIPTION (NEW CONSTRUCTION)
68 PULASKI STREET - SINGLE FAMILY HOME

TREDO ENGINEERS
CIVIL/STRUCTURAL
7555 SENECA ST. #202
BUFFALO, NY 14210
(716) 876 - 7147
MEP
BUFFALO ENG. PC
4745 UNION RD.
BUFFALO, NY 14225
(716) 633 - 5598

**HHL Architects**
172 Allen Street, Buffalo, New York 14201
716.885.0744 F: 716.885.6414
hhlarchitects.com

ISSUE DATE: 9,19,25

DRAWING NUMBER

SE...



EXPIRES: 10.31.25

DRAWING TITLE
SPECIFICATIONS

REVISIONS AFTER ISSUANCE
DATE

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

ARCHITECT OF RECORD

PROJECT NUMBER: 2317.006
T.E. PROJ. NUMBER: 25-61

DIVISION 5E - POST-INSTALLED ANCHORS

- A. EXCEPT WHERE INDICATED ON THE DRAWINGS, POST INSTALLED ANCHORS SHALL CONSIST OF THE FOLOWING ANCHOR TYPES AND INSTALLED IN ACCORDANCE WITH THEIR RESPECTIVE ICC-ES REPORT AND MANUFACTURER'S PUBLISHED INSTALLATION INSTRUCTIONS:

APPLICATION	ANCHORING SYSTEM	ICC-ES REPORT
ANCHORAGE TO CONCRETE	HILTI KWIK-X DUAL ACTION SYSTEM	ESR-5065
	HILTI HY 200 V3 ADHESIVE	ESR-4878
	HILTI KWIK HUS EZ	ESR-3027
REBAR DOWELING	HILTI HY 200 V3 WITH SAFESET INSTALLATION	ESR-3187
ANCHORAGE TO SOLID GROUTED MASONRY	HILTI HY 270 ADHESIVE WITH SAFESET	ESR-4143
ANCHORAGE TO HOLLOW / MULTI-WYTHE MASONRY	HILTI HY 270 ADHESIVE WITH SCREEN TUBE	ESR-4143, ESR-4144

BASIS OF DESIGN INCLUDES THE FOLLOWING DESIGN PARAMETERS:
(1) CRACKED CONCRETE
(2) WATER-SATURATED CONCRETE
(3) BASE MATERIAL TEMPERATURE OF 23-104 DEGREES FAHRENHEIT
(4) ALLOWABLE DRILLING METHOD: HAMMER-DRILL HOLLOW DRILL BIT SYSTEM
(5) CURRENT ICC-ES REPORT WITH APPROVAL FOR DEVELOPMENT OF BAR USING ACI PROVISIONS FOR EMBEDMENT DEPTHS GREATER THAN 20 BAR DIAMETERS

- B. ACI 318 REQUIRES ADHESIVE ANCHORS TO BE INSTALLED IN CONCRETE HAVING A MINIMUM AGE OF 21 DAYS AT THE TIME OF ANCHOR INSTALLATION.

- C. FOR ADHESIVE ANCHORS INSTALLED IN CONCRETE AGED LESS THAN 21 DAYS, CONTACT ENGINEER TO RE-EVALUATE THE ANCHOR DESIGN BASED ON THE CONCRETE STRENGTH AT THE TIME OF INSTALLATION AND USE A BOND STRENGTH VALUE FOR WATER SATURATED CONCRETE. SITE TESTING IS RECOMMENDED TO VERIFY THE FASTENING CAPACITY.

- D. ANCHOR CAPACITY USED IN DESIGN MUST BE BASED ON THE TECHNICAL DATA PUBLISHED BY ANCHOR MANUFACTURER OR SUCH OTHER METHOD AS APPROVED BY THE STRUCTURAL ENGINEER. SUBSTITUTION REQUESTS FOR ALTERNATE PRODUCTS MUST BE APPROVED IN WRITING BY THE STRUCTURAL ENGINEER. PRIOR TO USE, CONTRACTOR MUST PROVIDE CALCULATIONS STAMPED BY PROFESSIONAL ENGINEER DEMONSTRATING THAT THE SUBSTITUTED PRODUCT IS CAPABLE OF ACHIEVING THE PERFORMANCE VALUES OF THE SPECIFIED PRODUCT. SUBSTITUTIONS WILL BE EVALUATED BY THEIR HAVING AN ICC ESR SHOWING COMPLIANCE WITH THE RELEVANT BUILDING CODE FOR SEISMIC USES, LOAD RESISTANCE, INSTALLATION CATEGORY, AND AVAILABILITY OF COMPREHENSIVE INSTALLATION INSTRUCTIONS. ADHESIVE ANCHOR EVALUATION WILL ALSO CONSIDER CREEP, IN-SERVICE TEMPERATURE, AND INSTALLATION TEMPERATURE. CONTRACTOR IS RESPONSIBLE FOR PREPARATION OF SHOP DRAWINGS IN ACCORDANCE WITH THE DESIGN DOCUMENTS. SUBMIT SHOP DRAWINGS TO THE ENGINEER FOR APPROVAL.

- E. THE DESIGN OF STRAIGHT POST-INSTALLED REINFORCING BARS TO CONCRETE MUST BE PERFORMED PER THE DEVELOPMENT AND SPLICE REQUIREMENTS OF ACI 318. THE POST-INSTALLED REINFORCING BAR SYSTEM IS AN ALTERNATIVE TO CAST-IN-PLACE REINFORCING BARS GOVERNED BY ACI 318 AND BCNYS CHAPTER 19. SUBSTITUTION REQUESTS FOR ALTERNATE PRODUCTS MUST BE APPROVED IN WRITING BY THE STRUCTURAL ENGINEER PRIOR TO USE. CONTRACTOR MUST PROVIDE SIGNED AND SEALED CALCULATIONS SEALED BY PROFESSIONAL ENGINEER. THE EPOXY SYSTEM MUST BE TESTED IN ACCORDANCE WITH THE ICC-ES ACCEPTANCE CRITERIA FOR POST-INSTALLED EPOXY ANCHORS IN CONCRETE ELEMENTS (AC308), TABLE 3.8. TECHNICAL DATA MUST BE PUBLISHED IN AN ICC-ES EVALUATION SERVICE REPORT SHOWING COMPLIANCE WITH IBC.

- F. CONTINUOUSLY THREADED CARBON STEEL ANCHOR ELEMENTS MUST BE HILTI ASTM F1554 COMPLIANT UNLESS NOTED OTHERWISE.

- G. DRILL HOLES WITH ROTARY IMPACT HAMMER DRILLS USING HOLLOW DRILL BIT WITH INTEGRAL VACUUM CLEAN AS PERMITTED BY ICC-ESR. USE OF DIAMOND CORE BIT WITH ROUGHENING TOOL SHALL BE PERMITTED AFTER ENGINEERS OF RECORD APPROVAL. UNLESS OTHERWISE SHOWN ON THE DRAWINGS, ALL HOLES MUST BE DRILLED PERPENDICULAR TO THE CONCRETE SURFACE.

- H. INSTALL ANCHORS PER THE MANUFACTURER INSTRUCTIONS, AS INCLUDED IN THE ANCHOR PACKAGING. THE CONTRACTOR MUST ARRANGE AN ANCHOR MANUFACTURER'S REPRESENTATIVE TO PROVIDE ONSITE INSTALLATION TRAINING FOR ALL OF THEIR ANCHORING PRODUCTS SPECIFIED. THE STRUCTURAL ENGINEER MUST RECEIVE DOCUMENTED CONFIRMATION THAT ALL OF THE CONTRACTOR'S PERSONNEL WHO INSTALL ANCHORS ARE TRAINED PRIOR TO THE COMMENCEMENT OF INSTALLING ANCHORS.

- I. INSTALLATION OF ADHESIVE ANCHORS HORIZONTALLY OR UPWARDLY INCLINED TO SUPPORT SUSTAINED TENSION LOADS MUST BE PERFORMED BY PERSONNEL CERTIFIED BY AN APPLICABLE CERTIFICATION PROGRAM. CERTIFICATION MUST INCLUDE WRITTEN AND PERFORMANCE TESTS IN ACCORDANCE WITH THE ACI/CRSI ADHESIVE ANCHOR INSTALLER CERTIFICATION PROGRAM, OR APPROVED EQUIVALENT.

- J. ANCHOR CAPACITY IS DEPENDENT UPON SPACING BETWEEN ADJACENT ANCHORS AND PROXIMITY OF ANCHORS TO EDGE OF CONCRETE. INSTALL ANCHORS IN ACCORDANCE WITH SPACING AND EDGE CLEARANCES INDICATED ON THE DRAWINGS.

DIVISION 6 - WOOD

SECTION 6A - ROUGH CARPENTRY AND STRUCTURAL LAMINATED MEMBERS

- A. LUMBER SHALL COMPLY WITH PS20 "AMERICAN SOFTWOOD LUMBER STANDARD" WITH APPLICABLE GRADING RULES.
- B. ALL LUMBER SHALL BE VISUALLY GRADED OR MACHINE RATED WITH THE FOLLOWING MINIMUM ALLOWABLE UNIT STRESSES:

	SPRUCE PINE FIRDUGLAS FIR LARCH STUD GRADE	No. 2
Fb EXTREME FIBER IN BENDING:	675 PSI	900 PSI
Fc COMPRESSION PARALLEL TO GRAIN	725 PSI	1350 PSI
Fv HORIZONTAL SHEAR	135 PSI	180 PSI
E MODULUS OF ELASTICITY	1,200,000 PSI	1,600,000 PSI

- C. ALL LUMBER SHALL HAVE A MAXIMUM MOISTURE CONTENT AT TIME OF DRESSING OF 19%.

- D. PLYWOOD SHALL CONFORM TO REQUIREMENTS OF PS1 "U.S. PRODUCT STANDARD FOR CONSTRUCTION AND INDUSTRIAL PLYWOOD" AND AMERICAN PLYWOOD ASSOCIATION (APA) "PERFORMANCE STANDARD AND POLICIES FOR STRUCTURAL USE PANELS", FORM No. E445.

- E. FACTORY MARK EACH CONSTRUCTION PANEL WITH APA TRADEMARK INDICATING EXPOSURE DURABILITY CLASSIFICATION: EXPOSURE 1. WHILE OSB (OR EQUIVALENT) IS ACCEPTABLE FOR ALL APPLICATIONS, PLYWOOD IS RECOMMENDED FOR USE ON HORIZONTAL SURFACES TO AVOID WATER DAMAGE DURING CONSTRUCTION.

- F. PROVIDE FASTENERS AND ANCHORAGE AS INDICATED AND AS RECOMMENDED BY APPLICABLE STANDARDS, COMPLYING WITH FEDERAL STANDARDS FOR NAILS, STAPLES, SCREWS, BOLTS, NUTS, WASHERS AND ANCHORING DEVICES.

- G. WHERE ROUGH CARPENTRY WORK IS EXPOSED TO GROUND OR WEATHER, USE FASTENERS WITH A HOT-DIP ZINC COATING (ASTM A153).

- H. PRESSURE TREATED LUMBER WITH WATER BORNE PRESERVATIVES TO COMPLY WITH AWPB LP-2 FOR ALL LUMBER EXPOSED TO MOISTURE INCLUDING BUT NOT LIMITED TO WOOD CANTS, NAILERS, BLOCKING, STRIPPING, MEMBERS IN CONNECTION WITH ROOFING, FLASHING, VAPOR BARRIERS AND WATERPROOFING, SILLS, SLEEPERS, MEMBERS IN CONTACT WITH MASONRY OR CONCRETE, AND MEMBERS LESS THAN 18" ABOVE GRADE.

- I. STRUCTURAL LAMINATED MEMBERS SHALL BE ENGINEERED LUMBER CONSISTING OF THIN PLYWOOD VENEERS SECURELY BONDED TOGETHER. ACCEPTABLE PRODUCTS ARE MICRO=LAM BY TRUS JOIST CORPORATION, GANG=LAM LVL BY LOUISIANA-PACIFICA CORPORATION, AND ASI LAMINATED VENEER LUMBER BY ALPINE WOOD PRODUCTS, INC. EQUIVALENT SUBSTITUTIONS MAY BE USED IF SUBMITTED TO, AND ACCEPTED BY, THE ARCHITECT/ENGINEER. INSTALL IN ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS.

SECTION 6B - PREFABRICATED WOOD TRUSSES

- A. SUBMIT ENGINEERED AND CHECKED TRUSS SHOP DRAWINGS TO THE ARCHITECT/ENGINEER FOR REVIEW. SHOW SHOP FABRICATION DETAILS, FIELD ASSEMBLY DETAILS AND ERECTION PLANS FOR ALL PREFABRICATED WOOD TRUSSES.

- B. SUBMIT TRUSS MEMBER, METAL PLATE CONNECTOR, BEAM TO TRUSS AND TRUSS TO TRUSS CONNECTION DESIGN CALCULATIONS, PREPARED AND SEALED BY A QUALIFIED STRUCTURAL ENGINEER REGISTERED IN THE STATE OF NEW YORK, TO THE ARCHITECT/ENGINEER FOR REVIEW PRIOR TO FABRICATION.
- C. DESIGN ALL TRUSS MEMBERS AND CONNECTIONS IN ACCORDANCE WITH THE LATEST EDITIONS OF TPI "DESIGN SPECIFICATION FOR METAL PLATE CONNECTED WOOD TRUSSES" AND THE AF&PA "NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION" TO SUPPORT ALL LOAD CONFIGURATIONS INDICATED.

- D. ALL LUMBER SHALL BE NEW LUMBER.

- E. TRUSS CONNECTOR PLATES SHALL BE FORMED FROM NEW SHEET STEEL, 20 GAGE MINIMUM, CONFORMING TO ASTM A446 WITH A MINIMUM YIELD STRENGTH OF 33,000 PSI. CONNECTOR PLATES SHALL BE HOT-DIPPED GALVANIZED, COATING DESIGNATION G60.

- F. PROVIDE TRUSSES WITH AN UPWARD CAMBER, WHICH OFFSETS TRUSS DEFLECTIONS CAUSED BY MEMBER SELF-WEIGHT, ROOF SHEATHING, HUNG CEILING AND MECHANICAL UNITS.

- G. THE TRUSS MANUFACTURER SHALL DESIGN AND PROVIDE ALL TEMPORARY TRUSS BRACING, BRIDGING AND SHORING AS REQUIRED FOR THE SAFETY, STABILITY AND ALIGNMENT OF THE ROOF AND/OR FLOOR TRUSS SYSTEM. TEMPORARY BRACING SHALL REMAIN IN PLACE UNTIL THE PERMANENT LATERAL LOAD RESISTING SYSTEM IS FULLY OPERATIONAL.

- H. HANDLE AND ERECT ALL TRUSSES IN SUCH A MANNER AS TO AVOID PERMANENT STRUCTURAL DAMAGE TO TRUSS MEMBERS OR CONNECTIONS. HOIST TRUSSES INTO POSITION ONLY AT POINTS SPECIFICALLY DESIGNED AND DESIGNATED BY THE TRUSS MANUFACTURER.

- I. DO NOT FIELD CUT OR MODIFY TRUSS MEMBERS OR CONNECTIONS WITHOUT THE PRIOR REVIEW OR ACCEPTANCE OF THE ARCHITECT/ENGINEER OR TRUSS MANUFACTURER.

DIVISION 31 - SITE WORK/EARTHWORK/FOUNDATIONS

- A. A TESTING AGENCY WILL BE EMPLOYED BY THE OWNER TO VERIFY ACCEPTABILITY OF WORKMANSHIP AND MATERIALS.

- B. SLOPE SIDES OF EXCAVATIONS ARE TO COMPLY WITH THE LOCAL CODES, ORDINANCES AND REQUIREMENTS OF AGENCIES HAVING JURISDICTION. SHORE AND/OR BRACE WHERE SLOPING IS NOT POSSIBLE BECAUSE OF SPACE RESTRICTIONS OR STABILITY OF MATERIAL EXCAVATED. MAINTAIN SIDES AND SLOPES OF EXCAVATIONS IN SAFE CONDITION UNTIL COMPLETION OF BACKFILLING.

- C. PROVIDE MATERIALS FOR SHORING AND BRACING, SUCH AS SHEET PILING, UP-RIGHTS, STRINGERS, AND CROSS BRACES, AS REQUIRED. MAINTAIN SHORING AND BRACING IN EXCAVATIONS REGARDLESS OF TIME PERIOD EXCAVATIONS WILL REMAIN OPEN. EXTEND SHORING AND BRACING AS EXCAVATION PROGRESSES.

- D. BARRICADE OPEN EXCAVATIONS OCCURRING AS PART OF THIS WORK AND POST WITH WARNING LIGHTS. OPERATE WARNING LIGHTS DURING HOURS FROM DUSK TO DAWN EACH DAY AND AS OTHERWISE REQUIRED.

- E. ALL SUBGRADE SUPPORTED FOOTINGS AND CONCRETE PIERS SHALL BEAR ON UNDISTURBED NATURAL SUBGRADE MATERIAL MEETING OR EXCEEDING THE PRESUMPTIVE LOAD-BEARING VALUE OF 1.5 KIPS PER SQUARE FOOT (1 KIP=1000 LBS.) AS DEFINED BY TABLE 1806.2 OF THE BUILDING CODE OF NEW YORK STATE. NATIVE SUBGRADE SHALL BE INSPECTED AND CONFIRMED BY THE OWNER'S SOIL TESTING AGENCY.

REFERENCE SUMMARY TABLE FOR APPROXIMATE FILL DEPTHS BY ADDRESS. WHERE NATURAL SUBGRADE IS NOT PRESENT AT BOTTOM OF FOOTING ELEVATION, CONTINUE EXCAVATION AND FILL WITH EITHER LEAN CONCRETE OR OVERCAST FOOTING PER TYPICAL DETAIL.

- F. PREVENT SURFACE WATER AND SUBSURFACE GROUND WATER FROM FLOWING INTO EXCAVATIONS AND FROM FLOODING PROJECT SITE AND SURROUNDING AREA. NO FOOTINGS, GRADE BEAMS OR SLABS SHALL BE PLACED IN WATER OR ON FROZEN GROUND.

- G. ALL FOOTING EXCAVATIONS ARE TO BE FINISHED BY HAND.

- H. ALL FINISHED EXCAVATIONS AND BEARING GRADES SHALL BE INSPECTED AND APPROVED BY THE OWNER'S SOIL TESTING AGENCY BEFORE ANY CONCRETE IS PLACED.

- I. USE SIDE FORMS FOR ALL WALLS. FOOTINGS MAY BE TRENCH FORMED. THEY MAY BE WIDER BUT MUST BE NO LESS THAN THE DIMENSIONS SHOWN IN DETAILS.

- J. SHOULD ROCK BE ENCOUNTERED DURING FOUNDATION EXCAVATION, NOTIFY THE ARCHITECT/ENGINEER IMMEDIATELY. DO NOT PROCEED WITH ROCK EXCAVATION UNTIL GIVEN AUTHORIZATION TO DO SO. SUCH EXCAVATION WILL BE PAID FOR ON THE BASIS OF UNIT PRICES AS GIVEN IN THE BID FORM.

- K. IN GENERAL, EXTERIOR CONSTRUCTION SHALL BE CARRIED DOWN NOT LESS THAN 4-FEET BELOW FINISHED EXTERIOR GRADE.

- L. BACKFILL AGAINST FOUNDATION WALLS BELOW GRADE SO THAT DIFFERENCE IN FILL LEVEL ON OPPOSITE SIDE DOES NOT EXCEED 1'-0" AT ANY TIME OR PROVIDE TEMPORARY LATERAL SUPPORT UNTIL PERMANENT LATERAL SUPPORT SYSTEM IS IN PLACE AND OF ADEQUATE STRENGTH TO WITHSTAND THE APPLIED LATERAL PRESSURES.

MISCELLANEOUS

- M1 CONTRACTOR SHALL VERIFY ALL DIMENSIONS ON THE JOB. VERIFICATION OF EXISTING DIMENSIONS AND CONDITIONS SHALL BE DONE PRIOR TO PREPARATION OF SHOP DRAWINGS.

- M2 ALL OPENINGS THROUGH SLABS AND WALLS ARE NOT SHOWN. PROVIDE UNIT PRICES FOR ADDITIONAL FRAMING AND REINFORCING.

- M3 CONSULT THE ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS FOR LOCATIONS AND DIMENSIONS OF CHASES, INSERTS, OPENINGS, SLEEVES, WASHES, DRIPS, REVEALS, DEPRESSIONS AND OTHER PROJECT REQUIREMENTS.

- M4 TYPICAL DETAILS APPLY TO ALL DRAWINGS AND SHALL BE USED EXCEPT WHERE OTHERWISE SHOWN OR NOTED.

DESIGN LOADS

RESIDENTIAL

DWELLING (ONE- AND TWO-FAMILY)	
UNINHABITABLE ATTICS WITH STORAGE	20 PSF
ALL OTHER AREAS INCLUDING STAIRS, EXCEPT BALCONIES	40 PSF
BALCONIES (NOT EXCEEDING 100-SF)	60 PSF

PARTITION ALLOWANCE

	15 PSF
--	--------

CEILINGS

	5 PSF
--	-------

MECHANICAL ITEMS SUSPENDED FROM STRUCTURAL FRAMING

	5 PSF
--	-------

GROUND SNOW LOAD, Pg=

	50 PSF
--	--------

WIND

ULTIMATE WIND SPEED	115 MPH
WIND EXPOSURE	B

SEISMIC


SEISMIC DESIGN CATEGORY	B
SITE CLASS	D

BUILDING IS NOT DESIGNED FOR ADDITIONAL HORIZONTAL OR VERTICAL EXTENSIONS.

EXISTING FILL DEPTHS BY ADDRESS			
#	STREET	FILL DEPTH (FT)	REMARKS
18	CALUMET	3.5	A thin layer of 'clean' fill with old pipes underlying debris laden fill
144	HERTEL	3.5	A thin layer of 'clean' fill with old pipes underlying debris laden fill
88	BUSH	3.5	
143	HOWELL	2	
143	LA SALLE	3.5-5.5	Bedrock encountered at 7.5-ft below grade
362	EAST	2	
253	EAST	6.3	A thin layer of 'clean' fill with old pipes underlying debris laden fill
111	AUSTIN	7	
57	HOFFMAN	2	
911	COLUMBUS PKWY	5.5	
198	FOURTEENTH	5.5-7.5	3.5" concrete slab at 3.5-ft below grade
383	FOURTEENTH	5	
230	MASSACHUSETTS	6	
251	NORMAL	4	
873	PROSPECT	5	Bedrock encountered at 5.7-ft below grade
875	PROSPECT	3	
238	RHODE ISLAND	3	
240	RHODE ISLAND	n/a	
242	RHODE ISLAND	4.5	Intact wall/slab at 4.2-ft below grade
138	JERSEY	4.5	Concrete slab at 4.5-ft below grade
142	JERSEY	2.5	
144	JERSEY	2	1 to 2-ft slabs of dolomite at 5.5-ft below grade
226	MARYLAND	7	6" broken concrete slab at 6-ft below grade
258	WHITNEY	2	
262	WHITNEY	6.5	Intact wall/slab from 0.8- to 3.5-ft below grade
206	MIAMI	5.5	
208	MIAMI	4	
230	MIAMI	5	
236	MIAMI	4.5	
288	MIAMI	6.5	
66	O CONNELL	5	
92	GORTON	3	
116	HAMILTON	3.5	
153	THOMPSON	5	A thin layer of 'clean' fill with old pipes underlying debris laden fill and 12-in stone wall at 4-ft below grade
248	LAIRD	5	Concrete slab at 4.0-ft below grade
670	WEST	5.8	
762	AMHERST EAST	2.5	Concrete wall at 1.5-ft below grade
764	AMHERST EAST	n/a	
766	AMHERST EAST	2.7	
291	BERKSHIRE	4.5	
440	BERKSHIRE	5	Concrete slab at 3.7-ft below grade
442	BERKSHIRE	5	
447	BERKSHIRE	4	
449	BERKSHIRE	3.5	
256	HEWITT	5	Intact masonry wall/slab at 5.0-ft below grade
685	MINNESOTA	3	
130	ROUNDS	n/a	
431	SHIRLEY	3.5	

PROJECT NAME/LOCATION:
DESCRIPTION (NEW CONSTRUCTION)
68 PULASKI STREET - SINGLE FAMILY HOME

TREDO ENGINEERS
CIVIL/STRUCTURAL
7555 SENECA ST. #202
BUFFALO, NY 14210
(716) 876 - 7147
MEP
BUFFALO ENG. PC
4245 UNION RD.
BUFFALO, NY 14225
(716) 633 - 5598

**HHL Architects**
172 Allen Street, Buffalo, New York 14201
716.885.0743 ■ F: 716.885.6414
hhlarchitects.com

DRAWING TITLE
SPECIFICATIONS

ISSUE DATE: 9/19/25
DRAWING NUMBER
S201b

SEAL


EXPIRES: 10.31.25


DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

ARCHITECT OF RECORD


REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

COPYRIGHT © 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THIS
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 7209
PROVISION 2. OF THE NEW YORK
STATE EDUCATION LAW.


PROJECT NUMBER: **2317.006**
T.E. PROJ. NUMBER: **25-61**




3 REINFORCING at OPENINGS
IN CONCRETE WALLS
(4'-0" SQ. MAXIMUM OPENING SIZE)




2 WALL
CONSTRUCTION JOINT



1 HORIZONTAL
WALL REINFORCEMENT



5 ELEVATION OF
STEPPED WALL FOOTING




ALL BELOW GRADE UTILITIES SHALL PASS THRU STEM WALL (NOT FOOTING). IF UTILITY ELEVATION IS BELOW TOP OF FOOTING, UTILIZE TYPICAL ELEVATION OF STEPPED WALL FOOTING DETAIL TO LOWER FOUNDATIONS BELOW PENETRATION.

MEP SUBCONTRACTOR TO COORDINATE WITH CONTRACTOR ALL PENETRATIONS, SLEEVES, ETC.


NO PENETRATIONS OR SLEEVES SHALL BE CORED OR FIELD CUT WITHOUT THE EXPRESS APPROVAL OF THE STRUCTURAL ENGINEER OF RECORD.

IF BUNDLED UTILITIES EXCEED 24" IN WIDTH, UTILIZE TYPICAL REINFORCING at OPENING IN CONCRETE WALLS DETAIL.


4 TYPICAL SLEEVE SPACE
DETAIL IN FROST WALL




6 FOUNDATION UNDERCUT
AT DEEP FILL SITES



8 SAWCUT JOINT DETAIL
(SJ) at SLAB ON GRADE



7 TYPICAL
SLAB ON GRADE DETAIL
FOR AREAS WITH VCT, TILE OR CARPET
COORDINATE WITH ARCH. DRAWINGS



REFER TO TYPICAL SLAB ON GRADE DETAIL
FOR ADDITIONAL INFORMATION NOT SHOWN

9 THICKENED SLAB
DETAIL at STAIR BASE

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION
ARCHITECT OF RECORD

DRAWING TITLE
TYPICAL DETAILS

SEA1



ISSUE DATE: 9.19.25
DRAWING NUMBER


S202

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET - SINGLE FAMILY HOME
PROJECT NUMBER: 2317.006
T.E. PROJ. NUMBER: 25-61
BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203


TREDO ENGINEERS
CIVIL/STRUCTURAL
7555 SENECA ST. #202
BUFFALO, NY 14210
(716) 876-7147
MEP
4245 UNION RD.
BUFFALO, NY 14225
(716) 633-5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 • F: 716.885.6414
HHLArchitects.com


COPYRIGHT © 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THIS
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 7209
PROVISION 2. OF THE NEW YORK
STATE EDUCATION LAW.




3
TYP. PLYWOOD NAILING
at FLOOR DIAPHRAGM




4
TYP. PLYWOOD NAILING
at ROOF DIAPHRAGM




8
TYP. DETAIL FOR END LAPS
OF PANELIZED SHEAR WALLS



2
TYP. SHEATHING NAILING
PATTERN at SHEAR WALLS




7
PLAN VIEW at HOLDDOWNS




1
TYPICAL
LOAD BEARING WALL

STUDWALL BEARING HEADER SCHEDULE		
MARK	SIZE	MINIMUM BEARING EACH END
H1	(2) 2x6 DFL#2	(1) 2x
H2	(2) 2x8 DFL#2	(1) 2x

- NOTES
- ALL HEADERS TO HAVE A MINIMUM BEARING AS SHOWN
 - COORDINATE OPENING SIZE AND LOCATION WITH ARCH DRAWINGS
 - SEE ARCH DRAWINGS FOR NON-LOAD BEARING HEADERS



6
STUDWALL
BEARING HEADER SCHEDULE



5
TYP. BUILT-UP STUD DETAIL

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET - SINGLE FAMILY HOME

TREDO ENGINEERS
CIVIL/STRUCTURAL
755 SENECA ST. #202
BUFFALO, NY 14210
(716) 876 - 7147
MEP
4245 UNION RD.
BUFFALO, NY 14225
(716) 633 - 5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 • F: 716.885.6414
hhlarchitects.com

ARCHITECT OF RECORD

DRAWING TITLE
TYPICAL DETAILS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION


DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

SEAL


ISSUE DATE: 9.19.25
DRAWING NUMBER
S203

PROJECT NUMBER: **2317.006**
T.E. PROJ. NUMBER: **25-61**


COPYRIGHT © 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THIS
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 7209
PROVISION 2. OF THE NEW YORK
STATE EDUCATION LAW.




4 3/4" = 1'-0"




3 3/4" = 1'-0"



2A 2 3/4" = 1'-0"




1 3/4" = 1'-0"




5 3/4" = 1'-0"

COPYRIGHT © 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THIS
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 2209
PROVISION 2, OF THE NEW YORK
STATE EDUCATION LAW.


PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET - SINGLE FAMILY HOME		PROJECT NUMBER: 2317.006 T.E. PROJ. NUMBER: 25-61	
TREDO ENGINEERS CIVIL/STRUCTURAL 755 SENECA ST. #202 BUFFALO, NY 14210 (716) 876-7147	BENLIC DEVELOPMENT LLC 403 MAIN STREET, SUITE 602 BUFFALO, NEW YORK 14203 (716) 633-5598		
HHL Architects 172 Allen Street, Buffalo, New York 14201 716.885.0743 ■ F: 716.885.6414 hhlarchitects.com			
DRAWING TITLE SECTIONS and DETAILS		ARCHITECT OF RECORD	
DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION		REVISIONS AFTER ISSUANCE NO. DATE DESCRIPTION	
SEA: 		EXPIRES: 10.31.25	
ISSUE DATE: 9.19.25		DRAWING NUMBER	
S301			




3 3/4" = 1'-0"




6 3/4" = 1'-0"




2 3/4" = 1'-0"




5 3/4" = 1'-0"



1 3/4" = 1'-0"



4 3/4" = 1'-0"



7 3/4" = 1'-0"

COPYRIGHT © 2025 TREDO ENGINEERS
ALL RIGHTS RESERVED. NO PART OF THIS
DRAWING MAY BE REPRODUCED OR COPIED
IN ANY FORM BY ANY MEANS WITHOUT THE
WRITTEN PERMISSION OF THE ENGINEER.
REPRODUCTION OF THIS DRAWING FOR
USE IN THE PRODUCTION OF SHOP
AND/OR FIELD DETAIL DRAWINGS IS
EXPRESSLY FORBIDDEN.
UNAUTHORIZED ALTERATION AND/OR
DUPLICATION OF THIS DRAWING IS A
VIOLATION OF SECTION 7209
PROVISION 2, OF THE NEW YORK
STATE EDUCATION LAW.

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE

SECTIONS and DETAILS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

EXPIRES: 10.31.25

ISSUE DATE: 9.19.25
DRAWING NUMBER

PROJECT NAME/LOCATION:

DESCRIPTION [NEW CONSTRUCTION]

68 PULASKI STREET - SINGLE FAMILY HOME

BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

TREDO ENGINEERS

CIVIL/STRUCTURAL

755 SENECA ST. #202
BUFFALO, NY 14210
(716) 876 - 7147

MEP

4245 UNION RD.
BUFFALO, NY 14225
(716) 633 - 5598

HHL Architects

172 Allen Street, Buffalo, New York 14201
716.885.0743 • F: 716.885.6414
HHLArchitects.com

ARCHITECT OF RECORD

SE



EXPIRES: 10.31.25

ISSUE DATE: 9.19.25

DRAWING NUMBER

S302

ABBREVIATIONS

#	NUMBER OR POUNDS	FIXT	FIXTURE	QUAN	QUANTITY
#/CF	POUNDS PER CUBIC FOOT	FLOUR	FLOURESCENT	R	RISER
/		FLR	FLOOR, FLOORING	RAD	RADIUS
@	AT	FND	FOUNDATION	RB	RESILIENT BASE
A/E	ARCHITECTS / ENGINEER	FOW	FACE OF WALL	RCP	REFLECTED CEILING PLAN
AB	ANCHOR BOLT	FRJS	FIRE RESISTIVE JOINT SYSTEM	RD	ROOF DRAIN
AC DR	ACCESS DOOR	FRP	FIRBERGLASS REINFORCED PLASTIC	RE	REFERENCE
ACOUS	ACOUSTICAL	FRT	FIRE RETARDANT TREATED	RECT	RECTANGLE
ACPLAS	ACOUSTICAL PLASTER CEILING	FS	FULL SIZE	REF	REFRIGERATOR
CLG		FSP	FIRE STANDPIPE	REINF	REINFORCE(D)(ING)(MENT)
ACT	ACOUSTICAL CEILING TILE	FT	FOOT OR FEET	REQD	REQUIRED
AD	AREA DRAIN	FTG	FOOTING	RESIL	RESILIENT
ADDL	ADDITIONAL	FTR	FIN TUBE RADIATION	RFS	ROOM FINISH SCHEDULE
ADJ	ADJUSTABLE, ADJACENT	FURR	FURRING	RM	ROOM
AFF	ABOVE FINISHED FLOOR	FUT	FUTURE	RO	ROUGH OPENING
AHU	AIR HANDLING UNIT	FWC	FABRIC WALL COVERING	ROW	RIGHT OF WAY
ALUM	ALUMINIUM	FWP	FABRIC WRAPPED PANEL	RWC	RAIN WATER CONDUCTOR
ANOD	ANODIZED	GA	GAGE	S	SOUTH
APC	ACOUSTICAL PANEL CEILING	GALV	GALVANIZED	SB	SPLASH BLOCK
APPR	APPROXIMATE	GB	GRAB BAR	SC	SOLID CORE
ARCH	ARCHITECTURAL (OR ARCHITECT)	GFA	GROSS FLOOR AREA	SCHED	SCHEDULE
ASPH	ASPHALT	GFRC	GLASS FIBER REINFORCED CONCRETE	SECT	SECTION
AVG	AVERAGE	GL	GLASS	SF	SQUARE FEET
B/O	BY OTHERS	GND	GROUND	SFRM	SPRAYED FIRE RESISTIVE MATERIAL
BC	BRICK COURSE	GR	GRADE	SFWS	STRETCH FABRIC WALL SYSTEM
BD	BOARD	GRG	GLASS REINFORCED GYPSUM	SHR	SHOWER
BETWN	BETWEEN	GSF	GROSS SQUARE FEET	SIM	SIMILAR
BEY	BEYOND	GWB	GYPSUM WALL BOARD	SPEC	SPECIFICATIONS
BITUM	BITUMINOUS	GYP	GYPSUM	SPKLR	SPRINKLER
BL	BUILDING LINE	H	HEIGHT	SPMR	SINGLE PLY MEMBRANE ROOFING
BLDG	BUILDING	HB	HOSE BIB	SQ	SQUARE
BLKG	BLOCKING	HC	HANDICAPPED	SS	SERVICE SINK
BM	BEAM	HD	HEAD	SSM	SOLID SURFACING MATERIAL
BMK	BENCH MARK	HDW	HARDWARE	SST	STAINLESS STEEL
BOT	BOTTOM	HM	HOLLOW METAL	STA	STATION
BTU	BRITISH THERMAL UNIT	HO	HOLD OPEN	STC	SOUND TRANSMISSION CLASS
BUR	BUILT-UP ROOFING	HOR	HORIZONTAL	STD	STANDARD
C	CENTER	HP	HIGH POINT	STL	STEEL
CAB	CABINET	HR	HOUR	STOR	STORAGE
CAV	CAVITY	HT	HEIGHT	STRUCT	STRUCTURAL
CB	CATCH BASIN	HVAC	HEATING VENTILATING & AIR CONDITIONING	SUSP	SUSPENDED
CCTV	CLOSED CIRCUIT TELEVISION	HW	HOT WATER	SYM	SYMMETRICAL
CEM	CEMENT, CEMENTITIOUS	ID	INSIDE DIAMETER	T	TREAD
CF	CUBIC FEET	IG	INSULATING GLASS	T&B	TOP AND BOTTOM
CFMF	COLD FORMED METAL FRAMING	IN	INCHES	T&G	TONGUE AND GROOVE
CFT	CERAMIC FLOOR TILE	IND	INDICATED	TB	TACK BOARD
CG	CORNER GUARD	INSUL	INSULATION	TBD	TO BE DETERMINED
CH BD	CHALK BOARD	INT	INTERIOR	TEL	TELEPHONE
CHLF	CHAIN LINK FENCE	INV	INVERT	TEL/COM	TELECOMMUNICATION
CI	CAST IRON	IPS	IRON PIPE SIZE	TER	TERRAZZO
CJ	CONTROL JOINT	JAN	JANITOR	TH	THICK(NESS)
CL	CENTER LINE	JC	JANITOR'S CLOSET	TLT	TOILET
CLG	CEILING	JCT	JUNCTION	TMPD	TEMPERED
CLL	CONTRACT LIMIT LINE	JT	JOINT	TO	TOP OF
CLOS	CLOSET	KIT	KITCHEN	TOC	TOP OF CONCRETE, CURB
CLR	CLEAR	L	LONG, LENGTH	TOS	TOP OF SLAB
CM	CONSTRUCTION MANAGER	LAB	LABORATORY	TOST	TOP OF STEEL
CMU	CONCRETE MASONRY UNIT	LAM	LAMINATE	TOW	TOP OF WALL
CO	CLEAN OUT	LAV	LAVATORY	TPFS	THROUGH PENETRATION FIRESTOP SYSTEM
COL	COLUMN	LB	POUND	TYP	TYPICAL
COMP	COMPRESSIBLE	LIN	LINEAR	UC	UNDERCUT
CONC	CONCRETE	LINO	LINOLEUM	UH	UNIT HEATER
CONN	CONNECTION	LKR	LOCKER	UL	UNDERWRITERS LABORATORIES
CONSTN	CONSTRUCTION	LL	LIVELOAD	UNFIN	UNFINISHED
CONT	CONTINUOUS	LP	LOW POINT	UON	UNLESS OTHERWISE NOTED
CONTR	CONTRACTOR	LT	LIGHT	UR	URINAL
CORR	CORRIDOR	LTW	LIGHT WEIGHT	V	VENT
CPT	CARPET	LVR	LOUVER	VCT	VINYL COMPOSITION TILE
CPTT	CARPET LINE	MAX	MAXIMUM	VERT	VERTICAL
CS	CAST STONE	MB	MARKER BOARD	VEST	VESTIBULE
CSMT	CASEMENT	MDF	MEDIUM DENSITY FIBERBOARD	VIF	VERIFY IN FIELD
CT	CERAMIC TILE	MDO	MIDEUM DENSITY OVERLAY	VN	veneER
CTSK	COUNTERSUNK	MECH	MECHANICAL	VP	VENT PIPE
CU	CUBIC	MEMB	MEMBRANE	VR	VAPOR RETARDER
CUH	CABINET UNIT HEATER	MEP	MECHANICAL, ELECTRICAL & PLUMBING	VT	VINYL TILE
CW	COLD WATER	MFR	MANUFACTURER	VTR	VENT THROUGH ROOF
D	DEEP, DEPTH	MH	MANHOLE	VWC	VINYL WALL COVERING
DBL	DOUBLE	MHO	MAGNETIC HOLD OPEN	W	WEST
DEPT	DEPARTMENT	MIN	MINIMUM	WO	WITHOUT
DET	DETAIL	MISC	MISCELLANEOUS	WB	WOOD BASE
DF	DRINKING FOUNTAIN	MO	MASONRY OPENING	WC	WATER CLOSET
DH	DOUBLE HUNG	MOD BIT	MODIFIED BITUMEN (ROOF)	WD	WOOD
DIA	DIAMETER	MTD	MOUNTED	WD, FL	WOOD FLOOR
DIM	DIMENSION	MTG	MOUNTING	WP	WORKING POINT
DL	DEAD LOAD	N	NORTH	WT	WEIGHT
DN	DOWN	NEC	NATIONAL ELECTRIC CODE	WTRPRF	WATERPROOF
DO	DITTO	NIC	NOT IN CONTRACT	WWF	WLDDED WIRE FABRIC
DS	DOWNSPOUT	NO	NUMBER		
DSP	DRY STANDPIPE	NOM	NOMINAL		
DWG	DRAWING	NPS	NOMINAL PIPE SIZE		
DWR	DRAWER	NSF	NET SQUARE FEET		
E	EAST	NTS	NOT TO SCALE		
EA	EACH	OA	OVERALL		
EDP	ELECTRONIC DATA PROCESSOR	OC	ON CENTER		
EF	EXHAUST FAN	OD	OUTSIDE DIAMETER		
EIFS	EXTERIOR INSUL & FINISH SYSTEM	OFF	OFFICE		
EJ	EXPANSION JOINT	OH	OVERHEAD		
EL	ELEVATION	OPNG	OPENING		
ELEC	ELECTRICAL	OPP	OPPOSITE		
ELEV	ELEVATOR	ORD	OVERFLOW ROOF DRAIN		
EMER	EMERGENCY	P	PAINT		
ENCL	ENCLOSURE	PART	PARTIAL		
ENGR	ENGINEER(ING)	PB	PEG BOARD		
ENTR	ENTRANCE	PBD	PARTICLE BOARD		
EP	EPOXY PAINT	PERF	PERFORATED		
EPDM	ETHYLENE PROPYLENE DIENE MEMBRANE	PFAB	PREFRABICATED		
EQ	EQUAL	PFIN	PREFINISHED		
EQPT	EQUIPMENT	PL	PLATE		
EWC	ELECTRIC WATER COOLER	PLAM	PLASTIC LAMINATE		
EXP	EXPOSED	PLAS	PLASTER		
EXT	EXTERIOR	PLBG	PLUMBING		
EXTG	EXISTING	PLWD	PLYWOOD		
EXTR	EXTERIOR	PSF	POUNDS PER SQUARE FOOT		
FBD	FIBER BOARD	PSI	POUNDS PER SQUARE INCH		
FD	FLOOR DRAIN	PT	PRESERVATIVE TREATED		
FE	FIRE EXTINGUISHER	PTN	PARTITION		
FEC	FIRE EXTINGUISHER CABINET	PVC	POLYVINYL CHLORIDE		
FHC	FIRE EXTINGUISHER HOSE CABINET	PVDF	POLYVINYLIDNE FLOURIDE (KYNAR)		
FFE	FINISHED FLOOR ELEVATION	QT	QUARRY TILE		
FHC	FIRE HOSE CABINET	QUAL	QUALITY		
FIN	FINISH				

MATERIAL SYMBOLS

EARTH	
GRAVEL OR POROUS FILL	
CONCRETE MASONRY UNIT	
STONE	
CONCRETE	
FIBROUS INSULATION	
FIBER BOARD OR RIGID INSULATION	
PLASTER, GYPSUM WALL BOARD, MORTAR, OR PARTICLE BOARD	
FINISHED WOOD	
ROUGH WOOD	
PLYWOOD	
STEEL OR IRON	
ALUMINUM	

KEY TO SYMBOLS:

	BUILDING REFERENCE LINE FACE OF CMU OR FRAMING		ROOM SIGN
	ELEVATION		DOOR NUMBER
	ENLARGED DETAIL		ROOM NAME AND NUMBER
	SECTION DETAIL		GLAZING TYPE
	BUILDING SECTION		WINDOW TYPE
	WALL SECTION		ROOF TYPE
			NEW DOOR EXISTING DOOR
			TOILET ACCESSORY
			PARTITION TYPE KEYED NOTE

GENERAL NOTES

- A. ALL WORK IS TO CONFORM WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS AND AGENCIES HAVING JURISDICTION.
- B. CONTRACTOR IS TO FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO BEGINNING WORK. DO NOT SCALE DRAWINGS OR DETAILS.
- C. WHERE DIMENSIONAL DISCREPANCIES ARISE, REVIEW FIELD CONDITIONS WITH THE OWNERS REPRESENTATIVE BEFORE PROCEEDING WITH WORK OR ORDERING MATERIALS.
- D. THE CONTRACTOR IS RESPONSIBLE FOR THE PROTECTION OF ALL CONDITIONS AND MATERIALS WITHIN THE PROPOSED CONSTRUCTION AREA.
- E. ALL DETAILS, SECTIONS, AND MATERIALS SHOWN OR NOTED ON DRAWINGS SHALL APPLY TO ALL OTHER SIMILAR LOCATIONS UNLESS NOTED OTHERWISE.
- F. ALL FINISH TRIM JOINTS SHALL BE MITERED UNLESS NOTED OTHERWISE.
- G. ALL CORNERS AND JUNCTIONS WHERE TWO MATERIALS ADJOIN SHALL BE SEALED.
- H. ALL FLOOR, WALL AND CEILING INTERFACES AND PENETRATIONS SHALL BE PROPERLY SEALED TO MAINTAIN ACOUSTICAL INTEGRITY. EACH TRADE CONTRACTOR IS RESPONSIBLE FOR PENETRATION SEALING & FIRE STOPPING.
- I. ALL PENETRATIONS, GAPS AND JOINTS AT RATED FLOORS, ROOFS AND WALLS TO BE FIRE STOPPED. GAPS AND JOINTS INCLUDE (BUT NOT LIMITED TO) TOP OF WALL TO FLOOR OR ROOF DECK, WALL BEAMS, AND CONTROL OR EXPANSION JOINTS. FIRE STOPPING INCLUDES BOTH FORM OR PACKING MATERIAL AND THE FILL, VOID OR CAVITY MATERIAL.
- J. PROVIDE ACCESS PANELS OF APPROPRIATE SIZE, TYPE, AND FIRE RATING FOR ALL CONCEALED ITEMS THAT REQUIRE ADJUSTMENT, MAINTENANCE, MONITORING, ETC. COORDINATE LOCATION WITH OWNERS REPRESENTATIVE.
- K. THIS CONTRACT REQUIRES COMPLETE, FINISHED SPACES IN ALL AREAS INDICATED BY THE CONTRACT DOCUMENTS. INCLUDE ALL MATERIALS AND LABOR NECESSARY TO COMPLETE SAME, REGARDLESS OF WHETHER OR NOT EACH AND EVERY NECESSARY ITEM IS SPECIFICALLY INDICATED IN THE DRAWINGS AND/OR NOTES.
- L. ALL CONTRACTORS ARE RESPONSIBLE TO VERIFY ALL SITE, FIELD AND BUILDING CONDITIONS PRIOR TO SUBMITTING BIDS AND COMMENCING WORK. IF THERE ARE ANY DISCREPANCIES BETWEEN DRAWINGS AND FIELD CONDITIONS, CONFER WITH THE OWNERS REPRESENTATIVE FOR RESOLUTION.
- M. WOOD USED FOR BLOCKING OR OTHER PURPOSES ON OR ABOVE THE ROOF DECK SHALL BE PRESSURE TREATED TYP (P.T.)
- N. FINISHED DOOR OPENINGS SHALL BE NOMINAL @ 4" FROM FINISHED CORNER OF ROOM AT HINGE SIDE, EXCEPT WHERE DIMENSIONED OTHERWISE.
- P. MAINTAIN CONTINUITY OF ALL AIR/VAPOR BARRIERS (TYP) COORDINATE WITH ALL TRADES.
- Q. GC SHALL COORDINATE ALL WORK AT ROOF NOT TO VOID MFRG WARRANTIES.
- R. BUILDING SHALL BE TESTED AND VERIFIED AS HAVING AN AIR LEAKAGE RATE NOT EXCEEDING THREE AIR CHANGES PER HOUR TO COMPLY WITH SECTION N1102.4.1.2 (R402.4.1.2) IN THE RESIDENTIAL CODE OF NYS. WHERE REQUIRED BY THE BUILDING OFFICIAL, TESTING SHALL BE CONDUCTED BY AN APPROVED THIRD PARTY.

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET , SINGLE FAMILY HOME		PROJECT NUMBER: 2317.006	
TREDO ENGINEERING STRUCTURAL 755 SENECA ST., #202 BUFFALO, NY 14210 (716) 876, 7147			
 HHL Architects 172 Allen Street, Buffalo, New York 14201 716.885.0740 ■ F: 716.885.6414 HHLarchitects.com		ARCHITECT OF RECORD	
DRAWING TITLE GENERAL NOTES, LEGENDS, ABBREVIATIONS & PARTITIONS NO. _____ DATE _____		DESCRIPTION	
ISSUE DATE:09.19.25		DRAWING NUMBER A-001	

TECHNICAL SPECIFICATIONS - OUTLINE FORMAT

DIVISION 01 - GENERAL REQUIREMENTS

012500 - SUBSTITUTION PROCEDURES

1. SUBSTITUTION REQUESTS SHALL BE SUBMITTED TO ARCHITECT WITH DOCUMENTATION SHOWING COMPLIANCE WITH REQUIREMENTS. SUBSTITUTIONS MUST BE COMPATIBLE WITH OTHER PORTIONS OF THE WORK. SUBSTITUTIONS MUST BE COORDINATED WITH OTHER PORTIONS OF THE WORK AND ACCEPTABLE TO ALL TRADES INVOLVED. INCLUDE ANY CHANGES THE PROPOSED SUBSTITUTION HAS ON SCHEDULE AND/OR CONTRACT SUM.

012600 - CONTRACT MODIFICATION PROCEDURES

1. ARCHITECT WILL ISSUE SUPPLEMENTAL INSTRUCTIONS AUTHORIZING MINOR CHANGES IN THE WORK, NOT INVOLVING ADJUSTMENTS TO SCHEDULE OR CONTRACT SUM.
2. PROPOSAL REQUEST: CHANGES TO THE WORK THAT MAY REQUIRE ADJUSTMENT TO SCHEDULE OR CONTRACT SUM WILL BE REQUESTED WITH A DESCRIPTION OF PROPOSED CHANGES. WITHIN 14 DAYS OF REQUEST, SUBMIT A QUOTATION ESTIMATING COST OF ADJUSTMENT TO CONTRACT SUM AND SCHEDULE NECESSARY TO EXECUTE THE CHANGE. UPON OWNER'S APPROVAL OF PROPOSAL REQUEST, A CHANGE ORDER WILL BE ISSUED FOR SIGNATURES OF ARCHITECT, CONTRACTOR, AND OWNER.

012900 - PAYMENT PROCEDURES

1. SCHEDULE OF VALUES: SUBMIT SCHEDULE OF VALUES CONSISTENT WITH FORMAT OF AIA DOCUMENT G703 AT EARLIEST POSSIBLE DATE, BUT NO LATER THAN 7 DAYS BEFORE THE DATE SCHEDULE FOR SUBMITTAL OF INITIAL APPLICATIONS FOR PAYMENT.
2. APPLICATIONS FOR PAYMENT: SUBMIT MONTHLY. SUBMIT DRAFT COPY 7 DAYS PRIOR TO DUE DATE FOR REVIEW BY ARCHITECT. FINAL PAYMENT FORM WILL BE NOTARIZED AND INCLUDE LIEN WAIVERS.

013100 - PROJECT MANAGEMENT AND COORDINATION

1.1 REQUEST FOR INFORMATION (RFI)
A. UPON THE DISCOVERY OF THE NEED FOR ADDITIONAL INFORMATION, CLARIFICATION, OR INTERPRETATION OF THE CONTRACT DOCUMENTS, CONTRACTOR SHALL PREPARE AND SUBMIT AN RFI. COORDINATE AND SUBMIT RFIS IN A PROMPT MANNER TO AVOID DELAYS IN CONTRACTOR'S WORK OR WORK OF SUBCONTRACTORS.
B. INCLUDE ALL PERTINENT INFORMATION NECESSARY TO FULLY DESCRIBE ITEMS NEEDING INTERPRETATION. INCLUDE SKETCHES, DESCRIPTIONS, MEASUREMENTS, PHOTOS, PRODUCT DATA, AND SHOP OR COORDINATION DRAWINGS. INCLUDE CONTRACTOR'S SUGGESTED RESOLUTION AND IMPACTS TO THE SCHEDULE OR CONTRACT SUM.
C. ARCHITECT'S ACTION: ALLOW 7 DAYS FOR ARCHITECT TO REVIEW, DETERMINE ACTION REQUIRED, AND RESPOND TO EACH RFI.
D. REQUESTS FOR APPROVAL OF CONTRACTOR'S MEANS AND METHODS WILL BE RETURNED WITHOUT ACTION.
1.2 PROJECT MEETINGS: CONSTRUCTION MANAGER WILL SCHEDULE AND CONDUCT MEETINGS.

013300 - SUBMITTAL PROCEDURES

1.1 SUBMITTAL FORMAT
A. SUBMITTALS SHALL BE FORMATTED CONSISTENTLY WITH IDENTIFYING INFORMATION INCLUDING PROJECT NAME, DATE, NAMES OF ARCHITECT AND CONTRACTOR, UNIQUE SUBMITTAL NUMBER, AND LOCATIONS WHERE PRODUCT IS TO BE INSTALLED, AS APPROPRIATE.
B. ELECTRONIC SUBMITTALS: PREPARE SUBMITTALS AS PDF PACKAGE, INCORPORATING COMPLETE INFORMATION INTO EACH PDF FILE. NAME PDF FILE WITH SUBMITTAL NUMBER.
1.2 SUBMITTAL PROCEDURES
A. COORDINATE PREPARATION AND PROCESSING OF SUBMITTALS WITH PERFORMANCE OF CONSTRUCTION ACTIVITIES.
B. COORDINATE TRANSMITTAL OF SUBMITTALS FOR RELATED PARTS OF THE WORK SPECIFIED IN DIFFERENT SECTIONS, SO PROCESSING WILL NOT BE DELAYED BECAUSE OF NEED TO REVIEW SUBMITTALS CONCURRENTLY FOR COORDINATION. ARCHITECT RESERVES THE RIGHT TO WITHHOLD ACTION ON SUBMITTAL REQUIRING COORDINATION WITH OTHER SUBMITTALS UNTIL RELATED SUBMITTALS ARE RECEIVED.
1.3 PROCESSING TIME
A. ALLOW 7 DAYS PROCESSING TIME FOR ARCHITECT'S INITIAL REVIEW.
B. ALLOW 7 DAYS PROCESSING TIME FOR REVIEW OF EACH RESUBMITTAL.
C. SEQUENTIAL REVIEW: WHERE SEQUENTIAL REVIEW OF SUBMITTALS BY ARCHITECT'S CONSULTANTS, OWNER, OR OTHER PARTIES IS INDICATED, ALLOW 14 DAYS FOR INITIAL REVIEW OF EACH SUBMITTAL.
1.4 CONTRACTOR'S REVIEW: REVIEW EACH SUBMITTAL AND CHECK FOR COORDINATION WITH OTHER WORK OF THE CONTRACT AND FOR COMPLIANCE WITH THE CONTRACT DOCUMENTS. NOTE CORRECTIONS AND FIELD DIMENSIONS. SUBMITTALS SHALL BE MARKED WITH CONTRACTOR'S APPROVAL BEFORE SUBMITTING TO ARCHITECT.
1.5 ARCHITECT'S REVIEW:
A. ARCHITECT WILL RETURN PDF FILE WITH ARCHITECT AND/OR ENGINEER MARKUPS, INDICATING APPROPRIATE ACTION.
B. INCOMPLETE SUBMITTALS WILL BE RETURNED FOR RESUBMITTAL WITHOUT REVIEW.
C. ARCHITECT WILL RETURN WITHOUT REVIEW SUBMITTALS RECEIVED FROM SOURCES OTHER THAN CONTRACTOR.

DIVISION 03 - CONCRETE (RE STRUCT DWGS)

DIVISION 05 - METALS

057300 - DECORATIVE METAL RAILINGS

1.1 SUMMARY: ALUMINUM DECORATIVE RAILINGS
1.2 SUBMITTALS
A. PRODUCT DATA
B. SHOP DRAWINGS
C. SAMPLES
D. DELEGATED DESIGN SUBMITTAL
2.1 PERFORMANCE REQUIREMENTS
A. RAILINGS, INCLUDING ATTACHMENT TO BUILDING CONSTRUCTION, ARE TO WITHSTAND THE EFFECTS OF GRAVITY LOADS AND THE FOLLOWING LOADS AND STRESSES WITHIN LIMITS AND UNDER CONDITIONS INDICATED:
1. HANDRAILS AND TOP RAILS OF GUARDS:
a. UNIFORM LOAD OF 50 LBF/FT. APPLIED IN ANY DIRECTION.
b. CONCENTRATED LOAD OF 200 LBF APPLIED IN ANY DIRECTION.
2. INFILL OF GUARDS: CONCENTRATED LOAD OF 50 LBF APPLIED HORIZONTALLY ON ANY AREA OF 1 SQ. FT.
3. LOAD ASSUMPTION: LOADS NEED NOT BE ASSUMED TO ACT CONCURRENTLY.
B. THERMAL MOVEMENTS: ALLOW FOR THERMAL MOVEMENTS FROM AMBIENT AND SURFACE TEMPERATURE CHANGES ACTING ON EXTERIOR RAILINGS BY PREVENTING BUCKLING, OPENING OF JOINTS, OVERSTRESSING OF COMPONENTS, FAILURE OF CONNECTIONS, AND OTHER DETRIMENTAL EFFECTS.
2.2 BASIS-OF-DESIGN: ALUMI-GUARD
A. PRODUCT: YORKSHIRE
B. STYLE: CONTINUOUS TOP-CAP
C. FINISH: POWDER COAT
D. COLOR: TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE
3.1 INSTALL PER MANUFACTURER'S WRITTEN INSTRUCTIONS
3.2 TOUCH-UP PAINT SCRATCHED SURFACES USING PAINT PENS SUPPLIED BY MANUFACTURER THAT MATCH GUARDRAIL COLOR.

DIVISION 06 - WOOD, PLASTICS, AND COMPOSITES

061000 - ROUGH CARPENTRY (RE STRUCT DWGS)

061600 - SHEATHING

1.1 SUMMARY:
A. WALL SHEATHING
B. ROOF SHEATHING
C. SUBFLOORING AND UNDERLAYMENT
1.2 SUBMITTALS: PRODUCT DATA
2.1 PERFORMANCE REQUIREMENTS
A. FIRE-RESISTANCE RATINGS: AS TESTED IN ACCORDANCE WITH ASTM E119; TESTING BY A QUALIFIED TESTING AGENCY. IDENTIFY PRODUCTS WITH APPROPRIATE MARKINGS OF APPLICABLE TESTING AGENCY.
2.2 PLYWOOD WALL SHEATHING (RE STRUCT DWGS)
2.3 GLASS-MAT GYPSUM SHEATHING, WALLS: GEORGIA-PACIFIC DENSGLASS SHEATHING, TYPE X, 5/8 INCH THICK.
2.4 PLYWOOD ROOF SHEATHING (RE STRUCT DWGS)
2.5 SUBFLOORING AND UNDERLAYMENT:
A. PLYWOOD SUBFLOOR (RE STRUCT DWGS)
B. UNDERLAYMENT: 1/4 INCH SANDED PLYWOOD

061753 - SHOP-FABRICATED WOOD TRUSSES (RE STRUCT DWGS)

062013 - EXTERIOR FINISH CARPENTRY

1.1 SUMMARY: CELLULAR PVC EXTERIOR TRIM
1.2 SUBMITTALS:
A. PRODUCT DATA
B. SAMPLES
2.1 BASIS-OF-DESIGN: AZEK TRIM
A. TEXTURE: SMOOTH
3.1 INSTALL PVC TRIM TO COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS.

062023 - INTERIOR FINISH CARPENTRY

1.1 SUMMARY: INTERIOR TRIM
1.2 SUBMITTALS:
A. PRODUCT DATA
1.3 FIELD CONDITIONS: DO NOT DELIVER OR INSTALL INTERIOR FINISH CARPENTRY MATERIALS UNTIL BUILDING IS ENCLOSED AND WEATHERPROOF. WET-WORK IN SPACE IS COMPLETED AND NOMINALLY DRY, AND HVAC SYSTEM IS OPERATING AND MAINTAINING TEMPERATURE AND RELATIVE HUMIDITY AT OCCUPANCY LEVELS DURING THE REMAINDER OF THE CONSTRUCTION PERIOD.
2.1 MATERIALS:
A. LUMBER TRIM FOR OPAQUE (PAINTED) FINISH: EASTERN WHITE, IDAHO WHITE, LODGEPOLE, PONDEROSA, RADIATA, OR SUGAR PINT
1. OPTIONAL MATERIAL: PRIMED MDF OF SAME ACTUAL DIMENSIONS AS LUMBER INDICATED MAY BE USED IN LIEU OF LUMBER.
B. LUMBER FOR TRANSPARENT FINISH (STAIN OR CLEAR FINISH): RED OAK OR WHITE MAPLE

DIVISION 07 - THERMAL AND MOISTURE PROTECTION

072100 - THERMAL INSULATION

1.1 SUMMARY:
A. EXTRUDED POLYSTYRENE (XPS) FOAM-PLASTIC BOARD INSULATION
B. GLASS-FIBER BLANKET INSULATION
1.2 SUBMITTALS:
A. PRODUCT DATA
2.1 PERFORMANCE REQUIREMENTS
A. SURFACE-BURNING CHARACTERISTICS: MAXIMUM FLAME-SPREAD AND SMOKE-DEVELOPED INDEXES LESS THAN 25 AND 450 WHEN TESTED IN ACCORDANCE WITH ASTM E84.
B. THERMAL-RESISTANT VALUE: R-VALUE AS INDICATED ON DRAWINGS.
2.2 EXTRUDED POLYSTYRENE FOAM-PLASTIC BOARD INSULATION, TYPE IV: ASTM C578, TYPE IV, 25-PSI MINIMUM COMPRESSIVE STRENGTH, UNFACED.
2.3 GLASS-FIBER BLANKET INSULATION, KRAFT FACED: ASTM C665, TYPE II (NONREFLECTIVE FACED), CLASS C (FACED SURFACE NOT RATED FOR FLAME PROPAGATION); CATEGORY 1 (MEMBRANE IS A VAPOR BARRIER).
2.4 ACCESSORIES
A. INSULATION FOR MISCELLANEOUS VOIDS: SPRAY POLYURETHANE FOAM INSULATION: ASTM C1029, TYPE II, CLOSED CELL, WITH MAXIMUM FLAME-SPREAD AND SMOKE-DEVELOPED INDEXES OF 75 AND 450, RESPECTIVELY. PER ASTM E84.
B. EAVE VENTILATION TROUGHS; PREFORMED, RIGID FIBERBOARD OR PLASTIC SHEETS DESIGNED AND SIZED TO FIT BETWEEN ROOF FRAMING MEMBERS AND TO PROVIDE VENTILATION BETWEEN INSULATED ATTIC SPACES AND VENTED EAVES.
3.1 EXECUTION
A. PREP SURFACES & INSTALL PER MANUFACTURER'S WRITTEN INSTRUCTIONS.

072500 - WEATHER BARRIERS

1.1 SUMMARY:
A. BUILDING WRAP
B. FLEXIBLE FLASHING
1.2 SUBMITTALS: PRODUCT DATA
2.1 BUILDING WRAP BASIS-OF-DESIGN: TYVEK HOMEWRAP OR APPROVED EQUAL
2.2 FLEXIBLE FLASHING BASIS-OF-DESIGN: DUPONT FLEXWRAP OR APPROVED EQUAL
3.1 INSTALLATION:
A. COVER EXPOSED EXTERIOR SURFACE OF SHEATHING WITH BUILDING WRAP SECURELY FASTENED TO FRAMING IMMEDIATELY AFTER SHEATHING IS INSTALLED. COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS AND WARRANTY REQUIREMENTS.
B. APPLY FLEXIBLE FLASHING TO COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS. LAP FLASHING OVER BUILDING WRAP AT BOTTOM AND SIDES OF OPENINGS. LAP BUILDING WRAP OVER FLASHING AT HEADS OF OPENINGS.

073113 - ASPHALT SHINGLES

1.1 SUMMARY:
A. GLASS-FIBER-REINFORCED ASPHALT SHINGLES
B. UNDERLAYMENT MATERIALS
C. RIDGE VENTS
D. METAL FLASHING AND TRIM
1.2 SUBMITTALS: PRODUCT DATA & SAMPLES
1.3 MAINTENANCE MATERIALS SUBMITTALS: FURNISH 33 SQ. FT. OF ASPHALT SHINGLES IN UNOPENED, PACKAGED BUNDLE.
1.4 STORE ROOFING MATERIALS IN A DRY, WELL-VENTILATED LOCATION PROTECTED FROM WEATHER, SUNLIGHT, AND MOISTURE IN ACCORDANCE WITH MANUFACTURER'S WRITTEN INSTRUCTIONS.
1.5 WARRANTY:
A. MATERIALS: 25 YEARS FROM DATE OF SUBSTANTIAL COMPLETION, PRORATED, WITH FIRST 10 YEARS NONPRORATED.
B. WIND-SPEED: UP TO 130 MPH
C. ALGAE-RESISTANCE WARRANTY: 25 YEARS
2.1 GLASS-FIBER-REINFORCED ASPHALT SHINGLES BASIS-OF-DESIGN:
1. PINNACLE PRISTINE HIGH PERFORMANCE ARCHITECTURAL SHINGLES WITH SCOTCHGUARD ASPHALT SHINGLES
2. COLOR: MAJESTIC SHAKE
2.2 UNDERLAYMENT MATERIALS:
1. SYNTHETIC UNDERLAYMENT BASIS-OF-DESIGN: OWENS CORNING PROARMOR
2. ICE & WATER BARRIER BASIS-OF-DESIGN: OWENS CORNING RHINOROF
GRANULATED
2.3 RIDGE VENTS: MANUFACTURER'S STANDARD, RIGID-SECTION, HIGH-DENSITY, UV-STABILIZED PLASTIC RIDGE VENT FOR USE UNDER RIDGE SHINGLES.
2.4 METAL FLASHING AND TRIM: ALUMINUM, MILL FINISHED
2.5 ACCESSORIES: AIR INTAKE VENTS: DCI PRODUCTS SMARTVENT, TAPERED UNDER-SHINGLE ATTIC INTAKE VENTILATION
A. APRON FLASHINGS, STEP FLASHINGS, AND DRIP EDGE FLASHINGS
B. VENT-PIPE FLASHINGS: ASTM B749, TYPE L51121, AT LEAST 1/16 INCH THICK. PROVIDE LEAD SLEEVE SIZED TO SLIP OVER AND TURN DOWN INTO PIPE, SOLDERED TO SKIRT AT SLOPE OF ROOF, AND EXTENDING AT LEAST 4 INCHES FROM PIPE ONTO ROOF.
3.1 INSTALLATION
A. FOLLOW MANUFACTURERS' WRITTEN INSTRUCTIONS.
B. INSTALL METAL FLASHINGS IN ACCORDANCE WITH RECOMMENDATIONS IN NRCA'S "NRCA GUIDELINES FOR ASPHALT SHINGLE ROOF SYSTEMS."

074633 - VINYL SIDING

1.1 SUMMARY:
A. VINYL SIDING
B. VINYL SOFFIT
1.2 SUBMITTALS:
A. PRODUCT DATA INCLUDE CONSTRUCTION DETAILS, MATERIAL DESCRIPTION, DIMENSIONS OF INDIVIDUAL COMPONENTS AND PROFILES AND FINISHES.
B. SAMPLES OF COLOR AND TEXTURE
C. SAMPLE WARRANTY: MANUF. AGREES TO REPAIR OR REPLACE PRODUCTS THAT FAIL IN MATERIALS OR WORKMANSHIP WITHIN 10 YEARS.
1. FAILURES INCLUDE BUT ARE NOT LIMITED TO THE FOLLOWING:
A. STRUCTURAL FAILURES INCLUDING CRACKING, FADING AND DEFORMING
B. DETERIORATION OF MATERIALS BEYOND NORMAL WEATHERING
2. FADING IS DEFINED AS LOSS OF COLOR, AFTER CLEANING WITH PRODUCT RECOMMENDED BY MANUF OF MORE THAN 4 HUNTER COLOR DIFFERENCE UNITS AS MEASURED ACCORDING TO ASTM D2244.
2.1 PRODUCTS:
A. VINYL SIDING BASIS-OF-DESIGN: ALSIDE ODYSSEY PLUS PREMIUM VINYL SIDING
1. SUBTLE WOODGRAIN TEXTURE
2. 0.044 INCH PANEL THICKNESS.
3. ROLLED OVER NAILING HEM
4. 1/2 INCH PANEL PROJECTION (D4) PROFILE
5. 5 INCH CLAPBOARD
6. COLOR: SEE FINISH SCHEDULE, A-901
B. VINYL SOFFIT BASIS-OF-DESIGN: ALSIDE ALLIANCE T4 PREMIUM VINYL SOFFIT
1. TEXTURE: SMOOTH
2. COLOR: GLACIER WHITE
3. VENTILATION: PROVIDE UNPERFORATED SOFFIT UNLESS OTHERWISE INDICATED.
3.1 EXECUTION:
A. INSTALL ALL VINYL PRODUCTS IN COMPLIANCE WITH MANUFACTURER'S WRITTEN INSTRUCTIONS AND ASTM D4756.
1. CENTER NAIL IN ELONGATED NAILING SLOTS WITHOUT BINDING SIDING TO ALLOW FOR THERMAL MOVEMENT.
2. INSTALL FASTENERS FOR HORIZONTAL VINYL SIDING NO MORE THAN 16 IN. O.C.
B. INSTALL JOINT SEALANTS TO PRODUCE WEATHERTIGHT INSTALLATION.
C. CLEAN FINISHED SURFACES ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS AND MAINTAIN IN A CLEAN CONDITION DURING CONSTRUCTION.

077100 - ROOF SPECIALTIES

1.1 SUMMARY: ROOF-EDGE DRAINAGE SYSTEMS
A. SUBMITTALS: PRODUCT DATA
2.1 PERFORMANCE REQUIREMENTS: ROOF-EDGE DRAINAGE SYSTEMS
A. GUTTERS: MANUFACTURED IN UNIFORM SECTION LENGTHS NOT EXCEEDING 12 FEET WITH MATCHING CORNER UNITS, ENDS, OUTLET TUBES, AND OTHER ACCESSORIES. ELEVATE BACK EDGE AT LEAST 1 INCH ABOVE FRONT EDGE. FURNISH FLAT-STOCK GUTTER STRAPS, GUTTER BRACKETS, EXPANSION JOINTS, AND EXPANSION-JOINT COVERS FABRICATED FROM SAME METAL AS GUTTERS.
1. ALUMINUM SHEET MATERIAL: 0.032 INCH THICK, ASTM B209
2. GUTTER PROFILE: STYLE K
3. ACCESSORIES: CONTINUOUS SCREENED LEAF GUARD W/ SHEET METAL FRAME
B. DOWNSPOUTS: CORRUGATED RECTANGULAR COMPLETE WITH MACHINE-CRIMPED ELBOWS, MANUFACTURER FROM THE SAME METAL AS GUTTERS. FURNISH WITH METAL HANGERS, FROM SAME MATERIAL AS DOWNSPOUTS, AND ANCHORS.
C. ALUMINUM FINISH: TWO-COAT FLUOROPOLYMER
1. COLOR: AS SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.
3.1 EXECUTION:
A. INSTALL ROOF SPECIALTIES IN ACCORDANCE WITH MANUFACTURER'S WRITTEN INSTRUCTIONS. ANCHOR ROOF SPECIALTIES IN PLACE, WITH PROVISIONS FOR THERMAL AND STRUCTURAL MOVEMENT. USE FASTENERS, SOLDER, PROTECTIVE COATINGS, SEPARATORS, SEALANTS, AND OTHER MISCELLANEOUS ITEMS AS REQUIRED TO COMPLETE ROOF-SPECIALTY SYSTEMS.
B. COORDINATE INSTALLATION OF ROOF PERIMETER FLASHING WITH INSTALLATION OF ROOD-EDGE DRAINAGE SYSTEM.

DRAWING SUBMISSION STATUS: NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION		PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET , SINGLE FAMILY HOME		PROJECT NUMBER: 2317.006	
DRAWING TITLE OUTLINE SPECS		TREDO ENGINEERING STRUCTURAL 755 SENECA ST., #202 BUFFALO, NY 14210 (716) 876 , 7147		BENIC DEVELOPMENT LLC 403 MAIN STREET, SUITE 602 BUFFALO, NEW YORK 14203	
REVISIONS AFTER ISSUANCE NO. DATE		HHLArchitects 172 Allen Street, Buffalo, New York 14201 716.885.0742 ■ F: 716.885.6414 HHLarchitects.com		MEP 4245 UNION RD, BUFFALO, NY 14225 (716) 633 , 5598	
SEAL 		ISSUE DATE:09.19.25		DRAWING NUMBER A-002	

079200 - JOINT SEALANTS

- 1.1 SUMMARY:
A. SILICONE JOINT SEALANTS
B. URETHANE JOINT SEALANTS
C. MILDEW-RESISTANT JOINT SEALANTS
D. LATEX JOINT SEALANTS
1.2 SUBMITTALS: PRODUCT DATA
2.1 PRODUCTS
A. COMPATIBILITY: PROVIDE JOINT SEALANTS, BACKINGS, AND OTHER RELATED MATERIALS THAT ARE COMPATIBLE WITH ONE ANOTHER AND WITH JOINT SUBSTRATES UNDER CONDITIONS OF SERVICE AND APPLICATION, AS DEMONSTRATED BY JOINT-SEALANT MANUFACTURER, BASED ON TESTING AND FIELD EXPERIENCE.
B. COLOR OF EXPOSED JOINT SEALANTS: AS SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.
C. SILICONE JOINT SEALANT: SINGLE-COMPONENT, NONSAG, PLUS 25 PERCENT AND MINUS 25 PERCENT MOVEMENT CAPABILITY, NONTRAFFICE-USE, NEUTRAL-CURING SILICONE JOINT SEALANT; ASTM C920, TYPE S, GRADE NS, CLASS 25, USE NT.
D. URETHANE JOINT SEALANT: SINGLE-COMPONENT, NON SAG, PLUS 25 PERCENT AND MINUS 25 PERCENT MOVEMENT CAPABILITY, TRAFFIC- AND NONTRAFFIC-USE, URETHANE JOINT SEALANT; ASTM C920, TYPE S, GRADE NS, CLASS 25, USES T AND NT.
E. MILDEW-RESISTANT JOINT SEALANT: SILICONE, MILDEW RESISTANT, SINGLE-COMPONENT, NONSAG, PLUS 25 AND MINUS 25 PERCENT MOVEMENT CAPABILITY, NONTRAFFICE-USE, ACID-CURING SILICONE JOINT SEALANT; ASTM C920, TYPE S, GRADE NS, CLASS 25, USE NT.
F. LATEX JOINT SEALANT: ACRYLIC LATEX OR SILICONIZED ACRYLIC LATEX, ASTM C834, TYPE OP, GRADE NF.
G. JOINT-SEALANT BACKING MATERIAL: NONSTAINING, COMPATIBLE WITH JOINT SUBSTRATES, SEALANTS, PRIMERS, AND OTHER JOINT FILLERS; AND APPROVED FOR APPLICATIONS INDICATED BY SEALANT MANUFACTURER. CYLINDRICAL SEALANT BACKINGS, ASTM C1330, TYPE C, AND OF SIZE AND DENSITY TO CONTROL SEALANT DEPTH.
3.1 PREPARATION: SURFACE CLEANING OF JOINTS TO COMPLY WITH JOINT-SEALANT MANUFACTURER'S WRITTEN INSTRUCTIONS. PRIME JOINT SUBSTRATE WHERE RECOMMENDED.
3.2 INSTALLATION: COMPLY WITH JOINT-SEALANT MANUFACTURER'S WRITTEN INSTALLATION INSTRUCTIONS. COMPLY WITH RECOMMENDATIONS IN ASTM C1193.
3.3 CLEAN OFF EXCESS SEALANT OR SEALANT SMEARS ADJACENT TO JOINTS.

DIVISION 08 - OPENINGS

- 081433 - STILE AND RAIL WOOD DOORS
1.1 SUMMARY: EXTERIOR AND INTERIOR STILE AND RAIL WOOD DOORS.
1.2 SUBMITTALS: PRODUCT DATA
1.3 ENVIRONMENTAL LIMITATIONS: DO NOT DELIVER OR INSTALL DOORS UNTIL SPACES ARE ENCLOSED AND WEATHERTIGHT, WET WORK IN SPACES IS COMPLETE AND DRY, AND HVAC SYSTEM IS OPERATING AND MAINTAINING TEMPERATURE AND RELATIVE HUMIDITY LEVELS DESIGNED FOR BUILDING OCCUPANTS FOR THE REMAINDER OF CONSTRUCTION PERIOD.
1.4 WARRANTY PERIOD: ONE YEAR
2.1 PERFORMANCE REQUIREMENTS:
A. EXTERIOR DOOR THERMAL TRANSMITTANCE: MAXIMUM WHOLE FENESTRATION PRODUCT U-FACTOR OF 0.30 BTU/SQ. FT. X H X DEG F, IN ACCORDANCE WITH AAMA 1503, ASTM E1423, OR NFRC 100.
2.2 EXTERIOR STILE AND RAIL WOOD DOORS: EXTERIOR STOCK DOORS COMPLYING WITH THE AWI, AWMAC, AND W1'S ARCHITECTURAL WOODWORK STANDARDS OR WDMA I.S. 6A.
A. PERFORMANCE GRADE: HEAVY DUTY
B. FINISH: TRANSPARENT
C. SPECIES: DOUGLAS FIR, RED OAK, OR MAPLE
2.3 INTERIOR STILE AND RAIL WOOD DOORS: INTERIOR STOCK DOORS COMPLYING WITH AWI, ASMAC, AND W1'S ARCHITECTURAL WOODWORK STANDARDS OR WDMA I.S. 6A.
A. PERFORMANCE GRADE: STANDARD DUTY
B. FINISH: OPAQUE
3.1 INSTALLATION: INSTALL DOORS AND FRAMES TO COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS AND REFERENCED QUALITY STANDARDS.

- 081613 - FIBERGLASS DOORS
1.1 SUMMARY: PREHUNG EXTERIOR FIBERGLASS DOORS
1.2 SUBMITTALS: PRODUCT DATA
2.1 PERFORMANCE REQUIREMENTS:
A. EXTERIOR DOOR THERMAL TRANSMITTANCE: MAXIMUM WHOLE FENESTRATION PRODUCT U-FACTOR OF 0.30 BTU/SQ. FT. X H X DEG F.
B. MANUFACTURE: MASONITE OR APPROVED EQUAL
C. FACTORY FINISHED, COLOR AS SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.
3.1 INSTALLATION: INSTALL DOORS AND FRAMES TO COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS.

- 085313 - VINYL WINDOWS
1.1 SUMMARY: VINYL-FRAMED WINDOWS
1.2 SUBMITTALS:
A. PRODUCT DATA
B. PRODUCT SCHEDULE: USE SAME DESIGNATIONS INDICATED ON DRAWINGS.
1.3 MANUFACTURER'S WARRANTY: MANUFACTURER AGREES TO REPAIR OR REPLACE VINYL WINDOWS THAT FAIL IN MATERIALS OR WORKMANSHIP WITHIN WARRANTY PERIOD OF 10 YEARS.
2.1 WINDOW PERFORMANCE REQUIREMENTS
A. PRODUCT STANDARD: COMPLY WITH AAMA/WDMA/CSA 101/I.S.2/A440 FOR DEFINITIONS AND MINIMUM STANDARDS OF PERFORMANCE, MATERIALS, COMPONENTS, ACCESSORIES, AND FABRICATION.
1. WINDOW CERTIFICATION: WDMA CERTIFIED WITH LABEL ATTACHED TO EACH WINDOW.
B. PERFORMANCE CLASS AND GRADE: AAMA/WDMA/CSA 101/I.S.2/A440 AS FOLLOWS:
1. MINIMUM PERFORMANCE CLASS: R
2. MINIMUM PERFORMANCE GRADE: 35
C. THERMAL TRANSMITTANCE: NFRC 100 MAXIMUM WHOLE-WINDOW U-FACTOR OF 0.30 BTU/SQ. FT. X H X DEG F.
D. SOLAR HEAT-GAIN COEFFICIENT (SHGC): NFRC 200 MAXIMUM WHOLE-WINDOW SHGC OF 0.50.
E. SOUND TRANSMISSION CLASS (STC): RATED FOR NOT LESS THAN 26 STC WHEN TESTED FOR LABORATORY SOUND TRANSMISSION LOSS ACCORDING TO ASTM E90 AND DETERMINED BY ASTM E413.
2.2. VINYL WINDOW BASIS-OF-DESIGN: PELLA 250 SERIES
A. FRAMES AND SASHES: IMPACT-RESISTANT, UV-STABILIZED PVC COMPLYING WITH AAMA/WDMA/CSA 101/I.S.2/A440
1. FINISH: INTEGRAL COLOR, WHITE
B. INSULATING-GLASS UNITS: ASTM E2190
1. DUAL-PANE INSULATING GLASS W/ ARGON
2. LOW E COATING
2. KIND: FULLY TEMPERED WHERE INDICATED ON DRAWINGS
C. HARDWARE: MANUFACTURER'S STANDARD HARDWARE IN WHITE FINISH.
1. WINDOW OPENING CONTROL DEVICE TO LIMIT CLEAR OPENING TO 4 INCHES FOR VENTILATION W/ OVERRIDE FOR EMERGENCY ESCAPE AND RESCUE.

- 2.3 ACCESSORIES:
A. DIVIDERS (FALSE MUNTINS): PROVIDE DIVIDER GRILLES IN PATTERN AS INDICATED ON DRAWINGS, BASIS-OF-DESIGN: PELLA GRILLES-BETWEEN-THE-GLASS CONTOUR 3/4"
1. COLOR: TO MATCH EXTERIOR FRAME COLOR
2.4 INSECT SCREENS: FULL-SIZE SET IN ALUMINUM FRAME AND FITTED TO EXTERIOR OF WINDOW. SCREEN FRAME FINISH IS BAKED ENAMEL, COLOR TO MATCH EXTERIOR
3.1 INSTALLATION: COMPLY WITH MANUFACTURER'S WRITTEN INSTRUCTIONS FOR INSTALLING WINDOWS, HARDWARE, ACCESSORIES, AND OTHER COMPONENTS. FOR INSTALLATION PROCEDURES AND REQUIREMENTS NOT ADDRESSED IN MANUFACTURER'S WRITTEN INSTRUCTIONS, COMPLY WITH INSTALLATION REQUIREMENTS IN ASTM E2112.
3.2 CLEANING AND PROTECTION: CLEAN EXPOSED SURFACES IMMEDIATELY AFTER INSTALLING WINDOWS. KEEP PROTECTIVE FILMS AND COVERINGS IN PLACE UNTIL FINAL CLEANING.
A. REMOVE AND REPLACE SASHES IF GLASS HAS BEEN BROKEN, CHIPPED, CRACKED, ABRADED, OR DAMAGED DURING CONSTRUCTION PERIOD.

- 086000 - RETRACTABLE ATTIC LADDERS
1.1 SUBMITTAL: PRODUCT DATA
2.1 BASIS-OF-DESIGN: FAKRO STEEL FOLDING ATTIC LADDER LMS 22.5X47
A. ANSI TESTED LOAD CAPACITY OF 350 LB MIN.
B. ACCESSORIES: OPENING ROD
3.1 INSTALL PER MANUFACTURER'S WRITTEN INSTRUCTIONS

- 087100 - DOOR HARDWARE
1.1 SUBMITTALS:
A. PRODUCT DATA
B. FINISH SAMPLES
D. DOOR HARDWARE SCHEDULE
2.1 PRODUCTS: RE DOOR SCHEDULE FOR HARDWARE SETS BASIS-OF-DESIGN
2.2 PERFORMANCE REQUIREMENTS: MEANS OF EGRESS DOORS: LATCHES DO NOT REQUIRE MORE THAN 15 LBF TO RELEASE THE LATCH. LOCKS DO NOT REQUIRE USE OF A KEY, TOOL, OR SPECIAL KNOWLEDGE FOR OPERATION.
2.3 FINISHES: PROVIDE FINISHES COMPLYING WITH ANSI/BHMA A156.18 AS INDICATED IN DOOR HARDWARE SCHEDULE.
3.1 PREPARATION & INSTALLATION: COMPLY WITH DOOR AND HARDWARE MANUFACTURER'S WRITTEN INSTRUCTIONS.
A. THRESHOLDS: SET THRESHOLDS FOR EXTERIOR DOORS AND OTHER DOORS INDICATED IN FULL BED OF SEALANT.
3.2 CLEAN AND PROTECT EXPOSED SURFACES

DIVISION 09 - FINISHES

- 092900 - GYPSUM BOARD
1.1 SUMMARY:
A. INTERIOR GYPSUM BOARD
B. RELATED REQUIREMENTS: SEE SECTION 061600 "SHEATHING" FOR GYPSUM SHEATHING FOR EXTERIOR WALLS
1.2 SUBMITTALS: PRODUCT DATA
1.3 FIELD CONDITIONS: DO NOT INSTALL PAPER-FACED GYPSUM PANELS UNTIL INSTALLATION AREAS ARE ENCLOSED AND CONDITIONED. DO NOT INSTALL PANELS THAT ARE WET, MOISTURE DAMAGED, OR MOLD DAMAGED.
2.1 PERFORMANCE REQUIREMENTS:
A. FIRE-RESISTANCE-RATED ASSEMBLIES: FOR FIRE-RESISTANCE-RATED ASSEMBLIES, PROVIDE MATERIALS AND CONSTRUCTION IDENTICAL TO THOSE TESTED IN ASSEMBLY INDICATED IN ACCORDANCE WITH ASTM E119 BY AN INDEPENDENT TESTING AGENCY.
2.2 INTERIOR GYPSUM BOARD PRODUCTS
A. GYPSUM WALLBOARD: ASTM C1396/C1396M
1. MANUFACTURER: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, AVAILABLE MANUFACTURERS OFFERING PRODUCTS THAT MAY BE INCORPORATED INTO THE WORK INCLUDE, BUT ARE NOT LIMITED TO, THE FOLLOWING:
a. GEORGIA-PACIFIC GYPSUM LLC
b. NATIONAL GYPSUM COMPANY
c. PABCO GYPSUM
d. USG CORPORATION
2. THICKNESS: 1/2 INCH
B. GYPSUM BOARD, TYPE X: ASTM C1396/C1396M
1. MANUFACTURER: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, AVAILABLE MANUFACTURERS OFFERING PRODUCTS THAT MAY BE INCORPORATED INTO THE WORK INCLUDE, BUT ARE NOT LIMITED TO, THE FOLLOWING:
a. GEORGIA-PACIFIC GYPSUM LLC
b. NATIONAL GYPSUM COMPANY
c. PABCO GYPSUM
d. USG CORPORATION
2. THICKNESS: 5/8 INCH
C. MOLD-RESISTANT GYPSUM BOARD: ASTM C1396M. WITH MOISTURE- AND MOLD-RESISTANT CORE AND PAPER SURFACES.
1. MANUFACTURER: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, AVAILABLE MANUFACTURERS OFFERING PRODUCTS THAT MAY BE INCORPORATED INTO THE WORK INCLUDE, BUT ARE NOT LIMITED TO, THE FOLLOWING:
a. GEORGIA-PACIFIC GYPSUM LLC
b. NATIONAL GYPSUM COMPANY
c. PABCO GYPSUM
d. USG CORPORATION

- 2.3 INTERIOR TRIM: ASTM C1047
A. MATERIAL: GALVANIZED OR ALUMINUM-COATED STEEL SHEET, ROLLED ZINC, OR PAPER-FACED GALVANIZED-STEEL SHEET
B. SHAPE: CORNERBEAD
2.4 JOINT TREATMENT MATERIALS: COMPLY W/ ASTM C475/C475M.
A. JOINT TAPE: PAPER
B. JOINT COMPOUND: TYPE FOR EACH COAT, USE FORMULATION THAT IS COMPATIBLE WITH OTHER COMPOUNDS APPLIED ON PREVIOUS OR FOR SUCCESSIVE COATS.
2.5 SOUND-ATTENUATION BLANKETS: ASTM C665, TYPE I (BLANKETS WITHOUT MEMBRANE FACING)
2.6 ACOUSTICAL SEALANT
3.1 INSTALLATION: COMPLY WITH ASTM C840.
A. INSTALL GYPSUM PANELS OVER WOOD FRAMING, WITH FLOATING INTERNAL CORNER CONSTRUCTION. DO NO ATTACH GYPSUM PANELS ACROSS THE FLAT GRAIN OF WIDE-DIMENSION LUMBER, INCLUDING FLOOR JOISTS AND HEADERS. FLOAT GYPSUM PANELS OVER THESE MEMBERS OR PROVIDE CONTROL JOINTS TO COUNTERACT WOOD SHRINKAGE.
B. ON CEILINGS, APPLY GYPSUM PANELS BEFORE WALL/PARTITION BOARD APPLICATION TO GREATEST EXTEND POSSIBLE AND AT RIGHT ANGLES TO FRAMING UNLESS OTHERWISE INDICATED.
C. CONTROL JOINTS: INSTALL CONTROL JOINTS IN ACCORDANCE WITH ASTM C840 AND IN SPECIFIC LOCATIONS APPROVED BY ARCHITECT FOR VISUAL EFFECT.
3.2 GYPSUM BOARD FINISH LEVELS: FINISH PANELS TO LEVELS INDICATED BELOW AND IN ACCORDANCE WITH ASTM C840:
A. LEVEL 1: CONCEALED AREAS, ATTIC, MECHANICAL CLOSET
C. LEVEL 3: ALL FINISHED WALLS & CEILINGS UNLESS OTHERWISE NOTED
3.3 PROTECT INSTALLED PRODUCTS FROM DAMAGE FROM WEATHER, CONDENSATION, DIRECT SUNLIGHT, CONSTRUCTION, AND OTHER CAUSES DURING REMAINDER OF THE CONSTRUCTION PERIOD.

- 093013 - CERAMIC TILING
1.1 SUMMARY: GLAZED WALL TILE
1.2 SUBMITTALS:
A. PRODUCT DATA
B. SAMPLES
2.1 TILE PRODUCTS: SEE INTERIOR FINISH SCHEDULE FOR BASIS-OF-DESIGN PRODUCTS
A. GROUT COLOR: AS SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE
2.2 SETTING MATERIALS: ORGANIC ADHESIVE: ANSI A136.1, TYPE 1
2.3 GROUT MATERIALS: STANDARD CEMENT GROUT: ANSI A118.6
2.4 MIXING MORTARS AND GROUT: MIX MORTARS AND GROUTS TO COMPLY WITH REFERENCED STANDARDS AND MORTAR AND GROUT MANUFACTURER'S WRITTEN INSTRUCTIONS.
3.1 INSTALLATION: COMPLY WITH TCNA'S "HANDBOOK FOR CERAMIC, GLASS, AND STONE TILE INSTALLATION" FOR INSTALLATION METHOD: TCNA W242, ORGANIC ADHESIVE ON GYPSUM BOARD.
A. JOINT WIDTH: AS RECOMMENDED BY TILE MANUFACTURER
3.2 CLEANING: ON COMPLETION OF PLACEMENT AD GROUTING, CLEAN ALL CERAMIC TILE SURFACES SO THEY ARE FREE OF FOREIGN MATTER.
3.3 PROTECT FINISHED WORK DURING CONSTRUCTION

- 096519 - RESILIENT TILE FLOORING
1.1 SUMMARY: SOLID VINYL FLOOR TILE
1.2 SUBMITTALS:
A. PRODUCT DATA
B. SAMPLES
C. MAINTENANCE MATERIALS: FURNISH ONE BOX OF SOLID VINYL FLOOR TILES THAT ARE PACKAGED WITH PROTECTIVE COVERING FOR STORAGE AND IDENTIFIED WITH LABELS DESCRIBING CONTENTS.
1.3 FIELD CONDITIONS: INSTALL FLOOR TILE AFTER OTHER FINISHING OPERATIONS, INCLUDING PAINTING, HAVE BEEN COMPLETE.
2.1 SOLID VINYL FLOOR TILE PRODUCTS: SEE INTERIOR FINISH SCHEDULE FOR BASIS-OF-DESIGN PRODUCTS.
2.2 INSTALLATION MATERIALS
A. TROWELABLE LEVELING AND PATCHING COMPOUNDS: HYDRAULIC, PORTLAND/CSA CEMENT COMPOUND APPROVED BY FLOOR TILE AND ADHESIVE MANUFACTURERS FOR APPLICATIONS INDICATED.
C. ADHESIVES: WATERPROOF ADHESIVE RECOMMENDED BY FLOOR TILE AND ADHESIVE MANUFACTURERS TO SUIT FLOOR TILE AND SUBSTRATE CONDITIONS INDICATED.
1. BASIS-OF-DESIGN: AQUAFLEX WATERPROOF INSTALLATION SYSTEM
3.1 EXECUTION: PREPARE SUBSTRATES, FILL CRACKS & DEPRESSIONS, AND INSTALL FLOOR TILE TO COMPLY WITH MANUFACTURERS' WRITTEN INSTRUCTIONS.
3.2 WOOD SUBFLOORS: VERIFY UNDERLAYMENT OVER SUBFLOOR COMPLIES WITH REQUIREMENTS SPECIFIED IN SECTION 061600 "SHEATHING."
3.3 CLEAN AND PROTECT FINISHED WORK DURING CONSTRUCTION

- 096816 - SHEET CARPETING
1.1 SUMMARY: TUFTED CARPET
1.2 SUBMITTALS:
A. PRODUCT DATA
B. SAMPLES
C. WARRANTY-10 YEARS
1.3 FIELD CONDITIONS: DO NOT INSTALL CARPET CONCRETE SLABS UNTIL SLABS HAVE CURED AND ARE SUFFICIENTLY DRY TO BOND WITH ADHESIVE AND CONCRETE SLABS HAVE PH RANGE RECOMMENDED BY CARPET TILE MANUFACTURER.
2.1 CARPET PRODUCTS: SEE INTERIOR FINISH SCHEDULE FOR BASIS-OF-DESIGN PRODUCTS.
A. ACCESSORIES: PROVIDE MATCHING CARPET FOR INSTALLATION ON STAIRS.
3.1 EXAMINATION: PERFORM CONCRETE SLAB MOISTURE TESTS AS RECOMMENDED IN WRITING BY ADHESIVE AND CARPET TILE MANUFACTURERS.
A. WOOD SUBFLOORS: VERIFY UNDERLAYMENT OVER SUBFLOOR COMPLIES WITH REQUIREMENTS SPECIFIED IN SECTION 061600 "SHEATHING."
3.2 PREPARE, INSTALL, CLEAN & PROTECT CARPET . FOLLOW MANUFACTURER'S WRITTEN INSTRUCTIONS.

- 099123 - INTERIOR PAINTING
1.1 SUMMARY
A. PRIMERS
B. WATER-BASED FINISH COATINGS
C. SUBMITTALS:
A. PRODUCT DATA
B. SAMPLES
C. MAINTENANCE MATERIAL SUBMITTALS: FURNISH 1 GAL OF EACH PAINT PRODUCT OF EACH MATERIAL AND COLOR APPLIED THAT ARE PACKAGED WITH PROTECTIVE COVERING FOR STORAGE AND IDENTIFIED WITH LABELS DESCRIBING CONTENTS.
1.2 FIELD CONDITIONS: APPLY PAINTS ONLY WHEN TEMPERATURE OF SURFACES TO BE PAINTED AND AMBIENT AIR TEMPERATURES ARE BETWEEN 50 AND 95 DEG F. DO NOT APPLY PAINTS WHEN RELATIVE HUMIDITY EXCEEDS 85 PERCENT; AT TEMPERATURES OF LESS THAN 5 DEG F ABOVE THE DEW POINT, OR TO DAMP OR WET SURFACES.
2.1 PRODUCTS:
A. PRIMER FOR DRYWALL: SHERWIN WILLIAMS PROMAR 200 ZERO VOC LATEX PRIMER
B. PRIMER FOR WOOD: SHERWIN WILLIAMS PREMIUM WALL & WOOD PRIMER
C. WATER-BASED FINISH COATING: INTERIOR, LATEX; PIGMENTED, WATER-BASED PAINT FOR USE ON PRIMED/SEALED INTERIOR GYPSUM BOARD, AND ON PRIMED WOOD: BASIS-OF-DESIGN: SHERWIN-WILLIAMS PROMAR 200 ZERO VOC. SEE INTERIOR FINISH SCHEDULE FOR COLORS AND SHEEN LEVELS.
3.1 EXECUTION
A. VERIFY GYPSUM BOARD AND WOOD SUBSTRATES ARE SANDED SMOOTH AND CLEANED.
B. APPLY PAINTS ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS.
C. CLEAN AND PROTECT WORK.
D. PROVIDE LEVEL 4 FINISH.

DRAWING SUBMISSION STATUS: ☒ NOT FOR CONSTRUCTION ☐ SCHEMATIC DESIGN ☐ DESIGN DEVELOPMENT ☒ CONSTRUCTION DOCUMENTS ☒ ISSUED FOR CONSTRUCTION		PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET , SINGLE FAMILY HOME		PROJECT NUMBER: 2317.006	
TREDO ENGINEERING STRUCTURAL 755 SENECA ST., #202 BUFFALO, NY 14210 (716) 876, 7147				BENIC DEVELOPMENT LLC 403 MAIN STREET, SUITE 602 BUFFALO, NEW YORK 14203	
ARCHITECT OF RECORD HHL Architects 172 Allen Street, Buffalo, New York 14201 716.885.0740 ■ F: 716.885.6414 HHLarchitects.com					
DRAWING TITLE OUTLINE SPECS		DESCRIPTION		ISSUE DATE:09.19.25	
SEAL 		REV/SIONS AFTER ISSUANCE NO. DATE		DRAWING NUMBER A-003	

DIVISION 10 - SPECIALTIES

102800 - TOILET, BATH, AND LAUNDRY ACCESSORIES
1.1 SUMMARY: PRIVATE-USE BATHROOM ACCESSORIES
1.2 SUBMITTALS: PRODUCT DATA
2.1 PRODUCTS: SEE BATHROOM ELEVATIONS & ACCESSORY SCHEDULE ON DRAWINGS
FOR BASIS-OF-DESIGN PRODUCTS
3.1 INSTALLATION: INSTALL ACCESSORIES IN ACCORDANCE WITH MANUFACTURERS' WRITTEN INSTRUCTIONS, USING ASTERS APPROPRIATE TO SUBSTRATE INDICATED AND RECOMMENDED BY UNIT MANUFACTURER. INSTALL UNITS LEVEL, PLUMB, AND FIRMLY ANCHORED IN LOCATIONS AND AT HEIGHTS INDICATED.

105500.13 - USPS-DELIVERY POSTAL SPECIALTIES
1.1 SUMMARY: TRADITIONAL WALL MOUNTED MAILBOXES
A. SUBMITTALS: PRODUCT DATA
2.1 TRADITIONAL WALL MOUNTED MAILBOXES
A. 10-1/2" W X 14-1/2" H X 3-1/2" D
B. DETACHABLE MAGAZINE HOOKS
C. ELECTRO-GALVANIZED 20 GAUGE STEEL W/ POWER COATED FINISH TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.

DIVISION 11 - EQUIPMENT

113013 - RESIDENTIAL APPLIANCES
1.1 SUMMARY:
A. COOKING APPLIANCES
B. REFRIGERATION APPLIANCES
C. CLEANING APPLIANCES
1.2 SUBMITTALS: PRODUCT DATA
2.1 PRODUCTS: SEE APPLIANCE SCHEDULE ON DRAWINGS
2.2 PERFORMANCE REQUIREMENTS:
A. ELECTRICAL APPLIANCES: LISTED AND LABELED AS DEFINED IN NFPA 70, BY A QUALIFIED TESTING AGENCY, AND MARKED FOR INTENDED LOCATION AND APPLICATION.
2.3 COOKING APPLIANCES
A. ELECTRIC RANGE, 30" WIDTH
B. MICROWAVE OVEN, 30" WIDTH, UNDER CABINET MOUNT W/ EXHAUST FAN
2.4 REFRIGERATION APPLIANCES: REFRIGERATOR/FREEZER, TWO-DOOR SIDE-BY-SIDE REFRIGERATOR/FREEZER, FREESTANDING
2.5 CLEANING APPLIANCES
A. DISHWASHER, BUILT-IN UNDERCOUNTER, 24" WIDTH
B. CLOTHES WASHER, FRONT LOADING
C. CLOTHES DRYER, FRONT LOADING
1. STACKABLE WASHER/DRYER - INSTALL WHERE INDICATED TO BE STACKABLE
3.1 INSTALLATION: INSTALL APPLIANCES ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS.

DIVISION 12 - FURNISHINGS

122413 - ROLLER WINDOW SHADES
1.1 SUMMARY: MANUALLY OPERATED, SINGLE-ROLLER SHADES
1.2 SUBMITTALS:
A. PRODUCT DATA
B. SAMPLES
1.3 FIELD CONDITIONS: DO NOT INSTALL ROLLER SHADES UNTIL CONSTRUCTION AND FINISH WORK IN SPACES, INCLUDING PAINTING, IS COMPLETE AND DRY AND AMBIENT TEMPERATURE AND HUMIDITY CONDITIONS ARE MAINTAINED AT THE LEVELS INDICATED FOR PROJECT WHEN OCCUPIED FOR ITS INTENDED USE.
1.4 FIELD MEASURE
2.1 BASIS-OF-DESIGN MANUFACTURER: LEVOLOR, OR APPROVED EQUAL.
A. CHAIN-AND-CLUTCH OPERATING MECHANISM: WITH CONTINUOUS-LOP BEAD CHAIN AND CLUTCH THAT STOPS SHADE MOVEMENT WHEN BEAD CHAIN IS RELEASED; PERMANENTLY ADJUSTED AND LUBRICATED.
B. SHADE MATERIAL: LEVOLOR SOLAR SCREEN 3, (3% OPENNESS); WHITE
2.2 FABRICATION: FABRICATE UNITS IN SIZES TO FILL WINDOW OPENINGS
A. BETWEEN (INSIDE) JAMB INSTALLATION: WIDTH EQUAL TO JAMB-TO-JAMB DIMENSION OF OPENING IN WHICH SHAD IS INSTALLED LESS 1/4 INCH PER SIDE OR 1/2 INCH TOTAL, PLUS OR MINIMUM 1/8 INCH.
3.1 INSTALL ROLLER SHADES LEVEL, PLUMB, AND ALIGNED WITH ADJACENT UNITS ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS.
A. ROLLER SHADE LOCATIONS: AT DOUBLE HUNG WINDOWS AS INDICATED ON DRAWINGS.
3.2 CLEAN & PROTECT THE WORK

123530 - RESIDENTIAL CASEWORK
1.1 SUMMARY: KITCHEN AND VANITY CABINETS.
1.2 SUBMITTALS:
A. PRODUCT DATA
B. SHOP DRAWINGS
C. FINISH SAMPLES
1.3 FIELD CONDITIONS:
A. ENVIRONMENTAL LIMITATIONS: DO NOT DELIVER OR INSTALL CASEWORK UNTIL BUILDING IS ENCLOSED, WET-WORK IS COMPLETE, AND HVAC SYSTEM IS OPERATING AND MAINTAINING TEMPERATURE AND RELATIVE HUMIDITY LEVELS PLANNED FOR BUILDING OCCUPANTS DURING THE REMAINDER OF THE CONSTRUCTION PERIOD.

B. ESTABLISHED DIMENSIONS: WHERE CASEWORK IS INDICATED TO FIT TO OTHER CONSTRUCTION, ESTABLISH DIMENSIONS FOR AREAS WHERE CASEWORK IS TO FIT. COORDINATE CONSTRUCTION TO ENSURE THAT ACTUAL DIMENSIONS CORRESPOND TO ESTABLISHED DIMENSIONS. PROVIDE FILLERS AND SCRIBES TO ALLOW FOR TRIMMING AND FITTING.
2.1 CABINETS: QUALITY STANDARDS: PROVIDE CABINETS THAT COMPLY WITH KCMA A161.1.
1. A. CABINET STYLE: FACE FRAME, "SHAKER STYLE" DOORS
1. VANITY CABINETS: INCORPORATED FINISHED CABINET FEET INTO FRAME (WITH TOE KICKS LEFT OPEN)
B. EXPOSED WOOD SPECIES: MANUFACTURER'S STANDARD DOMESTIC HARDWOOD SPECIES.
C. FACTORY FINISH CABINETS: WHITE
2.2 HARDWARE: MANUFACTURER'S STANDARD UNITS COMPLYING WITH BHMA A156.9, OF TYPE, SIZE, STYLE, MATERIAL, AND FINISH AS SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.
3.1 INSTALLATION:
A. INSTALL CASEWORK WITH NO VARIATIONS IN ADJOINING SURFACES; USE CONCEALED SHIMS.
B. INSTALL CASEWORK WITHOUT DISTORTION SO DOORS AND DRAWERS FIT THE OPENINGS, ARE ALIGNED, AND ARE UNIFORMLY SPACED. COMPLETE INSTALLATION OF HARDWARE AND ACCESSORIES.
C. INSTALL CASEWORK LEVEL AND PLUMB TO A TOLERANCE OF 1/8 INCH IN 8 FEET.
D. FASTEN CASEWORK TO ADJACENT UNITS AND TO BACKING. FASTEN WALL CABINETS THROUGH BACK, NEAR TOP AND BOTTOM, AND AT ENDS NOT MORE THAN 16 INCHES O.C.
E. CLEAN CASEWORK, TOUCH UP AS REQUIRED TO RESTORE DAMAGED OR SOILED AREAS TO MATCH ORIGINAL FACTORY FINISH.

123623.13 - PLASTIC-LAMINATE-CLAD COUNTERTOPS
1.1 SUMMARY: PLASTIC-LAMINATE-CLAD COUNTERTOPS
1.2 SUBMITTALS:
A. PRODUCT DATA
B. SHOP DRAWINGS
C. SAMPLES
1.3 DELIVER COUNTERTOPS ONLY AFTER CASEWORK AND SUPPORTS ON WHICH THEY WILL BE INSTALLED HAVE BEEN COMPLETED IN INSTALLATION AREAS.
1.4 FIELD MEASUREMENTS: WHERE COUNTERTOPS ARE INDICATED TO FIT TO OTHER CONSTRUCTION, VERIFY DIMENSIONS OF OTHER CONSTRUCTION BY FIELD MEASUREMENTS BEFORE FABRICATION AND INDICATE MEASUREMENTS ON SHOP DRAWINGS. COORDINATE FABRICATION SCHEDULE WITH CONSTRUCTION PROGRESS TO AVOID DELAYING THE WORK.
2.1 QUALITY STANDARD: UNLESS OTHERWISE INDICATED, COMPLY WITH THE "ARCHITECTURAL WOODWORK STANDARDS" FOR GRADES OF PLASTIC-LAMINATE COUNTERTOPS INDICATED FOR CONSTRUCTION, FINISHES, INSTALLATION, AND OTHER REQUIREMENTS.
A. GRADE: CUSTOM
B HIGH-PRESSURE DECORATIVE LAMINATE: ISO 4586-3, GRADE HGS
C. BASIS-OF-DESIGN: WILSONART PREMIUM LAMINATE
D. AS INDICATED ON DRAWINGS
E. CORE MATERIAL: AS SELECTED BY FABRICATOR TO COMPLY WITH QUALITY STANDARD
F. CORE MATERIAL AT SINKS: MDF MADE WITH EXTERIOR GLUE OR EXTERIOR-GRADE PLYWOOD
2.2 ADHESIVE FOR BONDING PLASTIC LAMINATE: TYPE I, WATERPROOF TYPE AS SELECTED BY FABRICATOR TO COMPLY WITH REQUIREMENTS.
3.1 INSTALLATION:
A. SCRIBE AND CUT COUNTERTOPS TO FIT ADJOINING WORK, REFINISH CUT SURFACES, AND REPAIR DAMAGED FINISH AT CUTS.
B. ANCHOR SECURELY BY SCREWING THROUGH CORNER BLOCKS OF BASE CABINETS OR OTHER SUPPORTS INTO UNDERSIDE OF COUNTERTOP. INSTALL COUNTERTOPS LEVEL AND TRUE IN LINE. USE CONCEALED SHIMS AS REQUIRED TO MAINTAIN NOT MORE THAN 1/8-INCH-IN-96-INCHES VARIATION FROM A STRAIGHT, LEVEL PLANE.
C. SEAL JOINTS WHERE COUNTERTOP ABUT WALLS WITH MILDEW-RESISTANT SILICONE SEALANT OR OTHER PERMANENTLY ELASTIC SEALING COMPOUND RECOMMENDED BY COUNTERTOP MATERIAL MANUFACTURER.
3.2 CLEAN & PROTECT THE WORK.

DIVISION 22 - PLUMBING (RE PLUMB DWGS)

DIVISION 23 - HEATING, VENTILATING, AND AIR CONDITIONING (RE MECH DWGS)

DIVISION 26 - ELECTRICAL (RE ELEC DWGS)


DIVISION 31 - EARTHWORK (RE CIVIL & STRUCT DWGS)

DIVISION 32 - EXTERIOR IMPROVEMENTS (RE CIVIL DWGS)

DIVISION 33 - UTILITIES (RE CIVIL DWGS)

DRAWING SUBMISSION STATUS: ☐ NOT FOR CONSTRUCTION ☐ SCHEMATIC DESIGN ☐ DESIGN DEVELOPMENT ☒ CONSTRUCTION DOCUMENTS ☒ ISSUED FOR CONSTRUCTION	DRAWING TITLE OUTLINE SPECS	PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET , SINGLE FAMILY HOME
	REVISIONS AFTER ISSUANCE NO. DATE	TREDO ENGINEERING STRUCTURAL 755 SENECA ST., #202 BUFFALO, NY 14210 (716) 876, 7147 MEP BUFFALO ENG., PC 4245 UNION RD, BUFFALO, NY 14225 (716) 633, 5598
SEAL 		PROJECT NUMBER: 2317.006
ISSUE DATE: 09.19.25		
DRAWING NUMBER A-004		

ALTERNATE #3: VINYL PATIO SLIDER AT REAR DOOR 105 LOCATION (B.O.D. PELLA 250 SERIES)




CONSTRUCTION NOTE:
ALL INTERIOR WALLS ARE 2X4 WD. FRAME CONSTRUCTION, 3/A-410, UNLESS NOTED OTHERWISE ON PLAN

ALTERNATES:


ALTERNATE #1: PROPERTY FENCE WITH TWO (2) GATES (6'-0" (H))

ALTERNATE #2: THREE (3) ADDITIONAL TYPE F BEDROOM WINDOWS, (WINDOWS 204, 206 & 207); SEE PLAN

ALTERNATE #3: VINYL PATIO SLIDER AT REAR DOOR 105 LOCATION (B.O.D. PELLA 250 SERIES)



2 ROOF PLAN
1/4" = 1'-0"



1 ATTIC FLOOR PLAN
1/4" = 1'-0"

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE
ATTIC & ROOF PLANS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

SEAL



ISSUE DATE: 09.19.25

DRAWING NUMBER

A-102

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0748 ■ F: 716.885.6414
HHLArchitects.com

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876, 7147

MEP
4245 UNION RD,
BUFFALO, NY 14225
(716) 633, 5598

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET, SINGLE
FAMILY HOME

BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

PROJECT NUMBER: 2317.006


CONSTRUCTION NOTE:
ALL INTERIOR WALLS ARE 2X4 WD. FRAME CONSTRUCTION, 3/A-410, UNLESS NOTED OTHERWISE ON PLAN

ALTERNATES:


ALTERNATE #1: PROPERTY FENCE WITH TWO (2) GATES (6'-0" (H))

ALTERNATE #2: THREE (3) ADDITIONAL TYPE F BEDROOM WINDOWS, (WINDOWS 204, 206 & 207); SEE PLAN


ALTERNATE #3: VINYL PATIO SLIDER AT REAR DOOR 105 LOCATION (B.O.D. PELLA 250 SERIES)



3 ATTIC REFLECTED CEILING PLAN
1/4" = 1'-0"



2 SECOND FLOOR REFLECTED CEILING PLAN
1/4" = 1'-0"



1 FIRST FLOOR REFLECTED CEILING PLAN
1/4" = 1'-0"

LIGHT FIXTURE KEY

- LF2 KITCHEN ISLAND PENDANT
- LF3 15 IN. DIAM CEILING SURFACE MOUNT- STAIR HALL & BEDROOMS
- LF4 21 IN. DIAM. CEILING SURFACE MOUNT- DINING AND LIVING ROOM
- LF5 RECESSED LED CEILING FIXTURE
- LF5 WET RECESSED LIGHT FIXTURE- WET AREA UL RATED
- LF6 WALL SCONCE
- LF8 UTILITY PENDANT LIGHT FIXTURE - 1' X 4'
- LF10 EXTERIOR WALL SCONCE W/ MOTION SENSOR
- LF11 EXTERIOR PORCH SURFACE MTD CEILING LIGHT W/ MOTION SENSOR
- SS JAMB SWITCH: B.O.D. LEVITON 1865 BRASS DOOR JAM SWITCH 3 AM 125 VOLT
- CO SMOKE DETECTOR
- CFL CARBON MONOXIDE DETECTOR
- CFL CEILING MOUNT VENTILATION FAN AND LIGHT

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE
REFLECTED CEILING PLANS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION



ISSUE DATE: 09.19.25

DRAWING NUMBER

A-201



TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876, 7147
MEP
4245 UNION RD,
BUFFALO, NY 14225
(716) 633, 5598

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET , SINGLE
FAMILY HOME
BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

PROJECT NUMBER: **2317.006**

GENERAL NOTE:


1. INSTALL WINDOW OPENING CONTROL DEVICE (WOCD) WITH OVERRIDE FOR EMERGENCY ESCAPE & RESCUE AT ALL WINDOWS MEETING THE CRITERIA OF 2020 NYS RESIDENTIAL BUILDING CODE: R3.12: SECTION 1 AND 2:
1A. INSTALL WOCD AT WINDOWS WHERE:
THE SILL IS LOWER THAN 24" ABOVE FINISHED FLOOR AND MORE THAN 72" ABOVE FINISHED GRADE.
1B. WOCD: A 4" SPHERE CANNOT PASS THROUGH THE LARGEST OPENING ALLOWED.

ALTERNATES:


ALTERNATE #1: PROPERTY FENCE WITH TWO (2) GATES (6'-0" (H))

ALTERNATE #2: THREE (3) ADDITIONAL TYPE F BEDROOM WINDOWS, (WINDOWS 203, 304 & 205); SEE PLAN

ALTERNATE #3: VINYL PATIO SLIDER AT REAR DOOR 105 LOCATION (B.O.D. PELLA 250 SERIES)



2 EAST ELEVATION
1/4" = 1'-0"



1 SOUTH ELEVATION
1/4" = 1'-0"

DRAWING SUBMISSION STATUS: NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE
EXTERIOR ELEVATIONS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

ARCHITECT OF RECORD
HHL Architects

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876, 7147


PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET, SINGLE
FAMILY HOME

BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203
PROJECT NUMBER: 2317.006

ISSUE DATE: 09.19.25

DRAWING NUMBER

A-300



GENERAL NOTE:




1. INSTALL WINDOW OPENING CONTROL DEVICE (WOCD) WITH OVERRIDE FOR EMERGENCY ESCAPE & RESCUE AT ALL WINDOWS MEETING THE CRITERIA OF 2020 NYS RESIDENTIAL BUILDING CODE: R3.12: SECTION 1 AND 2:
1A. INSTALL WOCD AT WINDOWS WHERE:
THE SILL IS LOWER THAN 24" ABOVE FINISHED FLOOR AND MORE THAN 72" ABOVE FINISHED GRADE.
1B. WOCD: A 4" SPHERE CANNOT PASS THROUGH THE LARGEST OPENING ALLOWED.

ALTERNATES:

ALTERNATE #1: PROPERTY FENCE WITH TWO (2) GATES (6'-0" (H))

ALTERNATE #2: THREE (3) ADDITIONAL TYPE F BEDROOM WINDOWS, (WINDOWS 203, 304 & 205); SEE PLAN

ALTERNATE #3: VINYL PATIO SLIDER AT REAR DOOR 105 LOCATION (B.O.D. PELLA 250 SERIES)



DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE
EXTERIOR ELEVATIONS

SEAL



ISSUE DATE: 09.19.25

DRAWING NUMBER

A-301

ARCHITECT OF RECORD



716.885.0742 ■ F: 716.885.6414
HHLArchitects.com

TREDO ENGINEERING

STRUCTURAL

755 SENECA ST., #202

BUFFALO, NY 14210

(716) 876.7147

MEP

BUFFALO ENG., PC

4245 UNION RD,

BUFFALO, NY 14225

(716) 633.5598

PROJECT NAME/LOCATION:

DESCRIPTION [NEW CONSTRUCTION]

68 PULASKI STREET, SINGLE


FAMILY HOME

BENLIC DEVELOPMENT LLC


403 MAIN STREET, SUITE 602

BUFFALO, NEW YORK 14203

PROJECT NUMBER: 2317.006




2 Section 1
1/4" = 1'-0"




1 Section 2
1/4" = 1'-0"

DRAWING SUBMISSION STATUS: NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION	PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET , SINGLE FAMILY HOME	PROJECT NUMBER: 2317.006
	TREDO ENGINEERING STRUCTURAL 755 SENECA ST., #202 BUFFALO, NY 14210 (716) 876, 7147 MEP 4245 UNION RD, BUFFALO, NY 14225 (716) 633, 5598	HHL Architects 172 Allen Street, Buffalo, New York 14201 716.885.0748 • F: 716.885.6414 HHLarchitects.com
BUILDING SECTIONS		
DRAWING TITLE	REVISIONS AFTER ISSUANCE	DESCRIPTION
NO. DATE		
SEAL		
REGISTERED ARCHITECT ANTHONY J. LEE 021561-1 STATE OF NEW YORK		
ISSUE DATE:09.19.25		
DRAWING NUMBER		
A-401		



2 Section 3
1/4" = 1'-0"



1 Section 4
1/4" = 1'-0"

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION


DRAWING TITLE

BUILDING SECTIONS

REVISIONS AFTER ISSUANCE

NO. DATE

SEAL



ISSUE DATE: 09.19.25

DRAWING NUMBER

A-402

TREDO ENGINEERING

STRUCTURAL

755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876, 7147

MEP

4245 UNION RD,
BUFFALO, NY 14225
(716) 633, 5598



PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]


68 PULASKI STREET, SINGLE

FAMILY HOME

BENLIC DEVELOPMENT LLC

403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

PROJECT NUMBER: 2317.006



DRAWING SUBMISSION STATUS: ☒ NOT FOR CONSTRUCTION ☐ SCHEMATIC DESIGN ☐ DESIGN DEVELOPMENT ☒ CONSTRUCTION DOCUMENTS ☒ ISSUED FOR CONSTRUCTION
☐ IS ☒ DRAWING TITLE ARCHITECT OF RECORD TREDO ENGINEERING

SEAL

REGISTERED ARCHITECT
MATTHEW M. MEIER
021581-1
STATE OF NEW YORK

DRAWING NUMBER


A-410

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]


DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET , SINGLE

FAMILY HOME


BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203




8 1/2 BATHROOM NORTH ELEVATION
1/2" = 1'-0"




7 1/2 BATHROOM EAST ELEVATION
1/2" = 1'-0"




6 1/2 BATHROOM SOUTH ELEVATION
1/2" = 1'-0"




5 1/2 BATHROOM WEST ELEVATION
1/2" = 1'-0"




4 FULL BATHROOM NORTH ELEVATION
1/2" = 1'-0"



3 FULL BATHROOM EAST ELEVATION
1/2" = 1'-0"



2 FULL BATHROOM SOUTH ELEVATION
1/2" = 1'-0"



1 FULL BATHROOM WEST ELEVATION
1/2" = 1'-0"

GENERAL NOTE:
1. FOR BATH MILLWORK DETAILS SEE A-900
2. FOR DOOR CASING & BASE DETAILS SEE A-901.
3. FOR TOILET ACCESSORIES SEE A-901

DRAWING SUBMISSION STATUS: NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION
TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876, 7147
MEP
4245 UNION RD,
BUFFALO, NY 14225
(716) 633, 5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0748 ■ F: 716.885.6414
HHLarchitects.com

INTERIOR ELEVATIONS
REVISIONS AFTER ISSUANCE
NO. DATE
DESCRIPTION



ISSUE DATE: 09.19.25
DRAWING NUMBER
A-601

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET, SINGLE
FAMILY HOME
BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203
PROJECT NUMBER: **2317.006**



A-710


BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

- GENERAL NOTES:
- PREHUNG INTERIOR DOORS (1-3/8" TH) HINGES TO MATCH FINISH OF DOOR HARDWARE
 - USE DOOR STOP HINGE PIN FROM HARDWARE SET #1 AT ALL DOORS.


HOUSE TYPE 4: DOOR HARDWARE SETS: BASIS OF DESIGN							
DOOR HARDWARE #	DOOR TYPE	COMPONENTS	MANUF / SERIES	FIN	MODEL #	DIM	COMMENTS
1	EXTERIOR - FRONT & BACK	DOOR HANDLE SET; DEAD BOLT, EXTERIOR HANDLE SET, INTERIOR PASSAGE DOOR/LEVER	SCHLAGE / CENTURY	SATIN NICKEL	F60 G CEN 619 LAT	17.19 IN H X 2.5 IN W X 2.25 IN D	DR. TH. 1-3/8" - 1-7/8" ; UNIVERSAL HANDING; LIFETIME FINISH & MECHANICAL WARRANTY
		SECURITY GUARD	DEFIANT	SATIN NICKEL	70612	4.151 IN H X 2.48 IN W X 0.833 IN D	
		DOOR SEAL	M-D BULD. PRODUCTS	BROWN	70612	36 IN L X 2 IN W X 1-3/4 H	VINYL U SHAPED SLIDE ON UNDER DOOR SEAL
		DOOR STOP: HINGE PIN	DK HARDWARE	SAT. CHROME	01273		REPLACES HINGE PIN
2	CLOSET- DOUBLE DOORS	PASSAGE SET	SCHLAGE / LATITUDE	SATIN NICKEL	F10 V LAT 619	2.75 IN H X 5.39 IN W X 2.25 IN D	DR. TH. 1-3/8" - 1-3/4" ; UNIVERSAL HANDING; LIFETIME FINISH & MECHANICAL WARRANTY
			SCHLAGE / LATITUDE	SATIN NICKEL	F170 V LAT 619	2.75 IN H X 5.39 IN W X 2.25 IN D	DUMMY HANDLE, DR. TH. 1-3/8" - 1-3/4" ; UNIVERSAL HANDING; LIFETIME FINISH & MECHANICAL WARRANTY
3	BATHROOM / BEDROOM	PRIVACY SET	SCHLAGE / LATITUDE	SATIN NICKEL	F40 V LAT 619	2.75 IN H X 5 IN W X 2.375 IN D	DR. TH. 1-3/8" - 1-3/4" ; UNIVERSAL HANDING; LIFETIME FINISH & MECHANICAL WARRANTY
4	CLOSET/ MECH. RM / STORAGE/LAUNDRY	PASSAGE SET	SCHLAGE / LATITUDE	SATIN NICKEL	F10 V LAT 619	2.75 IN H X 5.39 IN W X 2.25 IN D	DR. TH. 1-3/8" - 1-3/4" ; UNIVERSAL HANDING; LIFETIME FINISH & MECHANICAL WARRANTY

POSITION DR. 104 R.O. , MECH. RM. TO CLEAR UNDERSIDE OF STAIR STRINGER


DOOR SCHEDULE																		
OPENING NUMBER	TYPE	DOOR					MATL	FINISH	GLASS	FRAME					GLASS	FIRE RATING (MIN.)	HDW SET	REMARKS
		SIZE				DETAILS												
		OPENIN G WIDTH	LEAF WIDTH	OPENING HEIGHT	THK	HEAD				JAMB	SILL							
FIRST FLOOR																		
101	B	3'- 0"		6'- 8"	1 3/8"	FIBERGLASS	PNT-1	--	1	WD	PNT-1				--		1	
102	C	5'- 0"		6'- 8"	1 3/4"	WD	PNT-1	--	2	WD	PNT-1				--		2	
103	A	3'- 0"		6'- 8"	1 3/8"	WD	PNT-1	--	1	WD	PNT-1				--		3	
104	A	2'- 10"		6'- 8"	1 3/8"	WD	PNT-1	--	1	WD	--				--		4	
105	B	3'- 0"		6'- 8"	1 3/8"	FIBERGLASS	--	--	1	WD	PNT-1				--		1	
201H	OX	6'- 2 1/2"		6'- 8"	6 3/8"													
SECOND FLOOR																		
201	A	2'- 10"		6'- 8"	1 3/8"													
201A	D	2'- 10"		6'- 8"	1 3/8"	WD	--	--	1	WD	--				--	4	LOUVER DOOR	
202	A	2'- 10"		6'- 8"	1 3/8"													
202A	A	2'- 10"		6'- 8"	1 3/8"													
203	A	2'- 10"		6'- 8"	1 3/8"	WD	PNT-1	--	1	WD	PNT-1				--		3	
204	A	2'- 10"		6'- 8"	1 3/8"	WD	PNT-1	--	1	WD	PNT-1				--		3	
204A	A	2'- 6"		6'- 8"	1 3/8"	WD	PNT-1	--	1	WD	PNT-1				--		4	
205	A	2'- 10"		6'- 8"	1 3/8"													
205A	A	2'- 10"		6'- 8"	1 3/8"													
Grand total: 15																		




FRAME TYPES



DOOR TYPES



2 EXTERIOR DOOR HEAD DETAIL
1 1/2" = 1'-0"



1 EXTERIOR DOOR JAMB AND SILL DETAIL
1 1/2" = 1'-0"

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876, 7147

MEP
4245 UNION RD,
BUFFALO, NY 14225
(716) 633, 5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0748 ■ F: 716.885.6414
HHLArchitects.com

DRAWING TITLE
DOOR SCHEDULE AND DETAILS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

SEAL



ISSUE DATE: 09.19.25

DRAWING NUMBER

A-800



PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]

68 PULASKI STREET , SINGLE


FAMILY HOME

BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 402
BUFFALO, NEW YORK 14203


PROJECT NUMBER: **2317.006**



2 JAMB DETAIL - TYPICAL
3" = 1'-0"



1 SILL DETAIL - TYPICAL
3" = 1'-0"



4 HEAD DETAIL - TYPICAL
3" = 1'-0"

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE

WINDOW SCHEDULE AND DETAILS

REVISIONS AFTER ISSUANCE

NO. DATE

DESCRIPTION

ARCHITECT OF RECORD

TREDO ENGINEERING

STRUCTURAL

755 SENECA ST., #202

BUFFALO, NY 14210

(716) 876, 7147

MEP

4245 UNION RD,

BUFFALO, NY 14225

(716) 633, 5598

PROJECT NAME/LOCATION:

DESCRIPTION [NEW CONSTRUCTION]

68 PULASKI STREET, SINGLE

FAMILY HOME

BENLIC DEVELOPMENT LLC

403 MAIN STREET, SUITE 602

BUFFALO, NEW YORK 14203

PROJECT NUMBER: 2317.006

ISSUE DATE: 09.19.25

DRAWING NUMBER

A-801


REGISTERED ARCHITECT

ANTHONY J. LEE



021591-1

STATE OF NEW YORK

2 KITCHEN CABINET DETAIL
1 1/2" = 1'-0"



1 KITCHEN ISLAND MILLWORK DETAIL
1 1/2" = 1'-0"



ISSUE DATE: 09.19.25

DRAWING NUMBER

A-900

DRAWING TITLE
MILLWORK DETAILS

REVISIONS AFTER ISSUANCE
NO. DATE

DESCRIPTION

ARCHITECT OF RECORD

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0742 • F: 716.885.6414
HHLarchitects.com

TREDO ENGINEERING
STRUCTURAL

755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876, 7147

MEP

BUFFALO ENG., PC
4245 UNION RD,
BUFFALO, NY 14225
(716) 633, 5598

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]

68 PULASKI STREET, SINGLE

FAMILY HOME

BENLIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

PROJECT NUMBER: **2317.006**

ALTERNATES:

ALTERNATE #1: PROPERTY FENCE WITH TWO (2) GATES (6'-0" (H))

ALTERNATE #2: THREE (3) ADDITIONAL TYPE F BEDROOM WINDOWS, (WINDOWS 203, 304 & 205); SEE PLAN

ALTERNATE #3: VINYL PATIO SLIDER AT REAR DOOR 105 LOCATION (B.O.D. PELLA 250 SERIES)

FINISHES:

LVT-1 FOR FIRST FLOOR ONLY: SHAW FLOORS ENDURA 512C PLUS 0720V, 7/8" X 5PC VINYL PLANK (FLOATING), 4.8 MM TH, 12 MIL WEAR LAYER, ARMOUR BEAD FINISH, MICRO BEVEL EDGE, COLOR: 5091 LIGHTHOUSE

LVT-2 FOR SECOND FL. BATH 203 ONLY: SHAW FLOORS ASPECT VINYL SHEET, FULLY ADHERED (COLOR: 05229 IRON WEAVE)

PNT-1 FOR TRIM ONLY: SHERWIN WILLIAMS-PROMAR 200 ZERO VOC INTERIOR ACRYLIC LATEX (COLOR: SW 7012 CREAMY, SHEEN: GLOSS)

PNT-2 FOR WALLS ONLY: SHERWIN WILLIAMS-PROMAR 200 ZERO VOC INTERIOR ACRYLIC LATEX (COLOR: SW 7005 PURE WHITE, SHEEN: EGG SHELL)

PNT-3 FOR CEILINGS ONLY: SHERWIN WILLIAMS-PROMAR 200 ZERO VOC INTERIOR ACRYLIC LATEX (COLOR: SW 7757 HIGH REFLECTIVE WHITE, SHEEN: EGG SHELL)

PNT-4 ACCENT WALL AT LIVING ROOM/KITCHEN NORTH ELEVATION (11A-600) ONLY: SHERWIN WILLIAMS - PROMAR 200 ZERO VOC INTERIOR ACRYLIC LATEX (COLOR: SW 9185 MAREA BAJA, SHEEN: EGG SHELL)

PNT-5 BEDROOM 2 RM 204 REAR FACADE WINDOW WALL, WEST ELEVATION ONLY: SHERWIN WILLIAMS - PROMAR 200 ZERO VOC INTERIOR ACRYLIC LATEX (COLOR: SW 7057 SILVER STRAND, SHEEN: EGG SHELL)

SHADE-1 AT FRONT WINDOWS (FIRST & SECOND FLOORS): ECOFABRIX SOLAR ROLLER SHADE 3% OPENNESS, POLYESTER PVC (COLOR: 253-18 WHITE/GREY)

PLAM-1 WILSONART PREMIUM LAMINATE, TEXTURED GLOSS #4925K-07 FINISH AEON SCRATCH RESISTANCE W/ SQUARE EDGE (COLOR: CALCUTTA MARBLE)

TILE-1 BEST TILE NEW YORK WHITE 4" X 12" GLOSSY CERAMIC WALL TILE 10400 ECWNEW307769

GROUT-LATICRETE PERMACOLOR GROUT (COLOR: SILVER SHADOW 88)

CPT-1 SHAW FLOORS CABANA BAY E-9955 W/ COLORGUARD BLEACH & FADE RESISTANT TECHNOLOGY & R2X STAIN TREATMENT, 100% PET POLYESTER, 10 YEAR WARRANTY (COLOR STAINLESS 542)


T-1 MSI: WHITE DOUBLE BEVELED 6.13" X 36.13 IN X 1.2 IN POL. ENGINEERED MARBLE THRESHOLD TILE TRIM MODEL #: THD2WH6X36DB

EXTERIOR


ALSIDE ODYSSEY PLUS PREMIUM VINYL SIDING (COLOR: CYPRESS)

TRIM:
ALSIDE: ALLIANCE T4: VINYL SOFFIT (COLOR: GLACIER WHITE)
ALSIDE: PERFORMANCE G8: ALUM. TRIM COIL (COLOR: GLACIER WHITE)
MOUNT BLOCKS FOR METERS & VENTS (COLOR: WHITE)
COLUMN WRAP & PORCH RAILINGS: VERSATEX (COLOR: WHITE)

PINNACLE PRISTINE HIGH PERFORMANCE ARCHITECTURAL SHINGLES WITH SCOTCHGUARD ASPHALT SHINGLES (COLOR: MAJESTIC SHAKE)



2 T1 TRANSITION LVT TO CPT
3" = 1'-0"



BASE TRIM & DOOR JAMB ELEVATION

DOOR HEAD SECTION

DOOR JAMB PLAN VIEW

FINISH SCHEDULE

RM #	ROOM	FLOOR		WALL		WINDOW		DOOR				CEILING	HARDWARE/ LIGHTING		COMMENTS
		FL. FINISH	BASE	BASE FIN.	WALL FIN.	TREATMENT	TRIM	TRIM FIN.	FINISH	TRIM	TRIM FIN.	CEILING FIN.	HARDWARE & LIGHTING FIN.		
101	LIVING ROOM	LVT-1	WB-1	PNT-1	PNT-2 & PNT-4	SHADE-1	WC-1	PNT-1	PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		
102	CLOSET	LVT-1	NONE		PNT-2	NONE			PNT-1	DC-1	PNT-1	PNT-3			
103	1/2 BATH	LVT-1	WB-1	PNT-1	PNT-2	NONE			PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		LAVATORY FAUCET POLISHED CHROME & ACCESSORIES (POL. CHROME); PLAM-1 C-TOP
104	KITCHEN	LVT-1	WB-1	PNT-1	PNT-2/ TILE-1	NONE	WC-1	PNT-1	PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		VIBRANT STAINLESS FOR KITCHEN FAUCET; PLAM-1 FOR C-TOP & TILE-1 FOR BACKSPLASH
105	MECH. RM.	LVT-1	NONE		PNT-2	NONE			PNT-1			PNT-3			
201	HALL	CPT-1	WB-1	PNT-1	PNT-2	NONE	WC-1	PNT-1	PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		
202	BEDRM 1	CPT-1	WB-1	PNT-1	PNT-2	SHADE-1	WC-1	PNT-1	PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		
202A	CLOSET	CPT-1	NONE		PNT-2	NONE			PNT-1			PNT-3	BRUSHED NICKEL POL. CHROME		
203	BATHROOM	LVT-2/T-1	WB-1	PNT-1	PNT-2	NONE	WC-1	PNT-1	PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		POL. CHROME FOR BATH/SHOWER FITTINGS; LAVATORY FAUCET POL. CHROME & ACCESSORIES (POL. CHROME); PLAM-1 C-TOP
204	BEDRM 2	CPT-1	WB-1	PNT-1	PNT-2	SHADE-1	WC-1	PNT-1	PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		
204A	CLOSET	CPT-1	NONE		PNT-2	NONE			PNT-1			PNT-3	BRUSHED NICKEL POL. CHROME		
205	BEDRM 3	CPT-1	WB-1	PNT-1	PNT-2	SHADE-1	WC-1	PNT-1	PNT-1	DC-1	PNT-1	PNT-3	BRUSHED NICKEL POL. CHROME		
205A	CLOSET	CPT-1	NONE		PNT-2	NONE			PNT-1			PNT-3	BRUSHED NICKEL POL. CHROME		
206	STORAGE	CPT-1	NONE		PNT-2	NONE			PNT-1			PNT-3			
207	LAUNDRY	LVT-2/T-1	WB-1	PNT-1	PNT-2	NONE			PNT-1	DC-1	PNT-1	PNT-3			

ACCESSORY SCHEDULE

RM #	ROOM	ACCESSORY	MANUF.	FINISH	QTY	DESCRIPTION
102	CLOSET	SHELF & ROD	CLOSETMAID SUPERSLIDE	WHITE	1	5 FT TO 8 FT VENTILATED WIRE CLOSET ORGANIZER W/ SHOE, DOUBLE HANGING, LONG HANGING AND FOLDED STORAGE UP TO 400LBS; MODEL # 5037; PROVIDE BLOCKING FOR ALL HANGING SYSTEMS.
103	1/2 BATH	HAND TOWEL BAR; TP DISPENSER; ROBE HOOK; TOWEL BAR	BWE	POL CHROME	1	4 PIECE SET: (1) ROBE HOOK, TOILET PAPER HOLDER, HAND TOWEL BAR AND TOWEL BAR; SUS304 ST. STL.; MODEL: A-91012-4-CP; PROVIDE BLOCKING
202A	CLOSET	SHELF & ROD	CLOSETMAID SUPERSLIDE	WHITE	1	5 FT TO 8 FT VENTILATED WIRE CLOSET ORGANIZER W/ SHOE, DOUBLE HANGING, LONG HANGING AND FOLDED STORAGE UP TO 400LBS; MODEL # 5037; PROVIDE BLOCKING FOR ALL HANGING SYSTEMS.
203	BATHRM	HAND TOWEL BAR; TP DISPENSER; (2) HOOKS; TOWEL BAR	BWE	POL. CHROME	1	5 PIECE SET: (2) ROBE HOOK, TOILET PAPER HOLDER, HAND TOWEL BAR AND TOWEL BAR; SUS304 ST. STL.; MODEL: A-91012-4-CP; PROVIDE BLOCKING
		24" TOWEL BAR	BWE	POL. CHROME	1	24.2 IN TOWEL BAR; MODEL # A-91089-CP
		SHOWER SHELF	GATCO	CHROME	2	8.4 IN (W) X 2.7 IN (H) X 5.9 IN (D); 5LB; MODEL #1452 PROVIDE BLOCKING
		SHOWER ROD	ZENNA HOME	CHROME	1	NEVER RUST 50 IN TO 72 IN; MODEL # 72S2ALSSL; PROVIDE BLOCKING
204A	CLOSET	SHELF & ROD	CLOSETMAID SUPERSLIDE	WHITE	1	5 FT TO 8 FT VENTILATED WIRE CLOSET ORGANIZER W/ SHOE, DOUBLE HANGING, LONG HANGING AND FOLDED STORAGE UP TO 400LBS; MODEL # 5037; PROVIDE BLOCKING FOR ALL HANGING SYSTEMS.
205A	CLOSET	SHELF & ROD	CLOSETMAID SUPERSLIDE	WHITE	1	5 FT TO 8 FT VENTILATED WIRE CLOSET ORGANIZER W/ SHOE, DOUBLE HANGING, LONG HANGING AND FOLDED STORAGE UP TO 400LBS; MODEL # 5037; PROVIDE BLOCKING FOR ALL HANGING SYSTEMS.
206	STORAGE	SHELF & ROD	CLOSETMAID SUPERSLIDE	WHITE	1	5 FT TO 8 FT VENTILATED WIRE CLOSET ORGANIZER W/ SHOE, DOUBLE HANGING, LONG HANGING AND FOLDED STORAGE UP TO 400LBS; MODEL # 5037; PROVIDE BLOCKING FOR ALL HANGING SYSTEMS.
205	LAUNDRY	SHELF & ROD	EZ SHELF	WHITE	1	EXPANDABLE LAUNDRY ROOM SHELVES; ONE SHELF W/ CLOSET ROD & ONE W/O ROD; 200 LBS PER SHELF; MODEL #E2S-K-WLR; PROVIDED BLOCKING FOR ALL HANGING SYSTEMS

APPLIANCE SCHEDULE

105	KITCHEN	30" RANGE OVEN; ADA COMPLIANT FRONT CONTROLS, 4.8 CU. FT.	WHIRLPOOL	WHITE	1	WFC315S0JW; 29-7/8" W X 47-7/8" H X 28" D; ELECTRIC RANGE & OVEN; KEEP WARM SETTING
105	KITCHEN	OVER THE RANGE MICROWAVE	WHIRLPOOL	WHITE	1	WMMS3130RW; 29-7/8" W X 15-9/16" H X 17-7/8" D; EXTERNAL VENTING
105	KITCHEN	REF/FR 18.3 CU. FT.; ENERGY STAR QUALIFIED	WHIRLPOOL	WHITE	1	WRT148FZDW; 29-1/2" W X 65-7/8" H X 33-1/2" D; LED LIGHTING, ADJ. SHELVES. TEMP. CONTROLS, ADA COMPLIANT
105	KITCHEN	DISHWASHER, TOP CONTROL W/ ST. STL. INTERIOR; ENERGY STAR	WHIRLPOOL	WHITE	1	WDT550SAPW; 23-9/16" W X 32-5/16" H X 25-3/8" D; ST. STL. TUB, ENERGY STAR QUALIFIED, ADA COMPLIANT, 44dBA
105	KITCHEN	GARBAGE DISPOSAL	SINK PRO	ST. STL.	1	SEE ADD ALTERNATE 2; SINK PRO X0D12PRO; 3 BOLT MOUNT SYSTEM CONTINUOUS FEED W/ ON/OFF SWITCH
205	LAUNDRY	UNITIZED STACKING W/D	WHIRLPOOL	WHITE	1	WET4027HW; 27-1/4" W X 75-1/2" H X 32-7/16" D; 3.5 CU. FT. WASHER, 5.9 CU. FT. DRYER; 4 DRYING CYCLES

1 TRIM BASE CASING AND PLINTH BLOCK
3" = 1'-0"

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION [] TREDO ENGINEERING [] ARCHITECT OF RECORD

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET , SINGLE
FAMILY HOME

PROJECT NUMBER:**2317.006**

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., # 202
BUFFALO, NY 14210
(716) 876 , 7147

MEP
BUFFALO ENG., PC
4245 UNION RD,
BUFFALO, NY 14225
(716) 633 , 5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0740 ■ F: 716.885.6414
HHLArchitects.com

SCHEDULES & DETAILS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

SEAL
REGISTERED ARCHITECT
ANTHONY A. LEBES
0215691-1
STATE OF NEW YORK

ISSUE DATE:09.19.25


DRAWING NUMBER
A-901

PLUMBING FIXTURE SCHEDULE							
MARK	FIXTURE	DRAINAGE		WATER		G	MAKE AND MODEL AND ACCESSORIES
		SAN	VENT	CW	HW		
WC-1	WATER CLOSET FLUSH TANK FLOOR MOUNT, ELONGATED WHITE VITREOUS CHINA	3"	2"	3/4"	-	-	GERBER MODEL GWS20918, "MAXWELL" WATER CLOSET, 1.28 GPF, ELONGATED BOWL, ADA COMPLIANT, WATERSENSE CERTIFIED, WITH TANK COVER AND TRIP LEVER. COORDINATE TRIP LEVER LOCATION WITH OPEN SIDE OF WATER CLOSET. CHURCH MODEL # 14001TC RESIDENTIAL TOILET SEAT, CLOSED FRONT, ELONGATED, WITH COVER. PROVIDE FLEXIBLE DOMESTIC WATER SUPPLY.
L-1	LAVATORY UNDERMOUNT WHITE VITREOUS CHINA MANUAL FAUCET	2"	2"	1/2"	1/2"	-	GERBER MODEL G0012834CH, DROP IN, ADA COMPLIANT, FRONT OVERFLOW, OVAL DESIGN. GERBER MODEL G0040024, SINGLE HANDLE FAUCET WITH METAL TOUCH DOWN DRAIN ASSEMBLY, 4" CENTERS, SINGLE LEVER HANDLE, 1.0 GPM AERATOR, WATERSENSE CERTIFIED. PROVIDE FLEXIBLE DOMESTIC WATER SUPPLY.
S-1	KITCHENETTE SINKS	2"	2"	1/2"	1/2"	-	ELKAY MODEL D12522, SINGLE BOWL DROP IN, 18 GAUGE 304 STAINLESS STEEL WITH CENTER DRAIN. GERBER MODEL 40-210-W, THREE HOLE WITH SIDE SPRAYER, 1.75 GPM, ADA COMPLIANT. PROVIDE FLEXIBLE DOMESTIC WATER SUPPLY. PROVIDE OFFSET TRAP FOR ADA LOCATIONS. PLUMBING ADD ALTERNATE TO PROVIDE PROVISIONS FOR GARBAGE DISPOSAL TO BE PROVIDED BY OTHERS.
BT-1	BATHTUB	2"	2"	1/2"	1/2"	-	STERLING MODEL 71370120, 60"x30" BATH/SHOWER, RIGHT DRAIN, 16" APRON. GERBER MODEL G000G9155TC, SINGLE HANDEL TUB AND SHOWER TRIM KIT, DIVERTER ON TUB SPOUT, WATER SENSE CERTIFIED, ADA COMPLIANT, G000G505 TUB AND SHOWER FAUCET ROUGH IN VALVE.
SH-1	SHOWER	2"	2"	1/2"	1/2"	-	OASIS MODEL SHFW-6235, 62"Wx36.25"Dx76.25"H, ONE PIECE FIBERGLASS COMPOSITE CONSTRUCTION, CENTER DRAIN. KOHLER MODEL K-TS45106-4G, RITE TEMP SHOWER KIT, 1.75 GPM, WATER SENSE CERTIFIED, ANTI-SCALD PROTECTION, PROVIDE WITH K-8304 VALVE AND CARTRIDGE KITS. PROVIDE ALL SHOWER ACCESSORIES INCLUDING GRAB BARS PER ARCHITECTURAL ELEVATIONS.
WH-1	NON-FREEZE WALL HYDRANT	-	-	3/4"	-	-	JAY R. SMITH MODEL # 5509QT BRONZE NICKEL PLATED QUARTER TURN SELF DRAINING NON-FREEZE HYDRANT WITH HOSE CONNECTION, INTEGRAL VACUUM BREAKER, "T" HANDLE KEY WITH SPARE, CHROME PLATED, NSF/ANSI STANDARD 61.
FD-1	FLOOR DRAIN	3"	2"	-	-	-	OATEY MODEL 72000 SERIES, ADJUSTABLE PVC DRAIN, 3", NO HUB, 5" DIAMETER ADJUSTABLE ROUND. PROSET SYSTEMS FLOOR DRAIN TRAP GUARD, VERIFY SIZE BASED ON MANUFACTURERS SPECIFICATIONS.
FD-2	FLOOR DRAIN	4"	2"	-	-	-	OATEY MODEL 72000 SERIES, ADJUSTABLE PVC DRAIN, 4", NO HUB, 5" DIAMETER ADJUSTABLE ROUND. PROSET SYSTEMS FLOOR DRAIN TRAP GUARD, VERIFY SIZE BASED ON MANUFACTURERS SPECIFICATIONS.
WMB-1	WASHING MACHINE BOX	-	-	3/4"	3/4"	-	SIOUX CHIEF MODEL # 696RG1W, NO LEAD VALVES, WITH ARRESTER, FIRE RATED OUTLET BOX. PROVIDE DRAIN PANS FOR WASHING MACHINES.
EWH-1	ELECTRIC WATER HEATER	-	-	-	-	-	'BRADFORD WHITE' MODEL 'R255T6' 5.5 KW, 240V, 55 GALLON CAPACITY, 75 GALLON FIRST HOUR RATING, 0.94 UEF, 25 GALLON RECOVERY AT 90 DEGREE RISE.
NOTE: REFER TO SPECIFICATIONS FOR LISTING OF ACCEPTABLE MANUFACTURERS AND FURTHER PRODUCT REQUIREMENTS. MANUFACTURERS LISTED ABOVE WERE USED FOR BASIS OF DESIGN. REFER TO DRAWINGS FOR ADDITIONAL REQUIRED ITEMS.							


PIPING INSULATION SCHEDULE		GENERAL NOTES:	
INSULATE THE FOLLOWING: A. HOT WATER PIPING B. COLD WATER PIPING C. LAVATORY TRAP AND WATER SUPPLIES (ON HANDICAPPED INSTALLATION). D. ROOF DRAINAGE (ROOF DRAIN & ALL HORIZONTAL STORM WATER). INSULATION PRODUCTS AND INSTALLATION SHALL COMPLY WITH ENERGY CONSERVATION CONSTRUCTION CODE OF NEW YORK STATE. HOT WATER PIPING INSULATION SHALL BE PREFORMED, SNAP-ON FIBERGLASS INSULATION WITH PAINTABLE WHITE KRAFT OR ALUMINUM FOIL JACKET. DOMESTIC COLD WATER AND ROOF DRAINAGE INSULATION SHALL BE SIMILAR TO HOT WATER WITH VAPOR BARRIER.		A. BACKFILLING REQUIREMENTS WITHIN BUILDING: (CONTRACTOR'S RESPONSIBILITY) SUPPORT BURIED PIPING THROUGHOUT ITS ENTIRE LENGTH. WHERE TRENCHES ARE EXCAVATED SUCH THAT THE BOTTOM OF THE TRENCH FORMS THE BED FOR THE PIPE, SOLID AND CONTINUOUS LOAD BEARING SUPPORT SHALL BE PROVIDED BETWEEN JOINTS. BACKFILL SHALL BE FREE FROM DISCARDED CONSTRUCTION MATERIAL AND DEBRIS. CHECK AND COMPLY WITH LOCAL AND FEDERAL BUILDING CODE REQUIREMENTS. B. THIS CONTRACTOR TO OBTAIN AND PAY FOR ALL NECESSARY PERMITS AND FEES REQUIRED TO PERFORM ALL WORK SHOWN WITH THE PROPER AUTHORITIES. C. REFER TO ARCHITECTURAL SITE PLANS AND LANDSCAPE DRAWINGS FOR AREAS OF GRADING, SIDEWALKS, DRIVES, ETC. D. ALL PIPING UNDER PAVED AREAS TO BE BACKFILLED WITH SELECT FILL. E. COORDINATE WITH OWNER PRIOR TO MAKING ANY SHUTDOWNS OF EXISTING SERVICES TO LIMIT DISTURBANCES TO BUILDING OPERATION. F. PROVIDE FINAL CONNECTION TO ALL FIXTURES AND EQUIPMENT INCLUDING ALL REQUIRED VALVES, TRAPS, SUPPLIES, REDUCERS, ETC. G. FIRESTOP ALL PENETRATIONS THROUGH RATED WALLS, FLOORS AND CEILING WITH APPROVED FIRESTOP SEALANT. PROVIDE INTUMESCENT SEAL FOR PLASTIC PIPING PENETRATING FIRE RATED ASSEMBLIES INCLUDING WALLS, FLOORS AND CEILINGS. H. ALL WORK IS TO BE IN ACCORDANCE WITH ENERGY STAR . NYSEDA'S MULTIFAMILY PERFORMANCE PROGRAM FOR NEW CONSTRUCTION HOUSING, THIRD PARTY STANDARD REQUIREMENTS VERSIONS 1.1. REFER TO AIR SEALING NOTES (G-002), SPECIFICATIONS CHECKLIST AS WELL AS TYPICAL GREEN BUILDING DETAILS (A-701-704). I. ALL WORK TO BE IN ACCORDANCE WITH ENTERPRISE GREEN COMMUNITIES 2020, MANDATORY AND PROJECT - SELECTED CRITERIA. REFER TO CHECKLIST IN SPECIFICATIONS. J. SUB CONTRACTORS / SPECIFIC TRADES ARE RESPONSIBLE TO REVIEW ALL SETS FOR COORDINATION TO ACHIEVE INTENT OF DOCUMENTS AS IT RELATES TO THE FINAL PRODUCT AND REQUIRED ENERGY CONSERVATION AND AIR SEALING COMPLIANCE. CONTRACTOR OR SUBCONTRACTOR(S) WILL NOT BE RELIEVED OF OBLIGATIONS FOR NOT COORDINATING WITH ALL DRAWINGS WITHIN THIS SET.	

PIPING MATERIAL SCHEDULE					SHOCK ABSORBER SCHEDULE		
SERVICE		PIPE MATERIALS	FITTINGS	CONNECTION	P.D.I. UNITS	FIXTURE UNITS	PIPE SIZE
WATER	ABOVE GROUND	TYPE "L" COPPER/PEX-A	WROUGHT COPPER/ PEX-A	NO-LEAD SOLDER/COMPRESSION JOINTS			
	BELOW GROUND	TYPE "K" COPPER	TYPE "K" COPPER	BRAZED OR COMPRESSED JOINTS			
SANITARY		SCHEDULE 40 PVC	NO HUB OR HUB AND SPIGOT	SOLVENT/WELD	A	1 – 11	1/2"
VENT		SCHEDULE 40 PVC	NO HUB OR HUB AND SPIGOT	SOLVENT/WELD	B	12 – 32	3/4"
STORM		SCHEDULE 40 PVC	NO HUB OR HUB AND SPIGOT	SOLVENT/WELD	C	33 – 60	1"
GAS	2" AND UNDER	SCHEDULE 40 BLACK STEEL	MALLEABLE IRON	THREADED	D	61 – 113	1–1/4"
	OVER 2"	SCHEDULE 40 BLACK STEEL	BUTT WELDED STEEL	WELDED	E	114 – 154	1–1/2"
					F	155 – 330	2"


LEGENDS AND ABBREVIATIONS					
---	CW	CW	COLD WATER	☒	REMOVE PIPING TO THIS POINT
---	HW	HW	HOT WATER	⊕	CONNECT NEW TO EXISTING
---	RHW	RHW	RECIRCULATING HOT WATER	+	WH WALL HYDRANT (EXTERIOR)
---	SAN	SAN	SANITARY SEWER (BELOW FLOOR)	☒	SA SHOCK ABSORBER (SIZE PER PDI)
---	SAN	SAN	SANITARY SEWER (ABOVE FLOOR)		VTR VENT THRU ROOF
---	V	V	VENT		PDI PLUMBING DRAINAGE INSTITUTE
---	ST	ST	PRIMARY STORM (BELOW FLOOR)		CFH CUBIC FEET PER HOUR
---	ST	ST	PRIMARY STORM (ABOVE FLOOR)	●	FCO FLOOR CLEANOUT
---	ST	SST	SECONDARY STORM (ABOVE FLOOR)	+	CO CLEANOUT
---	IW	IW	INDIRECT WASTE	☒	FD FLOOR DRAIN
---	G	G	GAS	+	CAP
---	G	G	GAS (BELOW FLOOR)	+	TFA TO FLOOR ABOVE
---			SHUT OFF VALVE	+	TFB TO FLOOR BELOW
---			CHECK VALVE	+	FFA FROM FLOOR ABOVE
---			GAS VALVE (AGA APPROVED)	+	FFB FROM FLOOR BELOW
---			SOLENOID VALVE	+	EX. EXISTING
---			UNION	+	TYP TYPICAL
---			STRAINER	+	CONT'D CONTINUED
---			BALANCING VALVE	+	WCO WALL CLEANOUT
---			WATER METER	+	COND CONDENSATE
NOTE: ALL LEGENDS AND ABBREVIATIONS MAY NOT BE USED ON DRAWINGS.					



1 FLOOR DRAIN DETAIL
NONE



3 ISLAND SINK DEATIL
NONE



2 WASHING MACHINE CONNECTION
NONE

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876 - 7147

ARCHITECT OF RECORD
HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 • F: 716.885.6414
HHLArchitects.com

PLUMBING COVERSHEET
REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION


SEAL

ISSUE DATE 09.19.2025


DRAWING NUMBER

P-001


PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET - SINGLE
FAMILY HOME
BENJIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203
PROJECT NUMBER: 2317.006




1 SANITARY AND VENT UNDER SLAB PLAN
SCALE: 1/4" = 1'-0"



2 SANITARY AND VENT FIRST FLOOR PLAN
SCALE: 1/4" = 1'-0"



3 SANITARY AND VENT SECOND FLOOR PLAN
SCALE: 1/4" = 1'-0"



4 SANITARY AND VENT ATTIC PLAN
SCALE: 1/4" = 1'-0"

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE

SANITARY AND VENT PLUMBING

PLANS

REVISIONS AFTER ISSUANCE

NO. DATE DESCRIPTION

SEAL



ISSUE DATE 09.19.2025

DRAWING NUMBER

P-100

ARCHITECT OF RECORD

HHL Architects

172 Allen Street, Buffalo, New York 14201
716.885.0743 ■ F: 716.885.6414
HHLArchitects.com

TREDO ENGINEERING

STRUCTURAL

755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876-7147
MEP
4245 UNION RD.
BUFFALO, NY 14225
(716) 633-5598

PROJECT NAME/LOCATION:

DESCRIPTION [NEW CONSTRUCTION]



68 PULASKI STREET - SINGLE

FAMILY HOME

BENJIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

PROJECT NUMBER: 2317.006





DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION	TREDO ENGINEERING STRUCTURAL 755 SENECA ST., #202 BUFFALO, NY 14210 (716) 876 - 7147	PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET - SINGLE FAMILY HOME
	ARCHITECT OF RECORD HHL Architects 172 Allen Street, Buffalo, New York 14201 716.885.0743 • F: 716.885.6414 HHLArchitects.com	BEN LUC DEVELOPMENT LLC 403 MAIN STREET, SUITE 602 BUFFALO, NEW YORK 14203 PROJECT NUMBER: 2317.006
DRAWING TITLE PLUMBING RISER DIAGRAMS		
SEAL 		
ISSUE DATE 09.19.2025		
DRAWING NUMBER P-102		

PLUMBING SPECIFICATIONS			
PART 1 – GENERAL:		PART 6 – PIPE SLEEVES AND SEALS	
1. SYSTEMS ARE TO BE COMPLETE AND WORKABLE IN ALL RESPECTS, PLACED IN OPERATION, AND PROPERLY ADJUSTED.		1. PROVIDE SLEEVES FOR ALL PIPING PASSING THRU FLOORS, WALLS OR CEILINGS AND SEAL OPENING.	
2. CONTRACTOR SHALL PROVIDE FOR HIS OWN CLEAN-UP, REMOVAL AND LEGAL DISPOSAL OF ALL RUBBISH ON A DAILY BASIS.		2. FIRESTOP ALL PIPING PENETRATIONS THROUGH RATED FLOORS, WALLS AND PARTITIONS.	
3. FULLY COORDINATE ALL WORK WITH OTHER CONTRACTORS, SUBCONTRACTORS, THE OWNER, AND COOPERATE COMPLETELY.		3. PROVIDE WATERTIGHT SEAL ON ALL PIPES PASSING THRU EXTERIOR WALLS, FOUNDATIONS OR WATERPROOF FLOORS.	
PART 2 – CODES AND STANDARDS:		4. PROVIDE CHROME ESCUTCHEON PLATES ON ALL EXPOSED PIPING PASSING THRU FLOORS, WALLS OR CEILINGS.	
1. CONFORM TO ALL APPLICABLE CODES, GOVERNMENT REGULATIONS, AND LOCAL REQUIREMENTS. CODES INCLUDE, BUT ARE NOT LIMITED TO THE FOLLOWING, NYS BUILDING CODES (PLUMBING, MECHANICAL, AND FUEL GAS), AND NFPA.		PART 7 – WARRANTY	
PART 3 – BASE EQUIPMENT AND SUBSTITUTIONS:		1. FULLY WARRANT ALL MATERIALS, EQUIPMENT AND WORKMANSHIP FOR ONE (1) YEAR FROM DATE OF ACCEPTANCE.	
1. ALL EQUIPMENT AND MATERIALS SHALL BE NEW AND FREE OF DEFECTS AND HOLD A U.L. LABEL.		2. REPAIR OR REPLACE WITHOUT CHARGE TO THE OWNER ALL ITEMS FOUND DEFECTIVE DURING THE WARRANTY PERIOD.	
2. BASE EQUIPMENT, MANUFACTURER, MODEL, AND CAPACITY OF EQUIPMENT ARE LISTED IN SCHEDULE ON DRAWING. ANY OTHER MANUFACTURER OR MODEL IS CONSIDERED A SUBSTITUTION.		PART 8 – SCOPE:	
3. SUBSTITUTIONS ARE SUBJECT TO THE APPROVAL OF THE OWNER. IF A SUBSTITUTION IS SUBMITTED, IT IS THE CONTRACTOR'S RESPONSIBILITY TO EVALUATE IT AND CERTIFY THAT THE SUBSTITUTION IS EQUIVALENT IN ALL RESPECTS TO THE BASE SPECIFICATIONS.		1. FURNISH ALL PLUMBING FIXTURES, EQUIPMENT AND MATERIAL INDICATED AND SHOWN ON DRAWINGS AND INSTALL COMPLETE AND PLACE IN PROPER OPERATION.	
4. IF SUBSTITUTIONS ARE APPROVED, NOTIFY ALL OTHER CONTRACTORS, SUBCONTRACTORS OR TRADES AFFECTED BY SUBSTITUTION AND FULLY COORDINATE ANY COSTS RESULTING FROM SUBSTITUTION, WHETHER BY CONTRACTOR OR OTHERS, SHALL BE RESPONSIBILITY OF AND PAID FOR BY SUBSTITUTING CONTRACTOR.		2. PLUMBING SYSTEMS CONSISTS OF, BUT NOT LIMITED TO THE FOLLOWING:	
5. ALL EQUIPMENT SHALL BE INSTALLED IN FULL ACCORDANCE WITH THE MANUFACTURERS DATA AND INSTALLATION INSTRUCTIONS. IT IS THIS CONTRACTORS RESPONSIBILITY TO CHECK AND CONFORM TO THESE REQUIREMENTS PRIOR TO START OF WORK.		A. PLUMBING FIXTURES WITH ALL REQUIRED TRIM AND VALVES.	
PART 4 – CHECK, START, ADJUST, AND BALANCING INSTRUCTIONS:		B. PLUMBING SPECIALTIES AS REQUIRED FOR COMPLETE INSTALLATION.	
1. AFTER INSTALLATION AND SERVICING, CHECK ALL EQUIPMENT AND PERFORM START UP IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.		C. COLD/HOT WATER, WASTE, VENT AND NATURAL GAS PIPING.	
2. ALL PIPING SHALL BE FULLY TESTED AND MADE FREE OF LEAKS.		D. INSULATION OF PIPING ITEMS AS NOTED.	
3. INSTRUCT OWNER IN OPERATION OF SYSTEMS AND SUBMIT OPERATING AND MAINTENANCE MANUAL ON ALL EQUIPMENT AND SYSTEMS.		PART 9 – SANITARY SEWERS/DRAINAGE SYSTEMS:	
PART 5 – CUTTING, PATCHING, AND DRILLING:		1. INSTALL SANITARY SEWERS, STACKS, VENTS, FLOOR DRAINS AND CLEANOUTS FOR PROJECT AND EXTEND AS INDICATED ON THE DRAWINGS.	
1. DO NOT CUT ANY STRUCTURAL COMPONENTS WITHOUT THE APPROVAL OF THE ARCHITECT OF RECORD.		PART 10 – VALVES:	
2. PATCH AND FINISH TO MATCH ADJACENT AREAS THAT HAVE BEEN CUT, DAMAGED OR MODIFIED AS A RESULT OF THE INSTALLATION OF PLUMBING EQUIPMENT. FIRE STOP ALL PENETRATIONS OF FIRE RATED CONSTRUCTION IN A CODE APPROVED MANNER IN ORDER TO MAINTAIN A FIRE RATING.		1. PROVIDE BALL VALVES, CHECK VALVES OR BALANCING VALVES AS INDICATED OR WHERE REQUIRED FOR PROPER MAINTENANCE, ISOLATION AND SAFETY.	
		2. DOMESTIC WATER: BALL VALVES SIMILAR TO MILWAUKEE NO. BA-100S THREADED OR NO. BA-150S SOLDERED WITH BUNA SEATS, PACKING AND GASKETS, 300 PSIG W.O.G. WORKING PRESSURE OR EQUIVALENT APPOLLO, GRINNELL OR WATTS.	
		3. PROVIDE UL LISTED AND AGA APPROVED LUBRICATED PLUG VALVES AND RATED FOR 125 PSIG.	
		A. 3" AND SMALLER – THREADED ENDS.	
		B. 4" AND LARGER – FLANGES ENDS.	
		PART 11 – PIPING INSULATION:	
		1. INSULATE THE FOLLOWING:	
		A. HOT WATER PIPING.	
		B. COLD WATER PIPING.	
		C. ANY REMOVED OR UN-INSULATED PIPING IN WORK AREA.	
		2. INSULATION PRODUCTS AND INSULATION SHALL COMPLY WITH ENERGY CONSERVATION CONSTRUCTION CODE OF NEW YORK STATE.	
		3. WATER PIPING INSULATION SHALL BE PREFORMED, SNAP-ON FIBERGLASS INSULATION WITH PAINTABLE WHITE KRAFT OR ALUMINUM FOIL JACKET.	
		4. ROOF DRAINAGE INSULATION SHALL BE SIMILAR TO HOT WATER WITH VAPOR BARRIER.	
		PART 12 – WATER PIPING:	
		1. PROVIDE DOMESTIC WATER PIPING AS NOTED PER PLUMBING FIXTURE AND EQUIPMENT SCHEDULE.	
		2. INCLUDE UNIONS, OR OTHER DISCONNECT MEANS, STOPS OR VALVES FOR ISOLATION OF FIXTURES AND EQUIPMENT. VALVES TO BE FULLY COMPATIBLE WITH PIPING FOR SERVICE INTENDED AS MANUFACTURED BY NIBCO, CRANE OR OTHER APPROVED MANUFACTURER.	
		PART 13 – STERILIZATION OF WATER PIPING:	
		1. THE WATER SUPPLY AND DISTRIBUTION SYSTEM SHALL BE STERILIZED WITH CHLORINE IN SOLUTION IN ACCORDANCE WITH THE AMERICAN WATER WORKS ASSOCIATION PUBLICATION C-601-1954 AND LOCAL ORDINANCES.	
		2. ALL WORK AND CERTIFICATION OF PERFORMANCE SHALL BE DONE BY APPROVED APPLICATIONS OR QUALIFIED PERSONNEL WITH CHEMICAL AND LABORATORY EXPERIENCE. SUBMIT A CERTIFICATE OF STERILIZATION.	
		PART 14 – PIPING TEST:	
		1. ALL PIPING SYSTEMS INCLUDING VALVES AND ACCESSORIES SHALL BE TESTED AS FOLLOWS: TEST PRESSURE SHALL BE MAINTAINED WITH NO LEAKS FOR DURATION SPECIFIED.	
		A. SOIL, WASTE, AND VENT – FILL WITH WATER TO 10 FT. ABOVE HIGHEST FIXTURE ON OUTLET, TIGHT FOR 8 HOURS.	
		B. HOT AND COLD WATER – 150 PSIG HYDROSTATIC. TIGHT FOR HOURS.	
		C. NATURAL GAS PIPING – TEST AT 15 PSIG AIR PRESSURE FOR MINIMUM OF 1 HOUR.	
		PART 15 – SUPPORTS AND HANGERS:	
		1. HANGERS AND SUPPORTS ARE TO BE PROVIDED TO PROPERLY SUPPORT, SECURE AND ALIGN PIPING AND TO MEET CONDITIONS. SPACING AND TO COMPLY WITH LOCAL CODE REQUIREMENTS.	
		PART 16 – EQUIPMENT IDENTIFICATION:	
		1. PREPARATION:	
		A. CLEAN PIPING AND EQUIPMENT SURFACES OF SUBSTANCES THAT COULD IMPAIR BOND OF IDENTIFICATION DEVICES, INCLUDING DIRT, OIL, GREASE, RELEASE AGENTS, AND INCOMPATIBLE PRIMERS, PAINTS, AND ENCAPSULANTS.	
		B. LOCATE EQUIPMENT LABELS WHERE ACCESSIBLE AND VISIBLE.	
		2. PIPING IDENTIFICATION:	
		A. GENERAL REQUIREMENTS FOR MANUFACTURED PIPE LABELS: PREPRINTED, COLOR-CODED, WITH LETTERING INDICATING SERVICE, AND SHOWING FLOW DIRECTION.	
		B. PRETENSIONED PIPE LABELS: PRECOILED, SEMIRIGID PLASTIC FORMED TO COMPLETELY COVER THE CIRCUMFERENCE OF PIPE AND TO ATTACH TO PIPE WITHOUT FASTENERS OR ADHESIVE.	
		C. SELF-ADHESIVE PIPE LABELS: PRINTED PLASTIC WITH CONTACT-TYPE, PERMANENT-ADHESIVE BACKING.	
		D. PIPE LABEL CONTENTS: INCLUDE IDENTIFICATION OF PIPING SERVICE USING SAME DESIGNATIONS OR ABBREVIATIONS AS USED ON DRAWINGS, PIPE SIZE, AND AN ARROW INDICATING FLOW DIRECTION.	
		a. FLOW-DIRECTION ARROWS: INTEGRAL WITH PIPING SYSTEM SERVICE LETTERING TO ACCOMMODATE BOTH DIRECTIONS, OR AS SEPARATE UNIT ON EACH PIPE LABEL TO INDICATE FLOW DIRECTION EVERY 20'-0".	
		b. LETTERING SIZE: AT LEAST 1-1/2 INCHES HIGH.	
		3. VALVE TAGS:	
		A. VALVE TAGS: STAMPED OR ENGRAVED WITH 1/4-INCH LETTERS FOR PIPING SYSTEM ABBREVIATION AND 1/2-INCH NUMBERS.	
		a. TAG MATERIAL: BRASS, 0.032-INCH MINIMUM THICKNESS, AND HAVING PREDRILLED OR STAMPED HOLES FOR ATTACHMENT HARDWARE.	
		b. FASTENERS: BRASS WIRE-LINK OR BEADED CHAIN; OR S-HOOK.	
		B. VALVE SCHEDULES: FOR EACH PIPING SYSTEM, ON 8-1/2-BY-11-INCH BOND PAPER. TABULATE VALVE NUMBER, PIPING SYSTEM, SYSTEM ABBREVIATION (AS SHOWN ON VALVE TAG), LOCATION OF VALVE (ROOM OR SPACE), NORMAL-OPERATING POSITION (OPEN, CLOSED, OR MODULATING), AND VARIATIONS FOR IDENTIFICATION. MARK VALVES FOR EMERGENCY SHUTOFF AND SIMILAR SPECIAL USES.	
		a. VALVE-TAG SCHEDULE SHALL BE INCLUDED IN OPERATION AND MAINTENANCE DATA.	
		C. INSTALL TAGS ON VALVES AND CONTROL DEVICES IN PIPING SYSTEMS, EXCEPT CHECK VALVES; VALVES WITHIN FACTORY-FABRICATED EQUIPMENT UNITS; SHUTOFF VALVES; FAUCETS; CONVENIENCE AND LAWN-WATERING HOSE CONNECTIONS; AND SIMILAR ROUGHING-IN CONNECTIONS OF END-USE FIXTURES AND UNITS. LIST TAGGED VALVES IN A VALVE SCHEDULE.	
		D. VALVE-TAG APPLICATION SCHEDULE: TAG VALVES ACCORDING TO SIZE, SHAPE, AND COLOR SCHEME AND WITH CAPTIONS SIMILAR TO THOSE INDICATED IN THE FOLLOWING SUBPARAGRAPHS:	
		a. VALVE-TAG SIZE AND SHAPE:	
		a.a. COLD WATER: 2 INCHES, ROUND.	
		a.b. HOT WATER: 2 INCHES, ROUND.	
		a.c. GAS: 2 INCHES, ROUND.	
		b. VALVE-TAG COLOR:	
		b.a. COLD WATER: NATURAL.	
		b.b. HOT WATER: NATURAL.	
		b.c. GAS: NATURAL.	
		c. LETTER COLOR:	
		c.a. COLD WATER: BLACK.	
		c.b. HOT WATER: BLACK.	
		c.c. GAS: YELLOW.	

REVISIONS AFTER ISSUANCE

NO.

DATE

DESCRIPTION

PLUMBING SPECIFICATIONS

DRAWING NUMBER

P-200

SEAL



ISSUE DATE 09.19.2025

DRAWING TITLE

PLUMBING SPECIFICATIONS

DRAWING SUBMISSION STATUS:

[] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [X] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

ARCHITECT OF RECORD

HHL Architects

172 Allen Street, Buffalo, New York 14201
716.885.0740 • F: 716.885.6414
HHLarchitects.com

TREDO ENGINEERING

STRUCTURAL

7555 SENECA ST., #202
BUFFALO, NY 14210
(716) 876 - 7147

MEP

4245 UNION RD.
BUFFALO, NY 14225
(716) 633 - 5598

PROJECT NAME/LOCATION:
DESCRIPTION
[NEW CONSTRUCTION]

68 PULASKI STREET - SINGLE FAMILY HOME

BENLUC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

PROJECT NUMBER: 2317.006

SPECIFICATION

1. IDENTIFICATION:
EQUIPMENT NAMEPLATES SHALL INCLUDE MANUFACTURER, PRODUCT NAME, MODEL AND SERIAL NUMBERS, CAPACITY, OPERATING AND POWER CHARACTERISTICS, ESSENTIAL DATA, AND LABELS OF TESTED COMPLIANCES.
DUCT AND PIPE MARKERS SHALL BE ENGRAVED COLOR CODED LAMINATED PLASTIC. INCLUDE DIRECTION OF AIRFLOW AND DUCT SERVICE (i.e. SUPPLY, RETURN, EXHAUST).
PIPING MARKERS SHALL COMPLY WITH ASME A13.1 FOR LOCATION, SIZE, AND COLOR.

2. DUCTWORK AND ACCESSORIES.
TYPE OF SYSTEM: LOW PRESSURE.
ALL DUCTWORK AND FITTINGS, SELECTIONS, APPLICATIONS AND INSTALLATION SHALL BE IN ACCORDANCE WITH "SMANCA" - "HVAC DUCT CONSTRUCTION STANDARDS".
CONSTRUCTION: LOW PRESSURE DUCTWORK SHALL BE CONSTRUCTED OF GALVANIZED STEEL SHEETS. DUCTWORK SHALL CONFORM ACCURATELY TO THE DIMENSIONS INDICATED, AND SHALL BE STRAIGHT AND SMOOTH ON THE INSIDE WITH JOINTS NEATLY FINISHED. DUCTS SHALL BE SECURE AND ANCHORED TO THE BUILDING'S STRUCTURAL COMPONENTS AND FRAMING, AND SHALL BE FABRICATED AND SUPPORTED IN SUCH A MANNER AS TO PREVENT VIBRATION AND PULSATION UNDER OPERATING CONDITIONS. BUTTON PUNCH OR BOLD CONNECTIONS IN STANDING SEAMS SHALL BE SPACED AT NOT GREATER THAN 6-INCHES ON CENTERS. LONGITUDINAL LOCKS OR SEAMS TERMED "BUTTON PUNCH SNAP LOCK" ARE ACCEPTABLE IN LIEU OF PITTSBURGH LOCKS. ELBOWS SHALL BE RADIUS TYPE WITH A CENTER RADIUS OF 1-1/2 TIMES THE WIDTH OR DIAMETER OF THE DUCT. WHERE SPACE DOES NOT PERMIT, THE USE OF SHORT RADIUS ELBOWS HAVING A MINIMUM RADIUS OF 1.0 TIMES THE WIDTH OR DIAMETER OF THE DUCT, OR SQUARE ELBOWS WITH FACTORY FABRICATED TURNING VANES MAY BE USED.
ALL DUCT JOINTS AND TRANSVERSE AND LONGITUDINAL SEAMS SHALL BE SEALED WITH A LATEX TYPE DUCT SEALER APPROVED BY THE ENGINEER.
FITTINGS: SQUARE ELBOWS, FITTINGS, AND BRANCH TAKE-OFFS SHALL BE DESIGNED AND CONSTRUCTED AS SPECIFIED IN SMACNA. ALL GENERAL VENTILATION ITEMS SHALL COMPLY WITH NFPA BULLETIN 90A.
SLEEVED AND FRAMED OPENINGS: SPACE BETWEEN THE SLEEVED OR FRAMED OPENING AND THE DUCT AND THE DUCT INSULATION SHALL BE PACKED WITH MINERAL WOOL OR OTHER APPROVED MATERIAL AND SEALED WITH APPROPRIATE MATERIAL TO MEET THE REQUIREMENTS OF WALL CONSTRUCTION FOR SMOKE OR FIRE CONTROL.
SINGLE WALL ROUND FITTINGS: MANUFACTURERS STANDARD FITTINGS FABRICATED AS INDICATED BELOW, UNLESS OTHERWISE INDICATED JOINTS MAY BE OF STANDING SEAM CONSTRUCTION, SOLID WELDED OR SPOTWELDED AND BONDED.
ELBOWS: FABRICATE IN DIE-FORMED, GORED, PLEATED, OR MITERED CONSTRUCTION. FABRICATE THE BEND RADIUS OF DIE-FORMED, GORED, AND PLEATED ELBOWS 1.5 TIMES THE ELBOW DIAMETER. UNLESS ELBOW CONSTRUCTION IS INDICATED, PROVIDE ELBOWS MEETING THE FOLLOWING REQUIREMENTS:

MITERED ELBOWS: FABRICATE WITH SOLID WELDED CONSTRUCTION IN GAUGES SPECIFIED BELOW:
NUMBER OF MITERED PIECES:
90 DEGREE ELBOW: 5 PIECES
60 DEGREE ELBOW: 4 PIECES
45 DEGREE ELBOW: 3 PIECES

ROUND MITERED ELBOW MATERIAL THICKNESS:
3 TO 14 INCH: 24 GAUGE.
15 TO 26 INCH: 22 GAUGE.

3. INSULATION:
PROVIDE ALL LABOR, MATERIALS, ETC., REQUIRED TO PRODUCE A COMPLETE FINISH INSULATION SYSTEM FOR THE FOLLOWING SYSTEMS:
-REFRIGERANT, AND CONDENSATE PIPING.
FLAME/SMOKE RATINGS:
PROVIDE COMPOSITE MECHANICAL INSULATION (INSULATION JACKETS, COVERINGS, SEALERS, MASTICS, AND ADHESIVES) WITH FLAME-SPREAD RATING OF 25 OR LESS AND SMOKE-DEVELOPED RATING OF 15 OR LESS, AS TESTED BY ANSI/ASTM E84 (NFPA 255) METHODS.

PIPING INSULATION:
MAKE: ARMAFLEX, OWEN-CORNING, CERTAINTeed, ARMSTRONG
TYPE: 1.5" THICK FOR REFRIGERATION PIPING, AND 1/2" FOR CONDENSATE PIPING.
SPECIAL: ALL OUTDOOR PIPING ON SHALL HAVE A PVC JACKET (22MM). ALL SEAMS CAULKED WATERTIGHT.
OUTDOOR INSULATION FINISH:
PIPING EXPOSED TO WEATHER SHALL HAVE INSULATION PROTECTIVE FINISH OR JACKETING INSTALLED AS RECOMMENDED BY THE MANUFACTURER. PIPING SHALL HAVE ALUMINUM JACKETING WITH MOISTURE BARRIER WITH LOCKING LONGITUDINAL SEAM AND BUTT STRAPS. FITTINGS, VALVES, FLANGES, ETC. SHALL HAVE FACTORY OR JOB FABRICATED ALUMINUM COVER SECURED WITH BANDING AND OR SCREWS.

4. PIPE AND FITTINGS:
PIPE AND FITTINGS:
ALL PIPING AND FITTINGS SECTION, APPLICATION, AND INSTALLATION SHALL BE IN ACCORDANCE WITH THE FOLLOWING STANDARDS:
AMERICAN SOCIETY FOR TESTING STANDARDS (ASTM).
AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME).
AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI).

PIPE HANGERS: CARPENTER AND PATERSON FEE AND MASON, GINNELL, F&S, CENTRAL, CONFORMING TO MANUFACTURERS STANDARDIZATION SOCIETY SPECIFICATION SP-58. INSULATED PIPING SHALL HAVE HANGERS OVERSIZED TO BE OUTSIDE THE PIPE INSULATION AND GALVANIZED INSULATION PROTECTION SHIELDS AT EACH HANGER.

BALL VALVES: BALL VALVES SHALL BE METAFLEX, MILWAUKEE, WATTS, OR NIBCO. VALVES SHALL BE 150 PSI, TWO PIECE CONSTRUCTION WITH ANTI-BLOWOUT STEM. VALVE SHALL BE CONSTRUCTED OF BRASS AND HAVE TEFLON SEATS.

5. REFRIGERANT PIPING
GENERAL: PROVIDE ALL COMPONENTS TO FURNISH A FULLY FUNCTIONAL HVAC SYSTEM PER THE EQUIPMENT MANUFACTURERS INSTALLATION REQUIRES. COMPONENTS SHALL INCLUDE CHECK VALVES, SERVICE VALVES, SAFETY VALVES, EXPANSION VALVES, FILTER DRIERS, MOISTURE/LIQUID INDICATORS, ETC - COMPLETE.
SUCTION LINES: COPPER, TYPE ACR, ANNEALED-TEMPER TUBING AND WROUGHT-COPPER FITTINGS WITH BRAZED OR SOLDERED JOINTS.
LIQUID LINES: COPPER, TYPE ACR, ANNEALED OR DRAWING-TEMPER TUBING AND WROUGHT-COPPER FITTINGS WITH BRAZED OR SOLDERED JOINTS.
INSTALLATION: INSTALL PIPING IN CONCEALED LOCATIONS UNLESS OTHERWISE INDICATED AND EXCEPT IN EQUIPMENT ROOMS AND SERVICE AREAS. INSTALL PIPING FREE OF SAGS AND BENDS. ARRANGE PIPING TO ALLOW INSPECTION AND SERVICE OF REFRIGERATION EQUIPMENT AND VALVES AND GAUGES IN ACCESSIBLE LOCATIONS FOR SERVICE AND INSPECTION.
PIPING SLOPE: INSTALL HORIZONTAL SUCTION LINES WITH UNIFORM SLOPE DOWNWARD TO COMPRESSOR. INSTALL TRAPS AND SOUBLE RISERS TO ENTRAIN OIL IN VERTICAL RUNS. LIQUID LINES MAY BE INSTALLED LEVEL. WHEN BRAZING OR SOLDERING, REMOVE SOLENOID-VALE AND SIGHT GLASSES. ALSO REMOVE VALVE STEMS, SEATS, AND PACKING, AND ACCESSIBLE INTERNAL PARTS OF REFRIGERANT SPECIALTIES. DO NOT APPLY HEAT NEAR EXPANSION-VALVE BULB.
SYSTEM CHARGING: INSTALL CORE IN FILTER DRYERS AFTER LEAK TEST, BUT BEFORE EVACUATION. EVACUATE ENTIRE REFRIGERANT SYSTEM WITH A VACUUM PUMP TO 500 MICROMETERS. IF VACUUM HOLDS FOR 12 HOURS, SYSTEM IS READY FOR CHARGING. BREAK VACUUM WITH REFRIGERANT GAS, ALLOWING PRESSURE TO BUILD UP TO 2 PSIG. CHARGE SYSTEM WITH NEW FILTER-DRYER CORE IN CHARGING LINE.

6. MULTI-ZONE SPLIT SYSTEM INDOOR UNITS
CABINET: ENAMEL STEEL WITH REMOVABLE PANELS ON FRONT AND OR ENDS. COLOR SELECTED BY THE ARCHITECT.
REFRIGERANT COIL: COPPER TUBE, WITH MECHANICALLY BONDED ALUMINUM FINS AND THERMAL-EXPANSION VALVE. COMPLY WITH ARI 210/240.
FAN: DIRECT DRIVE, CENTRIFUGAL.

FAN MOTORS: COMPLY WITH NEMA DESIGNATION, TEMPERATURE RATING, SERVICE FACTOR, ENCLOSURE TYPE, AND EFFICIENCY REQUIREMENTS SPECIFIED.
FILTERS: PER,ANENT, CLEANABLE.
CONDENSATE DRAIN PANS: FABRICATED WITH ONE PERCENT SLOPE IN AT LEAST TWO PLANES TO COLLECT CONDENSATE FROM COOLING COILS, INCLUDING COIL PIPING CONNECTIONS, COIL HEADERS, AND RETURN BENDS.
CONDENSATE LIFT PUMPS: WHEN REQUIRED (SEE PLAN SCHEDULES), MANUFACTURER: BLUE DIAMOND. MODEL NUMBER: BD-BLUE-230.
BASIS OF DESIGN: LG.
ACCEPTABLE ALTERNATES: MITSUBISHI/TRANE, SAMSUNG, HITACHI.

7. MULTI-ZONE SPLIT SYSTEM AIR COOLED CONDENSING UNIT
CASING: STEEL, FINISHED WITH BAKED ENAMEL IN COLOR SELECTED BY THE ARCHITECT, WITH REMOVABLE PANELS FOR ACCESS TO CONTROLS. WEEP HOLES FOR WATER DRAINAGE, AND MOUNTING HOLES IN BASE. PROVIDE BRASS SERVICE VALVES, FITTINGS, AND GAGE PORTS ON EXTERIOR OF CASING.
COMPRESSOR: HERMETICALLY SEALED WITH CRANKCASE HEATER NAD MOUNTED ON VIBRATION ISOLATION DEVICE. COMPRESSOR MOTOR SHALL HAVE THERMAL AND CURRENT-SENSITIVE OVERLOAD DEVICES, START CAPACITOR RELAY, AND CONTRACTOR. COMPRESSOR TYPE SHALL BE SCROLL.
REFRIGERANT: R-410A
REFRIGERANT COIL: COPPER TUBE, WITH MECHANICALLY BONDED ALUMINUM FINES AND LIQUID SUBCOOLER. COMPLY WITH ARI 210/240.
HEAT PUMP COMPONENTS: REVERSING VALVE AND BRANCH REFRIGERANT DISTRIBUTION BOXES.
FAN: ALUMINUM-PROPELLER TYPE DIRECTLY CONNECT TO MOTOR.
MOUNTING BASE: WALL MOUNTED.
CERTIFICATION: ENERGY STAR CERTIFIED, COLD CLIMATE CERTIFICATION, NEEP (NORTHEAST ENERGY EFFICIENCY PARTNERSHIPS) CERTIFIED.
ACCESSORIES: AS NOTED IN THE SCHEDULES.
BASIS OF DESIGN: LG.
ACCEPTABLE ALTERNATES: MITSUBISHI/TRANE, SAMSUNG, HITACHI.

8. CEILING TYPE VENTILATORS
FINISH: PROVIDE FAN WITH ENAMEL FINISH. COLOR SELECTED BY THE ARCHITECT.
GENERAL: CENTRIFUGAL FAN, DIRECT DRIVE, DESIGNED FOR INSTALLATION IN CEILINGS.
HOUSING: GALVANIZED STEEL, LINED WITH ACOUSTICAL INSULATION.
FAN WHEEL: CENTRIFUGAL WHEELS DIRECTLY MOUNTED ON MOTOR SHAFT FAN SHROUDS, MOTOR, AND FAN WHEEL SHALL BE REMOVABLE FOR SERVICE.
CONTROL: SWITCHED.
ACCESSORIES: MANUFACTURERS WALL CAP, INTEGRAL BACKDRAFT DAMPER, VIBRATION ISOLATORS.
CERTIFICATION: ENERGY STAR CERTIFIED.
BASIS OF DESIGN: BROAN.
ACCEPTABLE ALTERNATES: PANASONIC, COOK.

9. ELECTRIC RESISTANCE HEATERS
GENERAL: AS SCHEDULED.
ACCESSORIES: AS SCHEDULED.
BASIS OF DESIGN: RUNTAL, MARKEL.
ACCEPTABLE ALTERNATES: Q-MARK, BERKO, DAYTON.

8. RECORD DRAWINGS
COMPUTER AIDED DRAWINGS (CAD) RECORD DRAWINGS SHALL BE SUPPLIED BY THE HVAC CONTRACTOR AFTER THE SYSTEM HAS BEEN ACCEPTED BUT PRIOR TO FINAL PAYMENT.

9. OPERATOR INSTRUCTION
AFTER SYSTEM COMMISSIONING THE HVAC CONTRACTOR SHALL PROVIDE ON-SIGHT OPERATOR INSTRUCTION TO THE OWNERS OPERATING PERSONNEL. OPERATOR INSTRUCTION DURING NORMAL WORKING HOURS SHALL BE PERFORMED BY THE COMPETENT REPRESENTATIVES FAMILIAR WITH THE INSTALLED SYSTEM. AT A TIME MUTUALLY AGREED UPON WITH THE OWNER'S REPRESENTATIVE, THE HVAC CONTRACTOR SHALL GIVE FOUR (4) HOURS (OR REQUIRED AMOUNT OF TIME) OF INSTRUCTIONS TO THE OWNERS DESIGNATED PERSONNEL ON THE OPERATION OF ALL EQUIPMENT IN THE SYSTEM AND DESCRIBE ITS INTENDED USE. AN OWNERS MANUAL PREPARED FOR THE PROJECT BY THE HVAC CONTRACTOR SHALL BE USED DURING INSTRUCTION. THREE (3) COPIES OF THE OWNERS MANUAL SHALL BE PROVIDED TO THE OWNERS REPRESENTATIVE.


10. ADJUSTING, BALANCING, TESTING, AND INSPECTION:
ALL AIR AND WATER SYSTEMS SHALL BE BALANCED. TESTING, BALANCING, AND ADJUSTING SHALL BE PERFORMED BY FIRMS CERTIFIED BY THE NATIONAL ENVIRONMENT BALANCING BUREAU "NEBB" OF FIRMS QUALIFYING IN COMPLIANCE WITH THE PARAGRAPH ON PERFORMANCE.
FIELD TESTS: PROPOSED TESTING PROGRAM SHALL BE SUBMITTED TO THE ENGINEER AT LEAST TWO WEEKS PRIOR TO THE SCHEDULED TEST TO ASSURE AGREEMENT AS TO PERSONNEL AND INSTRUMENTATION REQUIRED, AND THE SCOPE OF THE TESTING PROGRAM. FINAL TEST REPORT SHALL BE ON PREPARED FORMS REQUIRED BY NEBB.

11. VERIFICATION OF DIMENSIONS: THE CONTRACTOR SHALL BECOME FAMILIAR WITH ALL DETAILS OF THE WORK, VERIFY ALL DIMENSIONS IN THE FIELD, AND SHALL ADVISE THE ENGINEER OF ANY DISCREPANCY BEFORE PERFORMING WORK.


12. COORDINATION: HEATING CONTRACTOR SHALL COORDINATE ALL WORK AND MATERIALS WITH OTHER CONTRACTORS.

13. GUARANTEE: PROVIDE 1 YEAR GUARANTEE THAT ANY DEFECTS IN MATERIALS OR WORKMANSHIP OCCURRING DURING TERMS OF SAID GUARANTEE SHALL BE MADE GOOD BY THE CONTRACTOR WITHOUT EXPENSE TO OWNER.

HVAC SYMBOL LIST			
	FLOW ARROW	8"Ø	TYPICAL ROUND DUCT DESIGNATION
	PITCH PIPING (DOWN IN DIRECTION OF ARROW)	24x12	TYPICAL DUCT SIZE DESIGNATION (INSIDE SHEETMETAL DIMENSIONS)
	REFRIGERANT PIPING	EF	EXHAUST FAN
	PIPING DROP/RISE	EVAP	EVAPORATOR
	THERMOSTAT	ACCU	AIR COOLED CONDENSING UNIT
	ELECTRIC BASEBOARD	CD	CONDENSATE DRAIN PIPING
	REFRIGERANT LIQUID LINE		
	REFERIGERANT SUCTION LINE		
	ALUMINUM DRYER VENTING		
	ELECTRIC WALL RADIATOR		
	KITCHEN HOOD		
	CLEAN OUT		




2 AIR COOLED CONDENSING UNIT INSTALLATION DETAIL
SCALE: NTS




1 SPLIT SYSTEM REFRIGERANT PIPING DIAGRAM
SCALE: NTS

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET - SINGLE FAMILY HOME		PROJECT NUMBER: 2317.006	
TREDO ENGINEERING STRUCTURAL 755 SENECA ST., #202 BUFFALO, NY 14210 (716) 876 - 7147			
HHL Architects 172 Allen Street, Buffalo, New York 14201 716.885.0743 ■ F: 716.885.6414 hhlarchitects.com			
DRAWING TITLE MECHANICAL SPECIFICATIONS & DETAILS		ISSUE DATE 09.19.2025	
REVISIONS AFTER ISSUANCE NO. DATE DESCRIPTION		DRAWING NUMBER M-001	
SEAL 			



1 TYPE 4 – MECHANICAL FIRST FLOOR PLAN
SCALE: 1/4" = 1'-0"



2 TYPE 4 – MECHANICAL SECOND FLOOR PLAN
SCALE: 1/4" = 1'-0"

EXHAUST FAN SCHEDULE (EF)

UNIT TAG	SERVICE/LOCATION	TYPE	CFM	E.S.P.	DRIVE	MOTOR			SOUND (SONES)	WEIGHT (LBS.)	DESIGN EQUIPMENT	REMARKS
						AMPS	POWER	VOLTAGE				
EF-1	BATHROOM'S	CEILING	80	0.10	DIRECT			120-60-1	0.70	10.0	NUTONE AERN80LK	1-3

NOTES:

1. PROVIDE INLET/OUTLET FLANGE ADAPTERS.
2. PROVIDE INTEGRAL BACKDRAFT DAMPER.
3. PROVIDE HANGING KIT W/ NEOPRENE ISOLATORS.
4. PROVIDE ENERGY STAR CERTIFICATION.

MULTI-ZONE HEAT PUMP SCHEDULE (ACCU)

UNIT No.	MANUFACTURER	SYSTEM MODEL No.	NOMINAL TONAGE	RATED COOLING CAPACITY (MBH)	RATED HEATING CAPACITY (MBH)	POWER			HEATING COP	COOLING COP	OPERATING WEIGHT (LBS)	REMARKS
						POWER	MCA	MOP				
ACCU-1	LG	LMU361HHV	3.0	36.0	45.0	208-1-60	32.7	40A	4.0	4.25	218	1-7

NOTES:

1. 100% HEATING CAPACITY AT -13°F OUTSIDE AMBIENT CONDITIONS. OVERSIZED COOLING CAPACITY SHALL NOT BE ACCEPTED.
2. PROVIDE WALL MOUNTED BRACKET.
3. PROVIDE R/RLS PIPING BETWEEN INDOOR/OUTDOOR UNITS.
4. PROVIDE ELECTRICAL DISCONNECT SWITCH.
5. PROVIDE BASE PAIN HEATERS.
6. PROVIDE COLD CLIMATE ENERGY STAR LABELED EQUIPMENT.

GENERAL PLAN NOTES

THESE DRAWINGS ARE DIAGRAMMATIC IN NATURE AND INDICATE THE SIZE AND GENERAL ARRANGEMENT OF PIPING, DUCTWORK, EQUIPMENT, ETC. EXACT LOCATIONS AND ROUTINGS SHALL BE DETERMINED IN THE FIELD BEFORE AND AS THE WORK PROGRESSES. CAREFULLY COORDINATE THE WORK OF THIS TRADE WITH ALL OTHER TRADES.

DRAWINGS DO NOT INDICATE ALL OFFSETS, CHANGES IN ELEVATION, ETC. WHICH MAY BE REQUIRED BY ACTUAL FIELD CONDITIONS. THE CONTRACTOR IS TO FIELD VERIFY CONDITIONS PRIOR TO INSTALLATION AND MAKE SUCH CHANGES IN PIPING, DUCTWORK, EQUIPMENT LOCATIONS, ETC. AS NECESSARY TO ACCOMMODATE FIELD CONDITIONS. COORDINATE ALL CHANGES WITH OTHER TRADES AND ARCHITECT/ENGINEER.

ALL CUTTING AND PATCHING OF BUILDING COMPONENTS REQUIRED TO ACCOMMODATE THE WORK OF THIS CONTRACT SHALL BE THE RESPONSIBILITY OF THIS CONTRACT. ALL PATCHING SHALL MATCH THE EXISTING COMPONENTS AND FINISHES. CUTTING AND PATCHING WORK SHALL BE PERFORMED BY PERSONNEL TRAINED AND REGULARLY EMPLOYED FOR SUCH SERVICES.

INSTALL ALL PIPING, DUCTWORK, EQUIPMENT, ETC. TO AVOID INTERFERENCE WITH THE OPERATION AND SERVICING OF ALL EQUIPMENT. IN GENERAL, DO NOT INSTALL ANYTHING ABOVE OR WITHIN 3 FT. IN FRONT OF ELECTRICAL GEAR.

THE WORK INCLUDED IN THIS CONTRACT ENCOMPASSES BOTH THE DRAWINGS AND SPECIFICATIONS. WORK INCLUDED ON THE DRAWINGS ONLY, OR IN THE SPECIFICATION ONLY, SHALL BE INCORPORATED AS IF INCLUDED IN BOTH. SYSTEMS ARE INTENDED TO BE COMPLETE AND FULLY FUNCTIONING. IT IS NOT INTENDED TO SHOW EVERY ITEM OF WORK OR MINOR PIECE OF EQUIPMENT. THE CONTRACTOR SHALL PROVIDE SUCH COMPONENTS, ETC. AS NECESSARY OR REQUIRED FOR A FULLY FUNCTIONING SYSTEM.

FLEXIBLE DUCT CONNECTIONS AT AIR DEVICES ARE NOT ALLOWED.

ALL CONDENSATE DRAIN PIPING SHALL BE 1"Ø, UNLESS OTHERWISE NOTED.

DRYER VENTING (DV) NOTES: DRYER VENTING SHALL BE CONSTRUCTED OF ALUMINUM AND SHALL BE ASSEMBLED USING AN APPROVED JOINING METHOD. NO SCREWS SHALL PENETRATE THE INTERIOR OF THE PIPE. INSTALLATION SHALL COMPLY WITH SECTION 504 OF THE IBC 2015. PROVIDE FLEXIBLE CONNECTION TO EACH DRYER. VERTICAL PIPING SHALL BE HARD DUCT. ALL DUCTWORK LOCATED ABOVE INACCESSIBLE AREAS SHALL BE HARD DUCT CONNECTIONS. DO NOT PROVIDE UNIT SCREEN AT TERMINATION. PROVIDE RECESSED DRYER VENTING BOX. COORDINATE EXACT LOCATION WITH THE ARCHITECT.

REFER TO STRUCTURAL PLANS FOR CONCEALED PIPE ROUTING REQUIREMENTS. THE M.C. SHALL BE RESPONSIBLE FOR ALL CORE PENETRATIONS ASSOCIATED WITH THIS CONTRACT.

MECHANICAL PLAN NOTES (#)

1. PROVIDE HONEYWELL MODEL "TH115-240S" LINE VOLTAGE WALL MOUNTED THERMOSTAT. REFER TO SPECIFICATIONS FOR THERMOSTAT REQUIREMENTS. REFER TO ARCHITECTURAL ELEVATIONS FOR THERMOSTAT MOUNTING HEIGHTS.
2. TERMINATE 1"Ø SCH.-40 CONDENSATE PIPING 3'-0" ABOVE GRADE. TERMINATE WITH 45 DEGREE FITTING AND 1"Ø OPEN ENDED TERMINATION CAP WITH SCREENING.
3. 1"Ø CONDENSATE RISER DOWN TO 3'-0" ABOVE GRADE. INSTALL CONDENSATE RISER WITHIN EXTERIOR WALL CONSTRUCTION, INSIDE THE THERMAL ENVELOPE.
4. ALTERNATE No.1 - PROVIDE "LG" MODEL "PRRS1" AUXILIARY HEAT CONTROLLER, FIELD LOCATE CONTROLLER(S) IN THE 1ST FLOOR MECHANICAL ROOM. PROVIDE ALL INTERCONNECTING POWER, 12VDC, AND 24VAC COMMUNICATION WIRING. PROVIDE COMPATIBLE CONTROL RELAY RATED FOR THE SPECIFIED BASEBOARD WATTAGE. BASE BID - PROVIDE INTEGRAL KNOB STYLE THERMOSTAT.
5. PROVIDE INTEGRAL KNOB STYLE THERMOSTAT.
6. PROVIDE 3-1/4" x 10" DUCT CONNECTION TO KITCHEN RANGE HOOD BY OTHERS. PROVIDE SLOPPED WALL PENETRATION WITH INTEGRAL BACKDRAFT DAMPER.
7. RS/RL PIPING ROUTED IN ATTIC SPACE.

MULTI-ZONE HEAT PUMP SYSTEM INDOOR UNIT SCHEDULE (EVAP)

SYSTEM	UNIT No.	"LG" MODEL No.	TYPE	SUPPLY FAN H/M/L (CFM)	COOLING CAPACITY (MBH)	HEATING CAPACITY (MBH)	ELECTRICAL		OPERATING WEIGHT (LBS)	REMARKS
							POWER	MCA		
ACCU-1	EVAP-1	LMN079HVT	WALL MOUNTED	254/204/148	7.0	8.1	230-1-60	0.4	18.3	1-2
	EVAP-2	LMN090HSV5	WALL MOUNTED	268/218/169	9.0	10.9	230-1-60	0.4	18.3	1-2
	EVAP-3	LMN079HVT	WALL MOUNTED	254/204/148	7.0	8.1	230-1-60	0.4	18.3	1-2
	EVAP-4	LMN079HVT	WALL MOUNTED	254/204/148	7.0	8.1	230-1-60	0.4	18.3	1-2
	EVAP-5	LMN079HVT	WALL MOUNTED	254/204/148	7.0	8.1	230-1-60	0.4	18.3	1-2

NOTES:

1. PROVIDE WALL MOUNTED BRACKET.
2. PROVIDE "LG" MODEL "PREMTBVC2" WIRED THERMOSTAT/CONTROLLER

ELECTRIC RADIATOR SCHEDULE (ER)

UNIT TYPE	MANUFACTURER	MODEL No.	LENGTH	WATTS	BTU'S	POWER	AMPS	REMARKS
ER-1	RUNTAL	EWPP-6	36	880	3003	240-1-60	3.7	SEE NOTES

NOTES:

1. REFER TO FLOOR PLANS FOR CONTROL REQUIREMENTS/ACCESSORIES.
2. COLOR SELECTION BY THE ARCHITECT.
3. PROVIDE ELECTRICAL DISCONNECT.

ELECTRIC BASEBOARD HEATER SCHEDULE (EB)

UNIT TYPE	MANUFACTURER	MODEL No.	LENGTH	WATTS	BTU'S	POWER	AMPS	REMARKS
EB-1	MARKEL	H3703-024	24"	375	1275	240-1-60	1.6	SEE NOTE S
EB-2	MARKEL	H3720-096	96"	2000	6826	240-1-60	8.3	SEE NOTES
EB-3	MARKEL	H3706-036	36"	600	2040	240-1-60	2.5	SEE NOTES

NOTES:


1. REFER TO FLOOR PLANS FOR CONTROL REQUIREMENTS/ACCESSORIES.
2. PROVIDE 12-GAUGE HEAVY DUTY EXTRUDED ALUMINUM HOUSING.
3. COLOR SELECTION BY THE ARCHITECT.
4. PROVIDE ELECTRICAL DISCONNECT.

SPLIT SYSTEM BRANCH CONTROLLER SCHEDULE (BC)

UNIT No.	"LG" MODEL NUMBER	NUMBER OF BRANCHES	ELECTRICAL			OPERATING WEIGHT (LBS)	NOTES
			POWER	MCA	WATTS		
BC-1	PMBD3620	2	208/1/60	0.08	16	13	1
BC-2	PMBD3620	3	208/1/60	0.12	24	14.3	1

NOTES:


1. PROVIDE SERVICE VALVES FOR EACH PORT.




SINGLE LINE KEYED NOTES:

- 1 NOT USED
- 2 PROVIDE #4 SERVICE GROUND PER NEC. ALL GROUNDING PER NEC 250. REFER TO GROUNDING ELECTRODE DETAIL #2 ON THIS DRAWING FOR ADDITIONAL INFORMATION.
- 3 3 #250MCM AL IN 2-1/2" RIGID CONDUIT
- 4 3 #250MCM AL SEU SERVICE ENTRANCE RATED CABLE.
- 5 UTILITY METER/CT CABINET. COORDINATE FINAL REQUIREMENTS AND SEQUENCING WITH NATIONAL GRID PRIOR TO PERFORMING ANY WORK.

1 SINGLE LINE DIAGRAM
8-002 SCALE: NONE



2 GROUNDING ELECTRODE DETAIL
8-002 SCALE: NONE



4 DOOR BELL WIRING DETAIL
8-002 SCALE: NONE

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

DRAWING TITLE

ELECTRICAL DETAILS

REVISIONS AFTER ISSUANCE

NO.

DATE

DESCRIPTION

SEAL



ISSUE DATE 09.19.2025

DRAWING NUMBER

E-002

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876-7147

MEP
4245 UNION RD.
BUFFALO, NY 14225
(716) 633-5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 ■ F: 716.885.6414
HHLArchitects.com

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]

68 PULASKI STREET - SINGLE


FAMILY HOME

BEN LUC DEVELOPMENT LLC


403 MAIN STREET, SUITE 602

BUFFALO, NEW YORK 14203


PROJECT NUMBER: 2317.006



1 ELECTRICAL FIRST FLOOR PLAN
SCALE: 1/4" = 1'-0"



2 ELECTRICAL SECOND FLOOR PLAN
SCALE: 1/4" = 1'-0"



3 ELECTRICAL ATTIC PLAN
SCALE: 1/4" = 1'-0"

LCA		120/240	VOLTS	1	Ø	40	CIRCUITS		200A MCB	LUGS ONLY	3
		200	AMP. MAINS	3	WIRE	22	KAIC	SURFACE	MOUNTING	MAIN BRKR.	
DESCRIPTION		BRKR.	L1		L2		BRKR.	DESCRIPTION			
1	REFRIGERATOR	20A-1P	6.0	40.0			50A	ELECTRIC RANGE		2	
3	KITCHEN COUNTER	20A-1P			3.0	40.0	2P			4	
5	KITCHEN COUNTER	20A-1P	3.0	23.0			30A	WATER		6	
7	HOOD	20A-1P			12.0	23.0	2P	HEATER (WH-1)		8	
9	DISHWASHER	20A-1P GF	8.0	32.7			40A	CONDENSING		10	
11	GARBAGE DISPOSER	20A-1P GF			6.0	32.7	2P	UNIT (ACCU-1)		12	
13	BATHROOM GFI	20A-1P	1.5	22.0			30A	ELECTRIC		14	
15	LIVING ROOM RECEPTS.	15A-1P			9.0	22.0	2P	DRYER		16	
17	DINING ROOM RECEPTS.	15A-1P	9.0	10.0			20A-1P	WASHER		18	
19	BEDROOM 1 RECEPTS/LTG.	15A-1P			9.0			SPACE		20	
21	BEDROOM 2 RECEPTS/LTG.	15A-1P	6.0					SPACE		22	
23	BEDROOM 3 RECEPTS/LTG.	15A-1P			9.0			SPACE		24	
25	BATHROOM GFI	20A-1P	1.5	1.6			15A	EVAP- 1-5, BC-1,2		26	
27	SPACE				1.6		2P			28	
29	SPACE		8.3				20A	ELECTRIC BASEBOARDS		30	
31	SPACE				8.3		2P			32	
33	SPACE		8.3				20A	ELECTRIC BASEBOARDS		34	
35	SPACE				8.3		2P			36	
37	SPACE		10.0				20A	ELECTRIC BASEBOARDS		38	
39	SPACE				10.0		2P			40	
TOTAL CONNECTED AMPS/LEG			190.9		193.9		TOTAL CONNECTED KVA			46.2	
NEMA 1 ENCLOSURE											

- NOTES:
1. AFCI CIRCUIT BREAKER
 2. HACR CIRCUIT BREAKER
 3. PANEL SHALL BE EATON LOAD CENTER "BR" SERIES" C/W PLUG-ON BREAKERS, 14" WIDE ENCLOSURE, C/W GROUNDING KIT, COPPER BUS.
 4. E.C. SHALL FURNISH AND INSTALL AFCI/GFI DUAL FUNCTION CIRCUIT BREAKER.

GENERAL DRAWING NOTES:

- REFER TO DRAWING E-001 FOR ELECTRICAL SYMBOL LEGENDS AND SCHEDULES.
- E.C. SHALL PROVIDE FIRESTOPPING MATERIALS FOR ALL PANELS, OUTLET BOXES, RACEWAYS, ETC. PENETRATING THROUGH FIRE RATED WALLS. ALL OUTLETS IN RATED WALLS MUST BE INSTALLED A MINIMUM OF 12" FROM EACH OTHER OR PROPERLY FIRE-STOPPED IF WITHIN THE SAME WALL OR CEILING CAVITY.
- ALL 15A AND 20A, 125VAC RECEPTACLES IN RESIDENTIAL UNITS AND AREAS MUST BE LISTED AS TAMPER RESISTANT AS DEFINED IN 406.12.
- E.C. SHALL FURNISH AND INSTALL AFCI TYPE CIRCUIT BREAKERS FOR ALL 15A OR 20A, 120V BRANCH CIRCUITS SUPPLYING OUTLETS (INCLUDING SMOKE ALARMS) IN KITCHENS, FAMILY ROOMS, DINING ROOMS, LIVING ROOMS, PARLORS, LIBRARIES, DENS, BEDROOMS, SUNROOMS, RECREATIONS ROOMS, CLOSETS, HALLWAYS, LAUNDRY AREAS OR SIMILAR ROOMS.
- ALL 15A AND 20A, 120V VOLT BRANCH CIRCUITS SHALL BE WIRED WITH 2 #12 & 1 #12 GROUND IN 3/4" CONDUIT UNLESS OTHERWISE NOTED.
- REFER TO DRAWING E-002 FOR SINGLE LINE DIAGRAM AND ELECTRICAL DETAILS.
- REFER TO DRAWING E-201 FOR ELECTRICAL SPECIFICATIONS.

ELECTRICAL KEYED NOTES:

- SINGLE STATION SMOKE DETECTORS AND CARBON MONOXIDE DETECTORS SHALL BE TANDEM WIRED WITH OTHER SMOKE DETECTORS IN UNIT.
- ALL SINGLE STATION SMOKE DETECTORS AND CARBON MONOXIDE DETECTORS TO BE CONNECTED INTO LIGHTING BRANCH CIRCUIT AHEAD OF LOCAL SWITCHES.
- FURNISH AND INSTALL 50 AMP, 125/250 VOLT RATED NEMA 14-50R RECEPTACLE FOR ELECTRIC RANGE. PROVIDE MATCHING CORD AND PLUG. COORDINATE INSTALLATION WITH EQUIPMENT MANUFACTURER'S INSTRUCTIONS PRIOR TO ORDERING ELECTRICAL EQUIPMENT. PROVIDE 3 #6 AWG & 1 #10 AWG GROUND TO UNIT LOAD CENTER AND CONNECT TO 50A-2P CIRCUIT BREAKER (CIRCUITS 2,4).
- HOOD MOUNTED ABOVE RANGE. REFER TO ARCHITECTURAL DRAWINGS FOR MOUNTING HEIGHT.
- INSTALL RECEPTACLES WITHIN 12" OF THE COUNTERTOP WORK SURFACE.
- ELECTRIC SERVICE WEATHERHEAD. COORDINATE EXACT LOCATION AND REQUIREMENTS WITH UTILITY PRIOR TO PERFORMING ANY WORK.
- PROVIDE NEMA 14-30R OUTLET FOR ELECTRIC DRYER.
- COORDINATE LOCATION OF GARBAGE DISPOSAL SWITCH WITH OWNER PRIOR TO ROUGH-IN.
- ELECTRIC WATER HEATER. CONTRACTOR TO MAKE COMPLETE ELECTRICAL CONNECTION TO EQUIPMENT. PROVIDE 2 #10 AWG & 1 #10 AWG GROUND TO UNIT LOAD CENTER AND CONNECT TO 30A-2P CIRCUIT BREAKER (CIRCUITS 6,8). COORDINATE FINAL REQUIREMENTS WITH HEATER INSTALLER.
- ELECTRICAL UTILITY METER. REFER TO SINGLE LINE DIAGRAM ON DRAWING E-002 FOR ADDITIONAL REQUIREMENTS.

PROJECT NAME/LOCATION:
DESCRIPTION [NEW CONSTRUCTION]
68 PULASKI STREET - SINGLE
FAMILY HOME

BENJIC DEVELOPMENT LLC
403 MAIN STREET, SUITE 602
BUFFALO, NEW YORK 14203

TREDO ENGINEERING
STRUCTURAL
755 SENECA ST., #202
BUFFALO, NY 14210
(716) 876-7147

MEP
BUFFALO ENG., PC
4245 UNION RD.
BUFFALO, NY 14225
(716) 633-5598

HHL Architects
172 Allen Street, Buffalo, New York 14201
716.885.0743 • F: 716.885.6414
HHLarchitects.com

ELECTRICAL FLOOR PLANS

REVISIONS AFTER ISSUANCE
NO. DATE DESCRIPTION

DRAWING TITLE
ELECTRICAL FLOOR PLANS

ISSUE DATE 09.19.2025

DRAWING NUMBER
E-101

ELECTRICAL SPECIFICATIONS

BASIC ELECTRICAL REQUIREMENTS

- A. THE INSTRUCTIONS TO BIDDERS, FORM OF BID, FORM OF CONTRACT, GENERAL CONDITIONS, SUPPLEMENTARY GENERAL CONDITIONS AND THE CONTRACT DRAWINGS ARE A PART OF THE SPECIFICATIONS FOR THIS DIVISION OF WORK AND THIS CONTRACTOR SHALL REFER TO THEM FOR INSTRUCTIONS PERTAINING TO HIS WORK.
- B. "THE CONTRACTOR", "THIS CONTRACTOR", AND "EC", AS USED IN THESE DRAWINGS AND SPECIFICATIONS, MEANS THE ELECTRICAL CONTRACTOR. "FURNISH AND INSTALL", "SUPPLY", AND "INSTALL", AS USED IN THESE SPECIFICATIONS, MEANS A COMPLETE AND WORKABLE INSTALLATION BY THE E.C.
- C. WHERE SPECIFICATIONS AND/OR DRAWINGS CONFLICT WITH ANY CODE REQUIREMENT, CODE REQUIREMENTS SHALL BE FOLLOWED.
- D. CODES AND STANDARDS:
1. NYS UNIFORM FIRE PREVENTION AND BUILDING CODE
 2. NFPA STANDARDS
 3. ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES
 4. NYS ENERGY CONSERVATION CONSTRUCTION CODE
 5. NATIONAL ELECTRICAL CODE
- E. THE ELECTRICAL SYSTEMS COVERED BY THIS CONTRACT INCLUDE, BUT ARE NOT LIMITED TO:
1. BRANCH CIRCUIT WIRING AND RACEWAYS
 2. WIRING DEVICES
 3. DISCONNECTS
 4. MOTOR STARTERS AND MOTOR STARTING EQUIPMENT
 5. GROUNDING AND BONDING
 6. LIGHTING CONTROLS
 7. LIGHTING FIXTURES AND LAMPS
 8. ELECTRICAL DISTRIBUTION SYSTEM, INCLUDING OVERCURRENT DEVICES
 9. EXISTING CONSTRUCTION AND COORDINATION OF DEMOLITION WORK
 10. CONNECTIONS TO HVAC, PLUMBING, FIRE PROTECTION, AND ALL OTHER ELECTRICALLY SUPPLIED EQUIPMENT, CONTROLS, CONTROL PANELS, MOTOR STARTERS, MOTOR STARTING EQUIPMENT AND DISCONNECTS NOT FURNISHED UNDER HVAC, PLUMBING, FIRE PROTECTION, OR OTHER CONTRACTS.
 11. FIRE ALARM SYSTEM
- F. PAY FOR ALL PERMITS, INSPECTION FEES, LICENSES AND FOR TESTS WHICH MAY BE REQUIRED IN DETERMINING THE COMPLETENESS OF THE ELECTRICAL WORK.
- G. ALL ELECTRICAL PRODUCTS USED ON THIS PROJECT SHALL BE LISTED BY UNDERWRITER'S LABORATORIES (UL).
- H. ALL ELECTRICAL PRODUCTS USED ON THIS PROJECT SHALL CONFORM TO APPLICABLE STANDARD OF THE NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION (NEMA).
- I. ALL ELECTRICAL INSTALLATION AND PRODUCTS USED ON THIS PROJECT SHALL COMPLY WITH THE NATIONAL ELECTRICAL CODE (NEC).
- J. THE PLANS SHOW THE APPROXIMATE LOCATION OF ALL PARTS OF THE WORK. THE ARCHITECT WILL GIVE EXACT LOCATIONS, WHERE STRUCTURAL CONDITIONS ENCOUNTERED NECESSITATE MINOR CHANGES, THESE SHALL BE MADE WITHOUT CHARGE, BUT MUST MEET WITH THE APPROVAL OF THE ARCHITECT. WHERE MAJOR CHANGES ARE REQUIRED, THEY SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT FOR DECISION BEFORE PROCEEDING WITH THE WORK.
- K. NOTIFY THE ARCHITECT, AND OBTAIN APPROVAL, BEFORE ANY COMPONENTS OF THE ELECTRICAL SYSTEM ARE CONCEALED BY CLOSING OFF AREAS, POURING CONCRETE, ETC.
- L. DETERMINE AND BE RESPONSIBLE FOR PROPER SIZE AND LOCATION OF OPENINGS AND CHASES, AND GIVE GENERAL CONTRACTOR NOTICE OF REQUIREMENTS. INSTALL ALL SLEEVES NECESSARY FOR THE WORK; WHEREVER ANY RACEWAY PASSES THROUGH A WALL, THE OPENING SHALL BE SEALED TIGHT AGAINST THE RACEWAY BY THIS CONTRACTOR. RACEWAYS THROUGH FOUNDATION WALLS AND ROOFS SHALL BE SEALED WATERTIGHT BY THIS CONTRACTOR.
- M. THIS CONTRACTOR SHALL DO ALL NECESSARY CUTTING AND PATCHING WHICH IS NOT CALLED TO BE DONE UNDER ANOTHER DIVISION. ALL CUTTING AND REPAIRING SHALL BE PERFORMED BY SKILLED WORKERS.
- N. PAINT ALL EXPOSED RACEWAYS IN FINISHED ROOMS WITH TWO COATS OF PAINT TO MATCH SURROUNDINGS. INSTALL PANELBOARD TRIMS, CABINETS, ENCLOSURES, ETC., IN SUFFICIENT TIME SO THAT THE PAINTING CONTRACTOR MAY PAINT THESE SURFACES WITH THE WALLS. THIS CONTRACTOR SHALL PAY FOR ALL NECESSARY PAINTING IF THE ABOVE PROCEDURE IS NOT FOLLOWED. THE CONTRACTOR SHALL FURNISH AND INSTALL THE POWER AND LIGHTING REQUIRED FOR THE CONSTRUCTION. THE SCOPE SHALL INCLUDE, BUT NOT LIMITED TO:
1. TEMPORARY POWER DISTRIBUTION
 2. LAMP SOCKETS AND LAMPS
 3. OUTLETS AND CONSTRUCTION EQUIPMENT CONNECTION INCLUDING WELDERS.
 4. REMOVAL OF TEMPORARY DISTRIBUTION AFTER COMPLETION OF CONSTRUCTION.
- O. THE CONTRACTOR SHALL INSTALL HIS RACEWAYS IN SUCH A MANNER THAT THE EXPANSION JOINTS OF THE BUILDING WILL FUNCTION PROPERLY AND NOT STRESS ANY ELECTRICAL RACEWAYS. EXPANSION JOINTS SHALL BE INSTALLED IN ALL RACEWAYS AT THE EXPANSION JOINTS OF THE BUILDING.
- P. BEFORE ORDERING ANY MATERIAL OR DOING ANY WORK THIS CONTRACTOR SHALL VERIFY ALL MEASUREMENTS AT THE BUILDING AND SHALL BE RESPONSIBLE FOR THE CORRECTNESS OF SAME. NO EXTRA CHARGE OR COMPENSATION WILL BE ALLOWED ON ACCOUNT OF DIFFERENCE BETWEEN ACTUAL DIMENSIONS AND THE MEASUREMENTS INDICATED ON THE DRAWINGS; ANY DIFFERENCE WHICH MAY BE FOUND SHALL BE SUBMITTED TO THE ARCHITECT FOR CONSIDERATION BEFORE PROCEEDING WITH THE WORK.
- Q. SUBMITALS: PROVIDE PRODUCT DATA, CATALOG CUT SHEETS WITH MFG. SPECIFICATIONS FOR REVIEW BY ARCH./ENGR. FOR THE FOLLOWING ITEMS:
1. SAFETY DISCONNECT SWITCHES
 2. LIGHTING FIXTURES
 3. LIGHTING CONTROL DEVICES
 4. CONDUCTORS & CABLES
 5. WIRING DEVICES
 6. PANELBOARDS
 7. FIRE ALARM SYSTEM
- R. PROVIDE ELECTRONIC SUBMITTAL COPIES FOR EACH ITEM LISTED ABOVE.
- S. MAINTAIN THROUGHOUT PROJECT A SET OF PLANS WHICH ACCURATELY PORTRAY THE ACTUAL INSTALLATION, INCLUDING LOCATION OF ALL WIRING, EQUIPMENT, CIRCUIT NUMBERS, ETC. TURN OVER TO OWNER AT COMPLETION OF JOB.

RACEWAYS AND FITTINGS

- A. WHERE CALLED FOR ON THE DRAWINGS, FLOOR OUTLET BOXES AND POKE-THROUGH DEVICE SHALL BE AS MANUFACTURED BY HUBBELL, WALKER, LEGRAND.
- B. WIRING AND RACEWAYS SHALL BE CONCEALED IN ALL ROOMS AND SPACES UNLESS OTHERWISE NOTED.
- C. FOR INDOOR USE IN FINISHED ROOMS INSIDE HOLLOW WALL OR CEILING CAVITIES: WIRE IN NM REXFIM CABLE.
- D. FOR USE IN UNFINISHED INTERIOR AREAS: WIRE IN SURFACE MOUNTED EMT CONDUIT, SET SCREW FITTINGS.
- E. WHERE EXPOSED IN EXTERIOR, DAMP/WET LOCATIONS OR WHERE SUBJECT TO PHYSICAL DAMAGE, WIRE IN SURFACE MOUNTED RGS CONDUIT.
- F. FOR UNDERGROUND CONDUIT RUNS, WIRE IN SCHEDULE 80 PVS CONDUIT UNLESS OTHERWISE CALLED FOR ON THE DRAWINGS.
- G. FOR FLOOR PENETRATIONS: WIRE IN RGS.
- H. FOR FINAL CONNECTION IN DAMP OR WET LOCATIONS: LIQUID TIGHT FLEXIBLE METAL CONDUIT, WITH LISTED FITTINGS.
- I. IN ALL INSTANCES, INCLUDE A SEPARATE GREEN INSULATED GROUNDING CONDUCTOR IN EACH RACEWAY, SIZE PER NEC.
- J. FURNISH ALL FITTINGS REQUIRED, BUT NOT LIMITED TO: BUSHINGS TO PREVENT WIRE ABRASION; SINGLE-AND MULTIPLE-GANG BOXES TO ACCOMMODATE DEVICE INSTALLATION; ADAPTERS FROM CONDUIT TO RACEWAY; TRANSITIONS TO BOTH LARGER AND SMALLER SURFACE METAL RACEWAYS; 90 DEGREE ELBOWS, TEES, FIXTURE BOXES, AND FLEXIBLE SECTIONS.
- K. SURFACE METAL RACEWAY AND FITTINGS SHALL MEET ALL REQUIREMENTS OF NEC ARTICLE 352A AND SHALL BE UL LISTED.
- L. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROPER APPLICATION, INSTALLATION, AND LOCATION OF ALL NECESSARY AND REQUIRED INSERTS, SUPPORTS, AND ANCHOR BOLTS, AND FOR A SATISFACTORY RACEWAY SYSTEM UPON COMPLETION OF THE PROJECT.
- M. WHERE ANY COMPONENT OF THE RACEWAY SYSTEM IS DAMAGED PRIOR TO FINAL ACCEPTANCE BY THE OWNER, THIS CONTRACTOR SHALL BE REQUIRED TO REPLACE SAME OR PROVIDE A NEW RACEWAY SYSTEM, AT THE EXPENSE OF THE CONTRACTOR RESPONSIBLE FOR THE DAMAGE.
- N. CONDUITS SHALL BE RUN TO AVOID ADVERSE CONDITIONS SUCH AS HEAT AND MOISTURE AND TO AVOID ALL MATERIALS AND EQUIPMENT OF OTHER TRADES. CONDUITS SHALL MAINTAIN A MINIMUM CLEARANCE OF SIX INCHES FROM ALL HOT WATER PIPES, FLUES, OR AND HIGH TEMPERATURE PIPING OR DUCTWORK. SHOULD IT BE FOUND NECESSARY TO INSTALL CONDUIT CLOSER THAN THIS TO HOT WATER PIPES AN INSULATING COVERING SHALL BE USED TO PROTECT THE CONDUIT FROM HIGH TEMPERATURE.
- O. RACEWAYS SHALL NOT BE SMALLER THAN THE SIZE REQUIRED BY THE NATIONAL ELECTRICAL CODE FOR THE CONDUCTORS ENCLOSED AND SHALL BE LARGER WHERE SO SPECIFIED OR INDICATED ON THE PLANS.
- P. ALL EXPOSED RUNS OF CONDUIT SHALL BE INSTALLED PARALLEL OR PERPENDICULAR TO WALLS OR CEILINGS. SUPPORTS SHALL BE FROM THE MASONRY OR STEEL STRUCTURE RATHER THAN FROM OTHER MECHANICAL WORK SUCH AS DUCTS, PIPING, ETC., IN ACCORDANCE WITH GOOD INDUSTRY PRACTICE IN A MANNER ACCEPTABLE TO THE ARCHITECT.
- Q. SUPPORTS AND ATTACHMENTS PROVIDED SHALL BE SPECIFICALLY DESIGNED FOR THE APPLICATIONS. PERFORATED HANGERS OR WIRE TIE SUPPORTS ARE NOT ACCEPTABLE. ALL HANGERS AND SUPPORTS SHALL HAVE CORROSION RESISTANT FINISH.
- R. ALL CONDUITS PASSING THROUGH WALLS, FLOORS, AND CEILINGS SHALL BE SLEEVED WITH A PIECE OF SCHEDULE 40 GALVANIZED STEEL PIPE WITH PLAIN ENDS. ALL SLEEVES SHALL BE SEALED WATERTIGHT USING A MATERIAL SIMILAR IN APPEARANCE TO THE SURROUNDING AREA OR APPROVED MATERIAL.
- S. CONDUITS EXTENDING THROUGH ROOFS SHALL BE EQUIPPED WITH PITCH POCKETS.
- T. ALL EMPTY RACEWAYS SHALL BE PROVIDED WITH A NYLON PULLWIRE.
- U. ALL CONDUIT PASSING THROUGH A FIRE ZONE SHALL HAVE A FIRE RATED INSTALLATION.
- V. CONDUIT SHALL BE INSTALLED SO THAT A CONTINUOUS GROUNDING SYSTEM WILL BE MAINTAINED FROM THE FURTHERMOST OUTLET TO THE ESTABLISHED WATER PIPE GROUND.
- W. CONDULETS, UNILETS, OR SIMILAR APPROVED TYPE FITTINGS SHALL BE USED ON EXPOSED WORK WHERE CONDUIT CHANGES DIRECTION AND WHERE BENDS WILL NOT MAKE A NEAT JOB.
- X. EXPOSED CONDUIT SHALL BE SECURELY FASTENED TO THE BUILDING AT EIGHT-FOOT MINIMUM INTERVALS, USING APPROVED HANGERS, STRAPS, CLAMPS, OR SCREWS. WOOD PLUGS SHALL NOT BE USED FOR FASTENING PURPOSES. CONDUIT RUN ABOVE HUNG CEILING OR IN CRAWL SPACES SHALL BE SUPPORTED IN THE SAME MANNER AS FOR EXPOSED RUNS. WIRE TIES ARE NOT ACCEPTABLE SUPPORTS.
- Y. CARE SHALL BE EXERCISED TO MAKE CERTAIN THAT THE CONDUIT SYSTEM NOW PLANNED WILL PERMIT REMOVAL OF CONDUCTORS FOR FUTURE CHANGES AS MAY BE REQUIRED. ALTHOUGH UP TO FOUR 90 DEGREE BENDS ARE PERMITTED BY THE NATIONAL ELECTRICAL CODE, THE PRACTICE OF USING MORE THAN THREE 90 DEGREE BENDS PER RUN SHALL BE AVOIDED. PULL BOXES SHALL BE USED IF AT ALL FEASIBLE.
- Z. PULLBOXES SHALL BE INSTALLED AT 100 FOOT INTERVALS IN LONG STRAIGHT RUNS. CLOSE NIPPLES WILL NOT BE PERMITTED.
- AA. CONDUIT SMALLER THAN 1/2" TRADE SIZE SHALL NOT BE USED.
- BB. THE REQUIRED STRENGTH OF THE SUPPORTING EQUIPMENT AND THE SIZE AND TYPE OF ANCHORS SHALL BE BASED ON THE COMBINED WEIGHT OF CONDUIT, HANGERS, AND CONDUCTORS. THE USE OF PERFORATED IRON STRAPS FOR SUPPORTING CONDUITS WILL NOT BE PERMITTED.
- CC. SINGLE RUNS:
1. WHERE CONDUITS ARE RUN INDIVIDUALLY, THEY SHALL BE SUPPORTED BY APPROVED PIPE STRAPS, SECURED BY MEANS OF TOGGLE BOLTS IN HOLLOW MASONRY; EXPANSION SHIELDS AND MACHINE SCREWS OR STANDARD PRESET INSERTS IN CONCRETE OR SOLID MASONRY; MACHINE SCREWS OR BOLTS IN METAL SURFACES; AND WOOD SCREWS IN WOOD CONSTRUCTION. THE USE OF PERFORATED IRON STRAPS WILL NOT BE PERMITTED.
 2. CONDUITS INSTALLED EXPOSED ON THE SURFACE IN DAMP LOCATIONS OR IN REFRIGERATED AREAS SHALL BE PROVIDED WITH CLAMP BACKS UNDER EACH CONDUIT CLAMP TO PREVENT ACCUMULATION OF MOISTURE AROUND THE CONDUITS.
 3. WHERE INDIVIDUAL CONDUITS ARE SUSPENDED FROM THE CEILING THEY SHALL BE SUPPORTED BY HANGERS EQUIVALENT TO STEEL CITY NO. C-149.
- DD. MULTIPLE RUNS:
1. WHERE A NUMBER OF CONDUITS ARE TO BE RUN EXPOSED AND PARALLEL, ONE WITH ANOTHER, THEY SHALL BE GROUPED AND SUPPORTED BY TRAPEZE HANGERS.
 2. HANGER RODS SHALL BE FASTENED TO STRUCTURAL STEEL MEMBERS WITH SUITABLE BEAM CLAMPS, OR TO CONCRETE INSERTS SET FLUSH WITH SURFACE.
- EE. THE CONTRACTOR SHALL FURNISH AND INSTALL JUNCTION BOXES, PULLBOXES, AND CABLE SUPPORT BOXES AS SHOWN ON THE DRAWINGS, SPECIFIED HEREIN, OR AS OTHERWISE REQUIRED. BOXES SHALL BE SECURED IN POSITION INDEPENDENTLY OF CONDUITS ENTERING THEM BY MEANS OF BOLTS, ROD HANGERS, BRACKETS, OR OTHER APPROVED METHODS. OUTLET BOXES SHALL BE SECURELY FASTENED TO CEILINGS, WALLS OR COLUMNS.
- FF. BOXES INSTALLED IN FINISHED CEILINGS, WALLS OR COLUMNS SHALL BE SET SO THAT THE FRONT EDGE OF THE BOX SHALL BE FLUSH WITH FINISHED CEILINGS, WALLS OR COLUMNS.
- GG. UNLESS OTHERWISE NOTED ON THE DRAWINGS OR SPECIFIED HEREIN, RECEPTACLE OUTLET CENTERLINES SHALL BE INSTALLED 18" ABOVE THE FLOOR.
- HH. PROVIDE FIRESTOPPING TO CABLE AND RACEWAY PENETRATIONS OR FIRE-RATED FLOOR AND WALL ASSEMBLIES TO ACHIEVE FIRE-RESISTANCE RATING OF THE ASSEMBLY.

WIRE AND CABLE

- A. ACCEPTABLE MANUFACTURERS SHALL BE ANACONDA, GENERAL ELECTRIC, CERRO, OR SOUTHWIRE.
- B. ALL CONDUCTORS SHALL BY COPPER, WITH 600 VOLT INSULATION, UNLESS OTHERWISE NOTED; STRANDING AND INSULATION TYPES AS FOLLOWS:
- C. BRANCH CIRCUIT FEEDERS
1. #10 AWG AND SMALLER (SOLID OR STRANDED) – TYPE THHN/THWN INSULATION.
 2. #8 AWG AND LARGER (STRANDED) – TYPE THHN/THWN INSULATION.
- D. ALL WIRE AND CABLE SHALL BE NEW, WITHIN ONE YEAR OF MANUFACTURE WHEN DELIVERED TO THE SITE AND BEAR THE UL LABEL, INSULATION TYPE, VOLTAGE, AND MANUFACTURER'S NAME AT REGULAR INTERVALS ON THE INSULATION.
- E. ALL WIRING SHALL BE DONE SO THAT THE SYSTEM WILL BE CONTINUOUSLY POLARIZED THROUGHOUT, FOLLOWING THE COLOR CODING INDICATED IN THE NEC.
- F. ALL CONNECTIONS USING COPPER SHALL BE MADE WITH CONNECTORS THAT ARE DESIGNED AND APPROVED FOR COPPER.
- G. JOINTS, TAPS AND SPLICES OF WIRES OF SIZES #10 AWG AND SMALLER SHALL BE MADE BY MEANS OF "SCOTCHLOK" SPRING CONNECTORS.
- H. JOINTS, TAPS AND SPICES OF WIRES OF SIZE #8 AWG AND LARGER SHALL BE MADE WITH THOMAS AND BETTS ALUMINUM/COPPER COLOR -KEYED COMPRESSION CONNECTORS, INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- I. WIRE SIZES SHALL BE AS SHOWN ON THE DRAWINGS OR SIZED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE.
- J. ALL FEEDER CABLES SHALL BE CONTINUOUS FROM ORIGIN TO EQUIPMENT TERMINATION WITHOUT RUNNING SPLICES IN INTERMEDIATE PULL OR SPLICE BOXES AS FAR AS PRACTICABLE. NO SPLICES ARE ALLOWED IN "C" CONDULETS.
- K. CONDUCTORS SHALL NOT BE SMALLER THAN CODE SIZE FOR THE LOADS BEING HANDLED AND SHALL BE LARGER IF SO INDICATED IN THE PLANS OR SPECIFICATIONS. NO CONDUCTOR SHALL BE LESS THAN #12 AWG EXCEPT FOR CONTROL CIRCUITS, WHICH MAY BE #14 WIRE WHEN INDICATED.
- L. PROVIDE SEPARATE GREEN INSULATED GROUND (EQUIPMENT GROUND) CONDUCTOR IN ALL FEEDERS AND BRANCH CIRCUITS.
- WIRING DEVICES**
- A. FOR FINISHED AREAS, USE DEVICES, COLOR AS SELECTED BY ARCHITECT, WITH MATCHING WALL PLATE.
- B. FOR UNFINISHED DRY INTERIOR SPACES, USE DEVICES IN STEEL UTILITY BOXES WITH MATCHING RAISED STEEL DEVICE COVERS.
- C. FOR INTERIOR AND EXTERIOR WET LOCATIONS, USE DEVICES INSTALLED WITH AN OUTLET ENCLOSURE CLEARLY MARKED "SUITABLE FOR WET LOCATIONS WHILE IN USE", AS MANUFACTURED BY TAYMAC CORP., WITH PUSH-BUTTON RELEASE.
- D. **RECEPTACLES:**
- 15A, 125V DUPLEX RECEPTACLE: HUBBELL #DR15TR
20A, 125V DUPLEX RECEPTACLE: HUBBELL #DR20TR
15A, 125V DUPLEX GFI RECEPTACLE: HUBBELL #GFSG53621
15A, 125V HEAVY DUTY GRADE DUPLEX WEATHER RESISTANT GFI RECEPT.: HUBBELL #GFSG52621 OR APPR. EQUAL
20A, 125V HEAVY DUTY GRADE DUPLEX WEATHER RESISTANT GFI RECEPT.: HUBBELL #GFSG53621 OR APPR. EQUAL
- E. **SWITCHES:**
- 20A, 120/277V A.C. TOGGLE SWITCH: HUBBELL #DS120
20A, 120/277V A.C. THREE-WAY SWITCH: HUBBELL #DS320
20A, 120/277V A.C. FOUR-WAY SWITCH: HUBBELL #DS420
- F. **MOUNTINGS:** MOUNT DEVICES IN SINGLE OR GANGED ARRANGEMENT, AS CALLED FOR ON THE DRAWINGS. PROVIDE APPROPRIATE STEEL BACKBOX AS REQUIRED; USE SINGLE OR MULTIPLE DEVICE COVERS, AS REQUIRED. MULTIPLE DEVICES TO BE EQUALLY SPACED, AND ALIGNED STRAIGHT SO AS TO ALLOW DEVICE PLATE TO FIT SNUGLY AND PROPERLY.
- G. WHERE MOUNTING ON MILLWORK OR OTHER EQUIPMENT, VERIFY PROPER ROUGH-IN DIMENSIONS WITH ARCHITECT.
- H. DEVICES TO BE INSTALLED AT HEIGHTS TO COMPLY WITH APPLICABLE ADA REQUIREMENTS. REFER TO TYPICAL MOUNTING HEIGHTS ON DRAWINGS FOR FURTHER REQUIREMENTS.
- I. MANUFACTURERS: HUBBELL, PASS & SEYMOUR, LEVITON, COOPER.

SAFETY DISCONNECT SWITCHES

- A. DISCONNECTION SWITCH RATING SHALL BE AS SHOWN ON THE DRAWINGS, HEAVY-DUTY, "QUICK-MAKE, QUICK-BREAK", SAFETY SWITCHES WITH INTERLOCKING COVER, CONSTRUCTED OF CODE GAGE STEEL (UL 98) ENCLOSURES SHALL BE TREATED WITH RUST INHIBITING PHOSPHATE AND FINISHED IN GRAY BAKED ENAMEL.
- B. DISCONNECTS SHALL BE FUSED OR NON-FUSED AS INDICATED ON THE DRAWINGS, OR AS REQUIRED BY NEC. NUMBER OF POLES, WITH OR WITHOUT SOLID NEUTRAL, SHALL BE AS INDICATED ON THE DRAWINGS, OR AS REQUIRED.
- C. ENCLOSURES FOR INDOOR USE SHALL BE NEMA 1 UNLESS NOTED OTHERWISE FOR DAMP/WET LOCATIONS. ENCLOSURES FOR EXTERIOR USE SHALL BE NEMA 3R, ENCLOSURES FOR HOSE DOWN/DUST TIGHT LOCATIONS SHALL BE NEMA 4X.
- D. DISCONNECTS SHALL REQUIRE THE USE OF A SCREWDRIVER FOR ACCESS TO INTERIOR WITHOUT OPENING CONTACTS.
- E. DISCONNECTS SHALL HAVE PROVISIONS FOR PADLOCKING THE SWITCH IN THE "OFF", OR "OPEN" POSITION.
- F. ACCEPTABLE MANUFACTURERS ARE SQUARE D, CUTLER-HAMMER, OR GENERAL ELECTRIC.
- G. FURNISH A SAFETY DISCONNECT DEVICE ON ALL EQUIPMENT CONNECTIONS WHERE INDICATED ON THE DRAWINGS, OR AS REQUIRED BY CODE.
- H. DISCONNECTS SHALL BE MOUNTED TO PERMANENT STRUCTURAL ELEMENTS WITH APPROVED FASTENING MEANS. DISCONNECTS SHALL NOT BE FASTENED BY WELDING THE ENCLOSURE TO ITS DESIGNATED STRUCTURAL SUPPORT. BEAM CLAMPS, UNISTRUT AND BOLTED WASHERS COMPRISE ACCEPTABLE FASTENING MEANS.
- I. NAMEPLATES SHALL BE PLASTIC LAMINATE WITH WHITE BACKGROUND AND 1/4" BLACK ENGRAVED LETTERS WITH THE TITLE OF THE EQUIPMENT THAT IS FED. NAMEPLATES SHALL BE ATTACHED USING RIVETS OR NUTS, WASHERS, AND BOLTS.

CABINETS, BOXES, AND FITTINGS

- A. USE SHEET STEEL JUNCTION, OUTLET AND PULL BOXES SIZED PER NEC IN ALL DRY LOCATIONS.
- B. USE CAST BOXES FOR EXTERIOR USE, WHERE IN CONCRETE FLOORS, AND IN ALL DAMP OR WET LOCATIONS.
- C. USE STEEL OR MALLEABLE IRON FITTINGS SPECIFICALLY DESIGNED FOR EACH RACEWAY TYPE, AS DICTATED BY GOOD PRACTICE.
- D. IN ALL CASES, ALL CABINETS, JUNCTION AND OUTLET BOXES SHALL BE ACCESSIBLE.

ELECTRICAL CONNECTIONS FOR EQUIPMENT

- A. FIXED EQUIPMENT REQUIRING ATTACHMENT PLUGS SHALL BE PROVIDED WITH APPROPRIATE RECEPTACLE TO MATCH PLUG.
- B. FIXED EQUIPMENT REQUIRING DIRECT WIRED CONNECTIONS SHALL BE PROVIDED WITH LOCAL JUNCTION BOX, AND FLEXIBLE NONMETALLIC CONDUIT, OR LIQUID TIGHT FLEXIBLE NONMETALLIC CONDUIT CONNECTIONS TO EQUIPMENT.
- C. PROVIDE SEPARATE FUSIBLE DISCONNECT FOR EQUIPMENT NOT FURNISHED WITH INTEGRAL OR FACTORY FURNISHED DISCONNECTING MEANS.
- D. PROVIDE MOTOR STARTER FOR EQUIPMENT NOT FURNISHED WITH FACTORY STARTER.
- NEW LOAD CENTERS**
- A. PHASE, NEUTRAL AND GROUND BUSES SHALL BE COPPER, AND PHASE BUSES SHALL EXTEND THE ENTIRE HEIGHT OF PANELBOARD. CIRCUIT BREAKERS CONNECTIONS TO THE BUS SHALL BE: BOLT-ON, DOUBLE ROW ARRANGEMENT, DISTRIBUTED PHASE BUS TYPE.
- B. CIRCUIT BREAKERS SHALL BE MOLDED CASE, THERMAL MAGNETIC, BOLT-ON TYPE, DEAD FRONT DESIGN, WITH QUICK-MAKE, QUICK-BREAK, COMMON TRIP TYPE SINGLE TOGGLE OPERATING MECHANISMS, 1, 2, OR 3 POLE, AND HACR LISTED WHEN USED FOR HVAC EQUIPMENT, SIZED PER PANELBOARD SCHEDULE.
- C. BACKBOXES SHALL BE FABRICATED FROM GALVANIZED, CODE GAUGE, SHEET STEEL, MEETING OR EXCEEDING NECESSARY REQUIREMENT FOR WIRE BENDING SPACE, WITHOUT KNOCKOUTS.
- D. COVERS SHALL BE DEAD FRONT DESIGN, WITH HINGED DOOR, CONCEALED FASTENERS, FABRICATED FROM CODE GAGE STEEL WITH POINTED ENAMEL FINISH, FLUSH LOCK AND CATCH.
- E. PANELBOARD DIRECTORY CARD, WITH CLEAR PLASTIC COVER, SHALL BE PROVIDED ON BACK OR DOOR. CONTRACTOR SHALL COMPLETE TYPE-WRITTEN DIRECTORY CARD, WITH CIRCUIT BREAKER NUMBERS CROSS REFERENCED TO THEIR RESPECTIVE LOAD(S), BY LOAD TYPE AND ROOM OR SPACE NAME AND NUMBER.
- F. PROVIDE PERMANENT LAMACOID OR EQUAL TYPE LABEL INSIDE PANELBOARD DOOR, IDENTIFYING PANELBOARD NAME.
- G. DESIGN EQUIPMENT SHALL BE SQUARE D, SIEMENS, EATON/CUTLER HAMMER OR GENERAL ELECTRIC.
- H. LOAD BALANCING: AFTER SUBSTANTIAL COMPLETION, BUT NOT MORE THAN 60 DAYS AFTER FINAL ACCEPTANCE, MEASURE LOAD BALANCING AND MAKE CIRCUIT CHANGES.

1. MEASURE AS DIRECTED DURING PERIOD OF NORMAL SYSTEM LOADING.
2. PERFORM LOAD-BALANCING CIRCUIT CHANGES OUTSIDE NORMAL OCCUPANCY/WORKING SCHEDULE OF THE FACILITY AND AT TIME DIRECTED. AVOID DISRUPTING CRITICAL 24-HOUR SERVICES SUCH AS FAX MACHINES AND ON-LINE DATA PROCESSING, COMPUTING, TRANSMITTING, AND RECEIVING EQUIPMENT.
3. AFTER CIRCUIT CHANGES, RECHECK LOADS DURING NORMAL LOAD PERIOD. RECORD ALL LOAD READINGS BEFORE AND AFTER CHANGES AND SUBMIT TEST RECORDS.
4. TOLERANCE: DIFFERENCE EXCEEDING 20 PERCENT BETWEEN PHASE LOADS, WITHIN A PANELBOARD, IS NOT ACCEPTABLE. REBALANCE AND RECHECK AS NECESSARY TO MEET THIS MINIMUM REQUIREMENT.

INFRARED SCANNING: PERFORM THE FOLLOWING INFRARED SCAN TESTS AND INSPECTIONS AND PREPARE REPORTS:

- I.
1. INITIAL INFRARED SCANNING: AFTER SUBSTANTIAL COMPLETION, BUT NOT MORE THAN 60 DAYS AFTER FINAL ACCEPTANCE, PERFORM AN INFRARED SCAN OF EACH PANELBOARD. REMOVE FRONT PANELS SO JOINTS AND CONNECTIONS ARE ACCESSIBLE TO PORTABLE SCANNER.
 2. FOLLOW-UP INFRARED SCANNING: PERFORM AN ADDITIONAL FOLLOW-UP INFRARED SCAN OF EACH PANELBOARD 11 MONTHS AFTER DATE OF SUBSTANTIAL COMPLETION.
 3. INSTRUMENTS AND EQUIPMENT: USE AN INFRARED SCANNING DEVICE DESIGNED TO MEASURE TEMPERATURE OR TO DETECT SIGNIFICANT DEVIATIONS FROM NORMAL VALUES.

GROUNDING AND BONDING

- A. GROUND SERVICE, EQUIPMENT, CIRCUITS PER NEC. USE COPPER CONDUCTORS.
- B. PROVIDE SEPARATE GROUND WIRE FOR EACH NEW BRANCH CIRCUIT CONDUIT.
- C. COMPLY WITH NEC ARTICLE 250.

LIGHTING

- A. PROVIDE AND INSTALL ITEMS AS SPECIFIED HEREIN AND LISTED ON THE LIGHTING FIXTURE SCHEDULE ON THE DRAWINGS.
- B. CATALOG NAMES AND NUMBERS USED IN THE LIGHTING FIXTURE SCHEDULE ARE TO ESTABLISH A STANDARD OF QUALITY AND SHALL NOT BE CONSTRUED AS LIMITING COMPETITION.
- C. IF ALTERNATED, OR OPTIONAL, METHODS ARE PROPOSED AS SUBSTITUTION FOR ANY ONE OF THE LIGHTING FIXTURES, THEY MUST BE EQUAL IN DESIGN AND QUALITY, AS DETERMINED BY THE ARCHITECT/ENGINEER. THE DATA SUBMITTED MUST INCLUDE A DESCRIPTION OF THE LIGHTING FIXTURE, LENS, BALLAST, SHEET METAL GAGE, PHOTOMETRIC DATA, ETC.
- D. UPON REQUEST OF THE ENGINEER, A SAMPLE OF THE PROPOSED SUBSTITUTION SHALL BE PROVIDED.
- E. FURNISH AND INSTALL ALL LIGHTING FIXTURES COMPLETE WITH LAMPS. PROVIDE 10% ADDITIONAL LAMPS FOR EACH TYPE OF LAMP REQUIRED ON PROJECT AND TURN OVER TO OWNER.
- F. ALL LIGHTING FIXTURES SHALL CARRY THE UNDERWRITER'S LABEL OF APPROVAL.
- G. FIXTURES SHALL BE FREE OF IMPERFECTIONS, HANDLING, OR INSTALLATION DAMAGE.
- H. OBTAIN EXACT LOCATION OF ALL CEILING OUTLETS FROM THE ARCHITECT.
- I. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FIT OF ALL LIGHTING FIXTURES INTO THE ACTUAL CEILING INSTALLED.
- J. ALL WIRING WITHIN EACH LIGHTING FIXTURE SHALL BE CONTAINED IN METALLIC WIRING CHANNEL AND NOT IN THE LAMP CHAMBER.
- K. LED LIGHTING FIXTURES – PROVIDE "LIGHTING FACTS" INFORMATION SHEETS. PROVIDE LED COLOR TEMPERATURE PER DRAWINGS, CRI 80 (MINIMUM).
- LED FIXTURES SHALL BE TESTED IN ACCORDANCE WITH LM-79, TM21. PROJECTED LIFE OF OVER 75,000 HOURS AT 50° C.
- L. LED CHIPS/MODULES SHALL BE TESTED IN ACCORDANCE WITH LM-80 TESTING STANDARDS.
- M. CONFIRM COMPATIBILITY AND INTERFACE OF OTHER MATERIALS WITH LUMINAIRE AND CEILING SYSTEM. REPORT DISCREPANCIES TO THE ENGINEER/ARCHITECT AND DEFER ORDERING UNTIL CLARIFIED.
- N. COORDINATE WITH OTHER TRADES TO AVOID CONFLICTS BETWEEN LUMINARIES, SUPPORTS, FITTINGS, AND MECHANICAL EQUIPMENT.
- O. IT WILL BE THE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR TO VERIFY, WITH THE CONSTRUCTION CONTRACTOR, THE TYPES OF CEILINGS IN ALL ROOMS HAVING TROFFERS, AS TO THE TYPE OF TROFFER CONSTRUCTION REQUIRED TO MATCH THE CEILING CONSTRUCTION
- P. ALL METAL PARTS SHALL BE GROUNDED AS A COMMON UNIT.
- Q. SUPPORT LUMINARIES DIRECTLY FROM BUILDING STRUCTURE BY ROD HANGERS AND INSERTS.
- R. INSTALL RECESSED LUMINARIES TO PERMIT REMOVAL FROM BELOW, TO GAIN ACCESS TO OUTLET OR PRE-WIRED LIGHTING FIXTURE BOX.

DRAWING SUBMISSION STATUS: [] NOT FOR CONSTRUCTION [] SCHEMATIC DESIGN [] DESIGN DEVELOPMENT [] CONSTRUCTION DOCUMENTS [X] ISSUED FOR CONSTRUCTION

PROJECT NAME/LOCATION: DESCRIPTION [NEW CONSTRUCTION] 68 PULASKI STREET - SINGLE FAMILY HOME		TREDO ENGINEERING STRUCTURAL 7555 SENECA ST., #202 BUFFALO, NY 14210 (716) 876 - 7147	BUFFALO ENG., PC MEP 172 Allen Street, Buffalo, New York 14201 716.885.0743 • F: 716.885.6414 HHLArchitects.com	PROJECT NUMBER: 2317.006	
ARCHITECT OF RECORD		HHL Architects		PROJECT NUMBER: 2317.006	
DRAWING TITLE ELECTRICAL SPECIFICATIONS		REVISIONS AFTER ISSUANCE		ISSUE DATE: 09.19.2025	
NO.		DATE		DRAWING NUMBER E-201	
DESCRIPTION		DESCRIPTION			
SEAL					